

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Press 8 Handling System

1 Hydraulic Power Pack

Fluid PETRO CANADA HYDREX AW 46 (1000 LTR)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

R)				May2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0796110		
Sample Date		Client Info		16 May 2023		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>20	<1		
Chromium	ppm	ASTM D5185(m)	>20	0		
Nickel	ppm	ASTM D5185(m)	>20	0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>20	<1		
Lead	ppm	ASTM D5185(m)	>20	<1		
Copper	ppm	ASTM D5185(m)	>20	5		
Tin	ppm	ASTM D5185(m)	>20	0		
Antimony	ppm	ASTM D5185(m)	200	<1		
/anadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium		ASTM D5185(m)		0		
	ppm					
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	0	8		
Barium	ppm	ASTM D5185(m)	0	0		
Volybdenum	ppm	ASTM D5185(m)	0	3		
Manganese	ppm	ASTM D5185(m)	0	0		
Vagnesium	ppm	ASTM D5185(m)	0	25		
Calcium	ppm	ASTM D5185(m)	50	124		
Phosphorus	ppm	ASTM D5185(m)	330	374		
Zinc	ppm	ASTM D5185(m)	430	432		
Sulfur	ppm	ASTM D5185(m)	760	1019		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS	\$	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>15	3		
Sodium	ppm	ASTM D5185(m)		<1		
Potassium	ppm	ASTM D5185(m)	>20	0		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	1764		
Particles >6μm		ASTM D7647	>1300	421		
Particles >14µm		ASTM D7647	>160	47		
Particles >21µm		ASTM D7647		15		
Particles >38µm		ASTM D7647	>10	1		
Particles >71µm		ASTM D7647	>3	0		
				~		
			>19/17/14	18/16/13		
Oil Cleanliness 32:25) Rev: 1		ISO 4406 (c)	>19/17/14	18/16/13		 By: Jesse Wes



OIL ANALYSIS REPORT

