

OIL ANALYSIS REPORT

Sample Rating Trend





Blower Fluid {not provided} (300 LTR)

DIAGNOSIS

Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

Fluid Condition

Viscosity of sample indicates oil is within ISO 46 range, advise investigate. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

				May2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PP		
Sample Date		Client Info		10 May 2023		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method		NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>20	0		
Chromium	ppm	ASTM D5185(m)	>20	0		
Nickel	ppm	ASTM D5185(m)	>20	<1		
Titanium	ppm	ASTM D5185(m)	~=	0		
Silver		ASTM D5185(m)		0		
Aluminum	ppm	. ,	> 20	0		
	ppm	ASTM D5185(m)		-		
Lead	ppm	ASTM D5185(m)	>20	<1		
Copper	ppm	ASTM D5185(m)	>20	4		
Tin	ppm	ASTM D5185(m)	>20	0		
Antimony	ppm	ASTM D5185(m)		<1		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		<1		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		0		
Calcium	ppm	ASTM D5185(m)		63		
Phosphorus	ppm	ASTM D5185(m)		365		
Zinc	ppm	ASTM D5185(m)		415		
Sulfur	ppm	ASTM D5185(m)		872		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>15	<1		
Sodium	ppm	ASTM D5185(m)		0		
Potassium	ppm	ASTM D5185(m)	>20	0		
FLUID CLEANLIN		method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>2500	695		
•		ASTM D7647	>640	262		
Particles >6um		ASTM D7647 ASTM D7647	>80	30		
			>00	30		
Particles >14µm			> 20	0		
Particles >14µm Particles >21µm		ASTM D7647		9		
Particles >14µm Particles >21µm Particles >38µm		ASTM D7647 ASTM D7647	>4	1		
Particles >6µm Particles >14µm Particles >21µm Particles >38µm Particles >71µm Oil Cleanliness		ASTM D7647	>4			



OIL ANALYSIS REPORT

Particle Trend	FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
	Acid Number (AN)	mg KOH/g	ASTM D974*		0.37		
14μm	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	Visual*	NONE	NONE		
	Yellow Metal	scalar	Visual*	NONE	NONE		
	Precipitate	scalar	Visual*	NONE	NONE		
0/23	Silt	scalar	Visual*	NONE	NONE		
May10/23	Debris	scalar	Visual*	NONE	NONE		
Acid Number	Sand/Dirt	scalar	Visual*	NONE	NONE		
	Appearance Odor	scalar	Visual* Visual*	NORML NORML	NORML NORML		
	Emulsified Water	scalar scalar	Visual*	NURIVIL	NEG		
	Free Water	scalar	Visual*		NEG		
	FLUID PROPERT		method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D7279(m)		43.2		
0,023 +	SAMPLE IMAGE		method	limit/base	current	history1	history2
czioli/wew Viscosity @ 40°C Abnormal	Color					no image	no image
Abnormal	Bottom					no image	no image
23 E	GRAPHS				Dautiala Caunt		
May10/23	Ferrous Alloys			491,520	Particle Count		T ²⁶
	iron chromium			122,880			-24
Particle Trend	E 5-			30,720	Severe		-22
Approximate 4 µm	0			7.090			
ι14μm	May10/23			0/2:	Abnormal		-20 -18 -16 -14
	—			Mad 1.920-		•	-10
	Non-ferrous Meta	s		offined jo	1.		-16
	copper						and the second
0.12 2.5 2.5 2.5 2.5 2.5 2.5 2.5 2.5 2.5 2.	E 5-			a 30-			-12 8
CC 01				8			-10
	0/23			2/0			
	May1			2 Way10/23	c	14µ 21µ	284 76
	Viscosity @ 40°C			4	^{µ 6µ} Acid Number	14μ 21μ	38µ 71µ
	_100 Abnormal			(PHO) 0.40 0.30 0.30	1		
	200 200 200 200 200 200 200 200			E 0.30			
	60						
	40 53			0.00			
	May10/22			May10/23	May 1 0/23		May10/23
Iso 17025:2017 Accredited Laboratory To discuss this sample report,	: WearCheck - C8-117 : PP : 02558093 : 5579133 : IND 2	Recei Teste Diagr	ved : 17 d : 18 nosed : 18	lgton, ON L7L 7 May 2023 3 May 2023 May 2023 - Kevi 1.	5H9 DUFFIN on Marson AL.ROFF	PI Cor EY@REGION.D	URHAM) WPC MCKAY ROA CKERING, O CA L1W 3A ntact: Al Roffe

Contact/Location: AI Roffey - DUFPIC