

FUEL REPORT

AIRBUS N316FA

Component Left Jet Fuel

JET FUEL Type A (--- GAL)

Sample Rating Trend



Recommendation

Laboratory test indicate that this fuel is suitable for use and meets all test requirements. Resample at the next service interval to monitor.

{not applicable}

Contamination

The water content is negligible. The fuel phase was tested for microbes, as there was no separate water phase present in the sample. The MicrobMonitor2 test kit was used to test for microbiological contamination in the sample. There is no indication of any contamination in the jet fuel.


Fluid Condition

All laboratory tests indicate that this sample appears to be Jet Fuel Type A.

				Jun 2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0824757		
Sample Date		Client Info		15 Jun 2023		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
PHYSICAL PROP	ERTIES	method	limit/base	current	history1	history2
Specific Gravity		ASTM D1298*		0.815		
Fuel Color	text	Visual Screen*		Clear		
Visc @ 40°C	cSt	ASTM D7279(m)	<8.0	1.4		
Pensky-Martens Flash Point	°C	ASTM D7215*	38	54.3		
Pour Point	°C	ASTM D97*	-45	-66		
SULFUR CONTE	NΤ	method	limit/base	current	history1	history2
Sulfur	ppm	ASTM D5185(m)	<3000	387		
DISTILLATION		method	limit/base	current	history1	history2
Initial Boiling Point	°C	ASTM D2887*		162		
5% Distillation Point	°C	ASTM D2887*		177		
10% Distill Point	°C	ASTM D2887*	205	180		
15% Distillation Point	°C	ASTM D2887*		184		
20% Distill Point	°C	ASTM D2887*		188		
30% Distill Point	°C	ASTM D2887*		194		
40% Distill Point	°C	ASTM D2887*		201		
50% Distill Point	°C	ASTM D2887*		209		
60% Distill Point	°C	ASTM D2887*		217		
70% Distill Point	°C	ASTM D2887*		226		
80% Distill Point	°C	ASTM D2887*		238		
85% Distillation Point		ASTM D2887*		246		
90% Distill Point	°C	ASTM D2887*		254		
95% Distillation Point		ASTM D2887*		267		
Final Boiling Point	°C	ASTM D2887*	300	287		
IGNITION QUALIT	ГΥ	method	limit/base	current	history1	history2
API Gravity		ASTM D1298*	44	42		
Cetane Index		ASTM D4737*		43		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	<1.0	0		
Sodium	ppm	ASTM D5185(m)	< 0.1	0		
Potassium	ppm	ASTM D5185(m)	<0.1	0		
Water	%	ASTM D6304*	< 0.05	0.003		
ppm Water	ppm	ASTM D6304*	<500	28.0		
MICROBIAL		method	limit/base	current	history1	history2
Microbes	CFU/L	ASTM D6469*	>=100000	0		



FUEL REPORT





CALA ISO 17025:2017 Accredited Laboratory

Laboratory Sample No. Lab Number Unique Number

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9

: WC0824757

: 02565174 : 5594215

Received Diagnosed

: 19 Jun 2023 : 23 Jun 2023 Diagnostician : Kevin Marson

Test Package: FUEL (Additional Tests: CC Flash, GC-PercFuel) To discuss this sample report, contact Customer Service at 1-800-268-2131.

Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

KF Aero 9500 Airport Road Mount Hope, ON CA LOR 1W0 Contact: Justin Lewis j.lewis@kfaero.ca T: (905)679-3313

F: (905)679-4921

Contact/Location: Justin Lewis - KELMOU