




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
BROWNING 215 25:1 #23 SCREW (S/N 525623)

Component
Reduction Gear

Fluid
MOBIL MOBILGEAR SHC 220 (9 LTR)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		WC0750561	WC938372	WC925156
Sample Date	Client Info		09 Aug 2023	13 Aug 2015	03 Nov 2014
Machine Age	hrs	Client Info	0	15382	10713
Oil Age	hrs	Client Info	0	15382	10713
Oil Changed	Client Info		Not Changed	Changed	Changed
Sample Status			NORMAL	ABNORMAL	ABNORMAL

WEAR METALS

	method	limit/base	current	history1	history2
PQ	ASTM D8184*		40	40	▲ 270
Iron	ppm	ASTM D5185(m)	134	59	▲ 467
Chromium	ppm	ASTM D5185(m)	<1	<1	1
Nickel	ppm	ASTM D5185(m)	<1	<1	0
Titanium	ppm	ASTM D5185(m)	0	0	<1
Silver	ppm	ASTM D5185(m)	0	0	0
Aluminum	ppm	ASTM D5185(m)	<1	<1	<1
Lead	ppm	ASTM D5185(m)	0	0	0
Copper	ppm	ASTM D5185(m)	<1	<1	1
Tin	ppm	ASTM D5185(m)	0	0	<1
Antimony	ppm	ASTM D5185(m)	0	0	0
Vanadium	ppm	ASTM D5185(m)	0	0	0
Beryllium	ppm	ASTM D5185(m)	0	0	0
Cadmium	ppm	ASTM D5185(m)	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	<1	<1	1
Barium	ppm	ASTM D5185(m)	0	0	<1
Molybdenum	ppm	ASTM D5185(m)	<1	0	0
Manganese	ppm	ASTM D5185(m)	1	<1	2
Magnesium	ppm	ASTM D5185(m)	<1	<1	11
Calcium	ppm	ASTM D5185(m)	20	4	5
Phosphorus	ppm	ASTM D5185(m)	466	426	465
Zinc	ppm	ASTM D5185(m)	2	2	17
Sulfur	ppm	ASTM D5185(m)	1772	1909	2043
Lithium	ppm	ASTM D5185(m)	<1	<1	3

CONTAMINANTS




	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	47	35	▲ 86
Sodium	ppm	ASTM D5185(m)	0	0	0
Potassium	ppm	ASTM D5185(m)	0	<1	2

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*	0.87	0.78	0.58




OIL ANALYSIS REPORT








VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE	NONE ▲ LIGHT
Yellow Metal	scalar	Visual*	NONE	NONE	NONE
Precipitate	scalar	Visual*	NONE	NONE	NONE
Silt	scalar	Visual*	NONE	NONE	NONE
Debris	scalar	Visual*	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	NORML	NORML
Odor	scalar	Visual*	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	NEG	NEG	NEG
Free Water	scalar	Visual*	NEG	NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	217	▲ 176	221

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : WC0750561 **Received** : 11 Aug 2023
Lab Number : **02575478** **Diagnosed** : 11 Aug 2023
Unique Number : 5620529 **Diagnostician** : Wes Davis
Test Package : IND 2 (Additional Tests: TAN Man)

CARMEUSE LIME CANADA LTD.
 BOX 1690,, HWY 17 EAST
 BLIND RIVER, ON
 CA P0R 1B0
 Contact: Rejean Baillargeon
 rejean.baillargeon@carmeuse.ca
 T: (705)849-2201
 F: (705)849-2355

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.