




PROBLEM SUMMARY




Sample Rating Trend

DEGRADATION

Area
Direct Strip Mill/Caster
 Machine Id
CH1 HYDRAULIC SYSTEM (DSC024) (S/N 1000024394)
 Component
Hydraulic System
 Fluid
HOUGHTON HOUGHTON SAFE 616 (3080 LTR)



COMPONENT CONDITION SUMMARY



RECOMMENDATION

Due to the low reserve alkalinity it is advised that you contact HOUGHTON to assist in restoring the proper amine concentration. We recommend you service the filters on this component. We recommend an early resample to monitor this condition.

PROBLEMATIC TEST RESULTS

Sample Status			ABNORMAL	ABNORMAL	ABNORMAL
Particles >14µm	ASTM D7647	>20	▲ 27	16	15
Particles >21µm	ASTM D7647	>4	▲ 9	7	5
Oil Cleanliness	ISO 4406 (c)	>16/14/11	▲ 16/14/12	18/15/11	15/13/11
Alkiline Reserve (Oils)	ml KOH/g	ASTM D1121* 150	▲ 123	142	▲ 125
Visc @ 40°C	cSt	ASTM D7279(m)	▲ 33.2	▲ 33.5	▲ 33.7

Customer Id: ALGSSM
 Sample No.: WC0813751
 Lab Number: 02575522
 Test Package: IND 2



To manage this report scan the QR code

To discuss the diagnosis or test data:
 Kevin Marson +1 (289)291-4644 x4644
Kevin.Marson@wearcheck.com

To change component or sample information:
 Gloria Gonzalez +1 (289)291-4643 x4643
gloria.gonzalez@wearcheck.com

RECOMMENDED ACTIONS

Action	Status	Date	Done By	Description
Change Filter	---	---	?	We recommend you service the filters on this component.
Resample	---	---	?	We recommend an early resample to monitor this condition.
Contact Required	---	---	?	Due to the low reserve alkalinity it is advised that you contact HOUGHTON to assist in restoring the proper amine concentration.

HISTORICAL DIAGNOSIS

21 Jun 2023 Diag: Kevin Marson

VISCOSITY



We recommend you service the filters on this component. We recommend an early resample to monitor this condition. All component wear rates are normal. There is a moderate amount of silt (particulates < 14 microns in size) present in the oil. The system cleanliness is above the acceptable limit for the target ISO 4406 cleanliness code. Viscosity of sample indicates oil is within ISO 32 range, advise investigate. The AN level is acceptable for this fluid. The pH level of this fluid is within the acceptable limits. The reserve alkalinity of this fluid is acceptable. The water concentration level is acceptable for this fluid. The oil is still serviceable provided that the contaminant(s) can be reduced to acceptable levels.

view report



16 May 2023 Diag: Kevin Marson

DEGRADATION



Due to the low reserve alkalinity it is advised that you contact HOUGHTON to assist in restoring the proper amine concentration. We recommend an early resample to monitor this condition. All component wear rates are normal. The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The reserve alkalinity of this fluid is lower than acceptable. Viscosity of sample indicates oil is within ISO 32 range, advise investigate. The AN level is acceptable for this fluid. The pH level of this fluid is within the acceptable limits. The water concentration level is acceptable for this fluid.

view report



18 Apr 2023 Diag: Kevin Marson

DEGRADATION



Due to the low reserve alkalinity it is advised that you contact HOUGHTON to assist in restoring the proper amine concentration. We recommend an early resample to monitor this condition. Please contact your representative for information regarding the proper sampling kits for your service. NOTE: We recommend using IND 3 test kits, this testkit includes Analytical Ferrography which provides a detailed morphological analysis of wear particles present in the fluid. Component wear rates appear to be normal (unconfirmed). The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable. The reserve alkalinity of this fluid is lower than acceptable. Viscosity of sample indicates oil is within ISO 32 range, advise investigate. The AN level is acceptable for this fluid. The pH level of this fluid is within the acceptable limits. The water concentration level is acceptable for this fluid.

view report






OIL ANALYSIS REPORT

Sample Rating Trend

DEGRADATION

Area
Direct Strip Mill/Caster
 Machine Id
CH1 HYDRAULIC SYSTEM (DSC024) (S/N 1000024394)
 Component
Hydraulic System
 Fluid
HOUGHTON HOUGHTON SAFE 616 (3080 LTR)



DIAGNOSIS

Recommendation

Due to the low reserve alkalinity it is advised that you contact HOUGHTON to assist in restoring the proper amine concentration. We recommend you service the filters on this component. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

There is a light amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition

The reserve alkalinity of this fluid is lower than acceptable. Viscosity of sample indicates oil is within ISO 32 range, advise investigate. The AN level is acceptable for this fluid. The pH level of this fluid is within the acceptable limits. The water concentration level is acceptable for this fluid.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		WC0813751	WC0780824	WC0780868
Sample Date	Client Info		09 Aug 2023	21 Jun 2023	16 May 2023
Machine Age	hrs	Client Info	0	0	0
Oil Age	hrs	Client Info	0	0	0
Oil Changed	Client Info		N/A	N/A	N/A
Sample Status			ABNORMAL	ABNORMAL	ABNORMAL

WEAR METALS

	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185(m)	>20	0	<1	6
Chromium	ppm	ASTM D5185(m)	>20	0	<1	<1
Nickel	ppm	ASTM D5185(m)	>20	0	0	0
Titanium	ppm	ASTM D5185(m)		0	0	0
Silver	ppm	ASTM D5185(m)		0	0	2
Aluminum	ppm	ASTM D5185(m)	>20	0	0	<1
Lead	ppm	ASTM D5185(m)	>20	0	0	0
Copper	ppm	ASTM D5185(m)	>20	0	2	3
Tin	ppm	ASTM D5185(m)	>20	<1	0	0
Antimony	ppm	ASTM D5185(m)		0	0	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
Beryllium	ppm	ASTM D5185(m)		0	0	0
Cadmium	ppm	ASTM D5185(m)		0	0	0

ADDITIVES

	method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185(m)		0	<1	3
Barium	ppm	ASTM D5185(m)		1	0	0
Molybdenum	ppm	ASTM D5185(m)		0	<1	<1
Manganese	ppm	ASTM D5185(m)		0	0	0
Magnesium	ppm	ASTM D5185(m)		0	<1	2
Calcium	ppm	ASTM D5185(m)		2	1	6
Phosphorus	ppm	ASTM D5185(m)		0	<1	6
Zinc	ppm	ASTM D5185(m)		0	0	1
Sulfur	ppm	ASTM D5185(m)		9	7	17
Lithium	ppm	ASTM D5185(m)		0	<1	<1

CONTAMINANTS

	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185(m)	>15	0	0	2
Sodium	ppm	ASTM D5185(m)		30	34	41
Potassium	ppm	ASTM D5185(m)	>20	26	25	39
Water	%	ASTM D6304*	>55	49.4	43.7	44.1
ppm Water	ppm	ASTM D6304*	>55000	494000	437000	441000


FLUID CLEANLINESS

	method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647	>640	321	▲ 1344	218
Particles >6µm	ASTM D7647	>160	139	▲ 275	80
Particles >14µm	ASTM D7647	>20	▲ 27	16	15
Particles >21µm	ASTM D7647	>4	▲ 9	▲ 7	5
Particles >38µm	ASTM D7647	>3	2	2	0
Particles >71µm	ASTM D7647	>3	0	0	0
Oil Cleanliness	ISO 4406 (c)	>16/14/11	▲ 16/14/12	▲ 18/15/11	15/13/11




OIL ANALYSIS REPORT


Reserve Alkalinity




Viscosity @ 40°C




Particle Count



Particle Trend



Acid Number




FLUID DEGRADATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*	4.52	4.86	4.61
Alkiline Reserve (Oils)	ml KOH/g	ASTM D1121*	123	142	125

VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE	NONE
Yellow Metal	scalar	Visual*	NONE	NONE	NONE
Precipitate	scalar	Visual*	NONE	NONE	NONE
Silt	scalar	Visual*	NONE	NONE	NONE
Debris	scalar	Visual*	NONE	NONE	NONE
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE
Appearance	scalar	Visual*	NORML	FRGLY	FRGLY
Odor	scalar	Visual*	NORML	NORML	NORML
Emulsified Water	scalar	Visual*	>55	>10%	>10%
Free Water	scalar	Visual*	NEG	NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
pH	Scale 0-14	ASTM D1287*	9.59	9.38	9.49
Visc @ 40°C	cSt	ASTM D7279(m)	33.2	33.5	33.7

SAMPLE IMAGES



ISO 17025:2017
Accredited
Laboratory

Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 **ALGOMA STEEL INC. - STORES DEPT.**
Sample No. : WC0813751 **Received** : 11 Aug 2023 301 WALLACE TERRACE
Lab Number : **02575522** **Diagnosed** : 21 Aug 2023 SAULT STE MARIE, ON
Unique Number : 5620573 **Diagnostician** : Kevin Marson CA P6C 1K8
Test Package : IND 2 (Additional Tests: KF, pH, ReserveAlk, TAN Man)
 Contact: Algoma Reliability
 algomareliability@algoma.com

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

T: (705)206-1059
 F: (705)945-3585