

# **OIL ANALYSIS REPORT**

### Sample Rating Trend

# April 023 Aug 2023





# MAIN LOWER BEARING

Component

**Lower Bearing** 

CHEVRON REGAL OIL R&O 46 (--- LTR)

### DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample.

### Wear

All component wear rates are normal.

### Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

			Apr2023	Aug2023		
SAMPLE INFORM	/ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0732066	WC0732080	
Sample Date		Client Info		10 Aug 2023	11 Apr 2023	
Machine Age	hrs	Client Info		7995	5434	
Oil Age	hrs	Client Info		0	0	
Oil Changed		Client Info		Not Changd	Not Changd	
Sample Status				NORMAL	ATTENTION	
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184*		0	0	
Iron	ppm	ASTM D5185(m)	>20	<1	<1	
Chromium	ppm	ASTM D5185(m)	>20	0	0	
Nickel	ppm	ASTM D5185(m)	>20	0	<1	
Titanium	ppm	ASTM D5185(m)		0	0	
Silver	ppm	ASTM D5185(m)		0	0	
Aluminum	ppm	ASTM D5185(m)	>20	<1	0	
Lead	ppm	ASTM D5185(m)	>20	0	<1	
Copper	ppm	ASTM D5185(m)	>20	1	<1	
Tin	ppm	ASTM D5185(m)	>20	0	0	
Antimony	ppm	ASTM D5185(m)		0	0	
Vanadium	ppm	ASTM D5185(m)		0	0	
Beryllium	ppm	ASTM D5185(m)		0	0	
Cadmium	ppm	ASTM D5185(m)		0	0	

Cadmium	ppm	ASTIVI DOTOD(III)		U	U	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		0	0	
Barium	ppm	ASTM D5185(m)		0	0	
Molybdenum	ppm	ASTM D5185(m)		0	0	
Manganese	ppm	ASTM D5185(m)		<1	<1	
Magnesium	ppm	ASTM D5185(m)		0	2	
Calcium	ppm	ASTM D5185(m)		9	0	
Phosphorus	ppm	ASTM D5185(m)		30	27	
Zinc	ppm	ASTM D5185(m)		8	29	
Sulfur	ppm	ASTM D5185(m)		76	127	
Lithium	ppm	ASTM D5185(m)		<1	<1	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>15	3	4	
Sodium	ppm	ASTM D5185(m)		<1	<1	

Potassium	ppm	ASTM D5185(m)	>20	<1	0	
FLUID CLEANLI	NESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	8340	<b>▲</b> 10867	
Particles >6µm		ASTM D7647	>2500	810	2075	
Particles >14µm		ASTM D7647	>160	15	70	
Particles >21µm		ASTM D7647	>40	5	9	
Particles >38µm		ASTM D7647	>10	0	1	
Particles >71µm		ASTM D7647	>3	0	1	
Oil Cleanliness		ISO 4406 (c)	>20/18/14	20/17/11	<u>\$\lambda\$\$ 21/18/13</u>	



## **OIL ANALYSIS REPORT**

