

OIL ANALYSIS REPORT

Baytech - W00300 [PRESS 33] A2308094

Component **Hydraulic System**

AW HYDRAULIC OIL ISO 46 (--- GAL)

Sample Rating Trend

NORMAL

Recommendation

This is a baseline read-out on the submitted sample.

Wear

{not applicable}

Contamination

{not applicable}

Fluid Condition

{not applicable}

| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
|-----------------|----------|-----------------------------|------------|-------------|----------|----------|
| Sample Number | | Client Info | | E30000121 | | |
| Sample Date | | Client Info | | 17 Aug 2023 | | |
| Machine Age | hrs | Client Info | | 0 | | |
| Oil Age | hrs | Client Info | | 0 | | |
| Oil Changed | | Client Info | | N/A | | |
| Sample Status | | | | NORMAL | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185(m) | >20 | 10 | | |
| Chromium | ppm | ASTM D5185(m) | >20 | <1 | | |
| Nickel | ppm | ASTM D5185(m) | >20 | <1 | | |
| Titanium | ppm | ASTM D5185(m) | | 0 | | |
| Silver | ppm | ASTM D5185(m) | | 0 | | |
| Aluminum | ppm | ASTM D5185(m) | >20 | <1 | | |
| Lead | ppm | ASTM D5185(m) | >20 | 2 | | |
| Copper | ppm | ASTM D5185(m) | >20 | 18 | | |
| Tin | ppm | ASTM D5185(m) | >20 | 0 | | |
| Antimony | ppm | ASTM D5185(m) | | 0 | | |
| Vanadium | ppm | ASTM D5185(m) | | 0 | | |
| Beryllium | ppm | ASTM D5185(m) | | 0 | | |
| Cadmium | ppm | ASTM D5185(m) | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185(m) | 5 | <1 | | |
| Barium | ppm | ASTM D5185(m) | 5 | <1 | | |
| Molybdenum | ppm | ASTM D5185(m) | 5 | 0 | | |
| Manganese | ppm | ASTM D5185(m) | | <1 | | |
| Magnesium | ppm | ASTM D5185(m) | 25 | 57 | | |
| Calcium | ppm | ASTM D5185(m) | 200 | 50 | | |
| Phosphorus | ppm | ASTM D5185(m) | 300 | 565 | | |
| Zinc | ppm | ASTM D5185(m) | 370 | 557 | | |
| Sulfur | ppm | ASTM D5185(m) | 2500 | 1675 | | |
| Lithium | ppm | ASTM D5185(m) | | <1 | | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185(m) | >15 | 3 | Thistory | HISTOLYZ |
| Sodium | | ASTM D5185(m) | >10 | 2 | | |
| Potassium | ppm | ASTM D5185(m) | >20 | 1 | | |
| Water | ppm % | ASTM D3163(III) ASTM D6304* | >0.05 | 0.014 | | |
| ppm Water | | ASTM D6304* | >50.03 | 140.9 | | |
| | ppm | | | | | |
| FLUID CLEANLIN | ESS | method | limit/base | current | history1 | history2 |
| Particles >4µm | | ASTM D7647 | >5000 | 1392 | | |
| Particles >6µm | | ASTM D7647 | >1300 | 132 | | |
| Particles >14µm | | ASTM D7647 | >160 | 9 | | |
| Particles >21µm | | ASTM D7647 | >40 | 3 | | |
| Particles >38µm | | ASTM D7647 | >10 | 0 | | |
| Particles >71μm | | ASTM D7647 | >3 | 0 | | |
| Oil Cleanliness | | ISO 4406 (c) | >19/17/14 | 18/14/10 | | |



OIL ANALYSIS REPORT

