



# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Area  
**[7747784]**  
 Machine Id  
**56 (S/N PH8722)**  
 Component  
**Hydraulic System**  
 Fluid  
**NOT GIVEN (--- GAL)**



## DIAGNOSIS

### Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

### Wear

All component wear rates are normal.

### Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>WC0741328</b>	---	---
Sample Date	Client Info	<b>12 Jul 2023</b>	---	---
Machine Age	hrs Client Info	<b>0</b>	---	---
Oil Age	hrs Client Info	<b>0</b>	---	---
Oil Changed	Client Info	<b>N/A</b>	---	---
Sample Status		<b>NORMAL</b>	---	---

## WEAR METALS

method	limit/base	current	history1	history2
Iron ppm ASTM D5185(m)	>20	<b>0</b>	---	---
Chromium ppm ASTM D5185(m)	>20	<b>0</b>	---	---
Nickel ppm ASTM D5185(m)	>20	<b>0</b>	---	---
Titanium ppm ASTM D5185(m)		<b>0</b>	---	---
Silver ppm ASTM D5185(m)		<b>0</b>	---	---
Aluminum ppm ASTM D5185(m)	>20	<b>&lt;1</b>	---	---
Lead ppm ASTM D5185(m)	>20	<b>0</b>	---	---
Copper ppm ASTM D5185(m)	>20	<b>&lt;1</b>	---	---
Tin ppm ASTM D5185(m)	>20	<b>0</b>	---	---
Antimony ppm ASTM D5185(m)		<b>0</b>	---	---
Vanadium ppm ASTM D5185(m)		<b>0</b>	---	---
Beryllium ppm ASTM D5185(m)		<b>0</b>	---	---
Cadmium ppm ASTM D5185(m)		<b>0</b>	---	---

## ADDITIVES

method	limit/base	current	history1	history2
Boron ppm ASTM D5185(m)		<b>&lt;1</b>	---	---
Barium ppm ASTM D5185(m)		<b>0</b>	---	---
Molybdenum ppm ASTM D5185(m)		<b>&lt;1</b>	---	---
Manganese ppm ASTM D5185(m)		<b>0</b>	---	---
Magnesium ppm ASTM D5185(m)		<b>6</b>	---	---
Calcium ppm ASTM D5185(m)		<b>66</b>	---	---
Phosphorus ppm ASTM D5185(m)		<b>368</b>	---	---
Zinc ppm ASTM D5185(m)		<b>442</b>	---	---
Sulfur ppm ASTM D5185(m)		<b>831</b>	---	---
Lithium ppm ASTM D5185(m)		<b>&lt;1</b>	---	---

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon ppm ASTM D5185(m)	>15	<b>0</b>	---	---
Sodium ppm ASTM D5185(m)		<b>0</b>	---	---
Potassium ppm ASTM D5185(m)	>20	<b>&lt;1</b>	---	---

## FLUID CLEANLINESS





method	limit/base	current	history1	history2
Particles >4µm ASTM D7647	>5000	<b>680</b>	---	---
Particles >6µm ASTM D7647	>1300	<b>102</b>	---	---
Particles >14µm ASTM D7647	>160	<b>5</b>	---	---
Particles >21µm ASTM D7647	>40	<b>2</b>	---	---
Particles >38µm ASTM D7647	>10	<b>0</b>	---	---
Particles >71µm ASTM D7647	>3	<b>0</b>	---	---
Oil Cleanliness ISO 4406 (c)	>19/17/14	<b>17/14/10</b>	---	---

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Acid Number (AN) mg KOH/g ASTM D974*		<b>0.45</b>	---	---



# OIL ANALYSIS REPORT






VISUAL	method	limit/base	current	history1	history2	
White Metal	scalar	Visual*	NONE	NONE	---	---
Yellow Metal	scalar	Visual*	NONE	NONE	---	---
Precipitate	scalar	Visual*	NONE	NONE	---	---
Silt	scalar	Visual*	NONE	NONE	---	---
Debris	scalar	Visual*	NONE	NONE	---	---
Sand/Dirt	scalar	Visual*	NONE	NONE	---	---
Appearance	scalar	Visual*	NORML	NORML	---	---
Odor	scalar	Visual*	NORML	NORML	---	---
Emulsified Water	scalar	Visual*	>0.05	NEG	---	---
Free Water	scalar	Visual*		NEG	---	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	43.6	---	---

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------

Color		no image	no image
Bottom		no image	no image

## GRAPHS



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : WC0741328 **Received** : 23 Aug 2023  
**Lab Number** : 02577726 **Diagnosed** : 24 Aug 2023  
**Unique Number** : 5630786 **Diagnostician** : Wes Davis  
**Test Package** : IND 2

**ESCO LTD.**  
 P.O. BOX 270, 185 HOPE STREET SOUTH  
 PORT HOPE, ON  
 CA L1A 3W4  
 Contact: Paul Dundas  
 paul.dundas@mail.weir  
 T: (647)725-8153  
 F: (905)885-7600

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.