



PROBLEM SUMMARY

Area
Woodbridge Foam - W04100
 Machine Id
AM888-R
 Component
Hydraulic System
 Fluid
MONARCH PREMIUM HYDRAULIC OIL AW R&O 46 (--- GAL)


Sample Rating Trend



WATER



COMPONENT CONDITION SUMMARY



RECOMMENDATION

This is a baseline read-out on the submitted sample.

PROBLEMATIC TEST RESULTS

Sample Status				ABNORMAL	---	---
Water	%	ASTM D6304*	>0.05	▲ 0.106	---	---
ppm Water	ppm	ASTM D6304*	>500	▲ 1062.1	---	---

Customer Id: CHECOB
 Sample No.: E30000041
 Lab Number: 02578309
 Test Package: IND 2



To manage this report scan the QR code

To discuss the diagnosis or test data:
 Tatiana Sorkina +1 (800)263-3939
tsorkina@e360s.ca

To change component or sample information:
 Gloria Gonzalez +1 (289)291-4643 x4643
gloria.gonzalez@wearcheck.com

RECOMMENDED ACTIONS

There are no recommended actions for this sample.

HISTORICAL DIAGNOSIS



OIL ANALYSIS REPORT

Sample Rating Trend



WATER



Area
Woodbridge Foam - W04100

Machine Id
AM888-R

Component
Hydraulic System
Fluid
MONARCH PREMIUM HYDRAULIC OIL AW R&O 46 (--- GAL)

DIAGNOSIS

Recommendation

This is a baseline read-out on the submitted sample.

Wear

{not applicable}

Contamination

Water and ppm water contamination levels are abnormal.

Fluid Condition

{not applicable}

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	E30000041	---	---
Sample Date	Client Info	23 Aug 2023	---	---
Machine Age	hrs Client Info	0	---	---
Oil Age	hrs Client Info	0	---	---
Oil Changed	Client Info	N/A	---	---
Sample Status		ABNORMAL	---	---

WEAR METALS

method	limit/base	current	history1	history2
Iron ppm ASTM D5185(m)	>20	<1	---	---
Chromium ppm ASTM D5185(m)	>20	<1	---	---
Nickel ppm ASTM D5185(m)	>20	<1	---	---
Titanium ppm ASTM D5185(m)		0	---	---
Silver ppm ASTM D5185(m)		<1	---	---
Aluminum ppm ASTM D5185(m)	>20	<1	---	---
Lead ppm ASTM D5185(m)	>20	<1	---	---
Copper ppm ASTM D5185(m)	>20	1	---	---
Tin ppm ASTM D5185(m)	>20	0	---	---
Antimony ppm ASTM D5185(m)		0	---	---
Vanadium ppm ASTM D5185(m)		0	---	---
Beryllium ppm ASTM D5185(m)		0	---	---
Cadmium ppm ASTM D5185(m)		0	---	---

ADDITIVES

method	limit/base	current	history1	history2
Boron ppm ASTM D5185(m)		<1	---	---
Barium ppm ASTM D5185(m)		0	---	---
Molybdenum ppm ASTM D5185(m)		0	---	---
Manganese ppm ASTM D5185(m)		0	---	---
Magnesium ppm ASTM D5185(m)		<1	---	---
Calcium ppm ASTM D5185(m)		40	---	---
Phosphorus ppm ASTM D5185(m)		360	---	---
Zinc ppm ASTM D5185(m)		394	---	---
Sulfur ppm ASTM D5185(m)		812	---	---
Lithium ppm ASTM D5185(m)		<1	---	---






CONTAMINANTS

method	limit/base	current	history1	history2
Silicon ppm ASTM D5185(m)	>15	<1	---	---
Sodium ppm ASTM D5185(m)		1	---	---
Potassium ppm ASTM D5185(m)	>20	<1	---	---
Water % ASTM D6304*	>0.05	▲ 0.106	---	---
ppm Water ppm ASTM D6304*	>500	▲ 1062.1	---	---

FLUID CLEANLINESS

method	limit/base	current	history1	history2
Particles >4µm ASTM D7647	>5000	517	---	---
Particles >6µm ASTM D7647	>1300	110	---	---
Particles >14µm ASTM D7647	>160	10	---	---
Particles >21µm ASTM D7647	>40	2	---	---
Particles >38µm ASTM D7647	>10	0	---	---
Particles >71µm ASTM D7647	>3	0	---	---
Oil Cleanliness ISO 4406 (c)	>19/17/14	16/14/10	---	---

OIL ANALYSIS REPORT







FLUID DEGRADATION		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*		0.49	---	---

VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE	---	---
Yellow Metal	scalar	Visual*	NONE	NONE	---	---
Precipitate	scalar	Visual*	NONE	NONE	---	---
Silt	scalar	Visual*	NONE	NONE	---	---
Debris	scalar	Visual*	NONE	NONE	---	---
Sand/Dirt	scalar	Visual*	NONE	NONE	---	---
Appearance	scalar	Visual*	NORML	NORML	---	---
Odor	scalar	Visual*	NORML	NORML	---	---
Emulsified Water	scalar	Visual*	>0.05	NEG	---	---
Free Water	scalar	Visual*		NEG	---	---

FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	45.7	43.3	---	---
Visc @ 100°C	cSt	ASTM D7279(m)	6.7	6.5	---	---
Viscosity Index (VI)	Scale	ASTM D2270*	100	99	---	---

SAMPLE IMAGES		method	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : E30000041 **Received** : 24 Aug 2023
Lab Number : **02578309** **Diagnosed** : 30 Aug 2023
Unique Number : 5631369 **Diagnostician** : Tatiana Sorkina
Test Package : IND 2 (Additional Tests: KF, KV100, VI)

Environmental 360 Solutions Ltd.
 640 Victoria Street
 Cobourg, ON
 CA K9A 5H5
 Contact: Tatiana Sorkina
 tsorkina@e360s.ca
 T: (800)263-3939
 F: (905)373-4950

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.