

FUEL REPORT

Sample Rating Trend



Area [66177] Machine Id KT0000822 Component

Diesel Fuel

No.2 DIESEL FUEL (ULTRALOW SULPHUR) (--- GAL)

DIAGNOSIS

Recommendation

Laboratory test indicate that this fuel is suitable for use and meets all test requirements. Resample at the next service interval to monitor.

Corrosion

{not applicable}

Contaminants

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The water content is negligible. There is no indication of any contamination in the diesel fuel.

Fuel Condition

All laboratory tests indicate that this sample meets specifications for No.2 ultra-low-sulfur diesel fuel (US EPA/CGSB-3.517-3 type B).

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KT0000822		
Sample Date		Client Info		21 Aug 2023		
Machine Age	hrs	Client Info		0		
Sample Status				NORMAL		
PHYSICAL PROP	ERTIES	method	limit/base	current	history1	history2
Specific Gravity		ASTM D1298*	0.839	0.839		
Fuel Color	text	Visual Screen*	Yllow	Yllow		
Visc @ 40°C	cSt	ASTM D7279(m)	3.0	2.5		
Pensky-Martens Flash Point	°C	ASTM D7215*	52	51.8		
SULFUR CONTEN	٦V	method	limit/base	current	history1	history2
Sulfur	ppm	ASTM D5185(m)	10	8		
DISTILLATION		method	limit/base	current	history1	history2
Initial Boiling Point	°C	ASTM D2887*	165	159		
5% Distillation Point	°C	ASTM D2887*		184		
10% Distill Point	°C	ASTM D2887*	201	196		
15% Distillation Point	°C	ASTM D2887*		205		
20% Distill Point	°C	ASTM D2887*	216	214		
30% Distill Point	°C	ASTM D2887*	230	231		
40% Distill Point	°C	ASTM D2887*	243	246		
50% Distill Point	°C	ASTM D2887*	255	261		
60% Distill Point	°C	ASTM D2887*	267	276		
70% Distill Point	°C	ASTM D2887*	280	291		
80% Distill Point	°C	ASTM D2887*	295	307		
85% Distillation Point	°C	ASTM D2887*	010	318		
90% Distill Point	°C	ASTM D2887*	310	329		
95% Distillation Point Final Boiling Point	°C °C	ASTM D2887* ASTM D2887*	341	348 365		
-			-			
IGNITION QUALIT	Υ	method	limit/base	current	history1	history2
API Gravity		ASTM D1298*	37.7	37		
Cetane Index		ASTM D4737*	<40.0	48		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	<1.0	0		
Sodium	ppm	ASTM D5185(m)		0		
Potassium	ppm	ASTM D5185(m)	<0.1	<1		
Water	%	ASTM D6304*	<0.05	0.003		
ppm Water	ppm	ASTM D6304*	<500	27.3		
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>2500	624		
Particles >6µm		ASTM D7647	>640	170		
Particles >14µm		ASTM D7647	>80	17		
Particles >21µm		ASTM D7647	>20	6		
Particles >38µm		ASTM D7647	>4	0		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>18/16/13	16/15/11		

Contact/Location: Rick Dawson - KIOMIS



FUEL REPORT

