


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



NO UNIT WC0844647

Component

Unknown Component

NOT GIVEN (--- LTR)

| | G١ | | |
|--|----|--|--|
| | | | |
| | | | |
| | | | |

Recommendation

This is a baseline read-out on the submitted sample.

Wear

{not applicable}

Contamination

Insufficient sample was received to conduct all the routine laboratory tests.

Fluid Condition

{not applicable}

| | | | | Aug2023 | | |
|---------------|--------|-----------------------------|------------|-------------|----------|----------|
| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | WC0844647 | | |
| Sample Date | | Client Info | | 10 Aug 2023 | | |
| Machine Age | hrs | Client Info | | 0 | | |
| Oil Age | hrs | Client Info | | 0 | | |
| Oil Changed | | Client Info | | N/A | | |
| Sample Status | | | | NORMAL | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185(m) | | <1 | | |
| Chromium | ppm | ASTM D5185(m) | | 0 | | |
| Nickel | ppm | ASTM D5185(m) | | 0 | | |
| Titanium | ppm | ASTM D5185(m) | | 0 | | |
| Silver | ppm | ASTM D5185(m) | | <1 | | |
| Aluminum | ppm | ASTM D5185(m) | | <1 | | |
| Lead | ppm | ASTM D5185(m) | | 0 | | |
| Copper | ppm | ASTM D5185(m) | | <1 | | |
| Tin | | , | | 0 | | |
| | ppm | ASTM D5185(m) ASTM D5185(m) | | 0 | | |
| Antimony | ppm | () | | | | |
| Vanadium | ppm | ASTM D5185(m) | | 0 | | |
| Beryllium | ppm | ASTM D5185(m) | | 0 | | |
| Cadmium | ppm | ASTM D5185(m) | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185(m) | | <1 | | |
| Barium | ppm | ASTM D5185(m) | | 0 | | |
| Molybdenum | ppm | ASTM D5185(m) | | 0 | | |
| Manganese | ppm | ASTM D5185(m) | | 0 | | |
| Magnesium | ppm | ASTM D5185(m) | | <1 | | |
| Calcium | ppm | ASTM D5185(m) | | 7 | | |
| Phosphorus | ppm | ASTM D5185(m) | | 434 | | |
| Zinc | ppm | ASTM D5185(m) | | 478 | | |
| Sulfur | ppm | ASTM D5185(m) | | 1881 | | |
| Lithium | ppm | ASTM D5185(m) | | <1 | | |
| CONTAMINANTS | ; | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185(m) | | 3 | | |
| Sodium | ppm | ASTM D5185(m) | | 1 | | |
| Potassium | ppm | ASTM D5185(m) | >20 | <1 | | |
| VISUAL | | method | limit/base | current | history1 | history2 |
| White Metal | scalar | Visual* | NONE | NONE | | |
| Yellow Metal | scalar | Visual* | NONE | NONE | | |
| Precipitate | scalar | Visual* | NONE | NONE | | |
| Silt | scalar | Visual* | NONE | NONE | | |
| Debris | scalar | Visual* | NONE | NONE | | |
| Sand/Dirt | scalar | Visual* | NONE | NONE | | |
| Appearance | scalar | Visual* | NORML | NORML | | |
| Odor | scalar | Visual* | NORML | NORML | | |
| | COMICI | | | | | |



OIL ANALYSIS REPORT





CALA ISO 17025:2017 Accredited Laboratory

Laboratory Sample No. Lab Number

Unique Number : 5631999

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 GLASLYN POWER AND EQUIPMENT : WC0844647 : 02578939

Received Diagnosed

: 28 Aug 2023 : 29 Aug 2023 Diagnostician : Kevin Marson

BOX 459 GLASLYN, SK CA S0M 0Y0

Contact: LLOYD JOHNSON

Test Package : TEST (Additional Tests: ICP) To discuss this sample report, contact Customer Service at 1-800-268-2131.

Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

T: (306)342-4808

F: