

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

COMISSIONED SALFORD #12

Unknown Component Fluid CHEVRON 1000 THF (--- LTR)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the sample.


Fluid Condition


The AN level is acceptable for this fluid. The condition of the sample is suitable for further service.

SAMPLE INFORM		method	limit/base	current	history1	history2
		Client Info	mmbasc	WC0815337		
Sample Number		Client Info		20 Jul 2023		
Sample Date Machine Age	hrs	Client Info		20 JUI 2023 0		
Oil Age	hrs	Client Info		0		
•	1115	Client Info		U N/A		
Oil Changed		Cilent Inio				
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184*		0		
Iron	ppm	ASTM D5185(m)		2		
Chromium	ppm	ASTM D5185(m)		0		
Nickel	ppm	ASTM D5185(m)		<1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)		<1		
Lead	ppm	ASTM D5185(m)		0		
Copper	ppm	ASTM D5185(m)		<1		
Tin	ppm	ASTM D5185(m)		0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		4		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		2		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		17		
Calcium	ppm	ASTM D5185(m)		2805		
Phosphorus	ppm	ASTM D5185(m)		1073		
Zinc	ppm	ASTM D5185(m)		1235		
Sulfur	ppm	ASTM D5185(m)		2996		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)		18		
Sodium	ppm	ASTM D5185(m)		<1		
Potassium	ppm	ASTM D5185(m)	>20	<1		
FLUID DEGRADA	TIO <u>N</u>	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*		2.30		



OIL ANALYSIS REPORT





	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	Visual*	NONE	NONE		
	Yellow Metal	scalar	Visual*	NONE	NONE		
	Precipitate	scalar	Visual*	NONE	NONE		
	Silt	scalar	Visual*	NONE	NONE		
	Debris	scalar	Visual*	NONE	VLITE		
	Sand/Dirt	scalar	Visual*	NONE	NONE		
	Appearance	scalar	Visual*	NORML	NORML		
	Ouor	scalar	Visual*	NORML	NORML		
	Emulsified Water	scalar	Visual*		NEG		
	Free Water	scalar	Visual*		NEG		
	FLUID PROPER	RTIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D7279(m)	58.4	54.1		
	SAMPLE IMAGE	ES	method	limit/base	current	history1	history2
	-						
						no image	no image
	Juľ						
	Bottom					no image	no image
	GRAPHS						
	Ferrous Alloys			220-	PQ		
	iron			200	Severe		
	E 6 - nickel						
				180-			
	2			160	1		
	0 2			140.			
	Jul20/23			120- 120- 120-			
	Non-ferrous Met	als		100-	Abnormal		
	¹⁰ T			80-			
	8 - copper			60-	·		
	E 6			40-			
	4						
	2			20.			
	Jul20/23			Jul20/23	Jul20/23		
	਼ Viscosity @ 40°C	_		ηſ			
	⁷⁰ T			<u> </u>	Acid Number		
	65 Abnormal			Hoy 2.0			
	⊖ 60 - Base € 55 -			<u>ق</u> 1.5			
	³ 50			-9 1.0-			
				(5, 2.5 HOX 2.0 But 1.5 april 1.0 N 0.5- O 0.5	• • • • • • • • • • • • • • • • • • • •		
	40 L +				/23 +		
	Jul20/23			Jul20/23	Jul20/23		-
CALA Laboratory	: WearCheck - C8-1	1175 Applel	by Line, Bur	lington, ON L7	7L 5H9	Salf	ord Group In
Sample No.	: WC0815337	Received	: 29	Aug 2023	-		18 McBeth R
Lab Number		Diagnose		Aug 2023			Salford, O
Accredited Unique Numb		Diagnosti		vin Marson		Conte	CA NOJ 1W
Test Packag				1.	~	bris.poppe@sal	t: Chris Popp
st denoted (*) outside sco	-						(519)485-397
lidity of results and intern							, ,

Validity of results and interpretation are based on the sample and information as supplied.

F: