




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
2228
 Component
Natural Gas Engine
 Fluid
NOT GIVEN (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

Metal levels are typical for a new component breaking in.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			WC0849876	WC0830187	WC0791331
Sample Date	Client Info			25 Aug 2023	10 Jul 2023	01 Jun 2023
Machine Age	kms	Client Info		31683	23288	15541
Oil Age	kms	Client Info		0	0	0
Oil Changed	Client Info			N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>50	9	13	47
Chromium	ppm	ASTM D5185(m)	>4	<1	<1	<1
Nickel	ppm	ASTM D5185(m)	>2	<1	<1	1
Titanium	ppm	ASTM D5185(m)		<1	<1	<1
Silver	ppm	ASTM D5185(m)	>3	0	0	0
Aluminum	ppm	ASTM D5185(m)	>9	1	2	3
Lead	ppm	ASTM D5185(m)	>30	<1	<1	1
Copper	ppm	ASTM D5185(m)	>35	3	4	15
Tin	ppm	ASTM D5185(m)	>4	<1	<1	1
Antimony	ppm	ASTM D5185(m)		0	0	<1
Vanadium	ppm	ASTM D5185(m)		0	0	0
Beryllium	ppm	ASTM D5185(m)		0	0	0
Cadmium	ppm	ASTM D5185(m)		0	0	0

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		10	12	11
Barium	ppm	ASTM D5185(m)		0	<1	3
Molybdenum	ppm	ASTM D5185(m)		51	50	54
Manganese	ppm	ASTM D5185(m)		<1	2	10
Magnesium	ppm	ASTM D5185(m)		763	808	778
Calcium	ppm	ASTM D5185(m)		1174	1186	1228
Phosphorus	ppm	ASTM D5185(m)		669	713	690
Zinc	ppm	ASTM D5185(m)		825	828	822
Sulfur	ppm	ASTM D5185(m)		1917	1856	1888
Lithium	ppm	ASTM D5185(m)		<1	<1	<1

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>+100	6	9	36
Sodium	ppm	ASTM D5185(m)		3	2	4
Potassium	ppm	ASTM D5185(m)	>20	0	<1	1

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	ASTM D7844*		0	0	0
Nitration	Abs/cm	ASTM D7624*	>20	10.8	12.0	12.4
Sulfation	Abs/.1mm	ASTM D7415*	>30	21.5	21.7	24.4

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	ASTM D7414*	>25	17.2	19.7	22.7










VISUAL		method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG	NEG



OIL ANALYSIS REPORT

FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D7279(m)		14.3	14.4	14.0

GRAPHS



ISO 17025:2017
Accredited
Laboratory

Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : WC0849876 **Received** : 05 Sep 2023
Lab Number : 02580259 **Diagnosed** : 05 Sep 2023
Unique Number : 5633319 **Diagnostician** : Wes Davis
Test Package : MOB 1

CITY OF HAMILTON
 2200 UPPER JAMES., MOUNTAIN TRANSIT STOREROOM
 MOUNT HOPE, ON
 CA L0R 1W0
 Contact: Ron Skinner
 ron.skinner@hamilton.ca

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.

T:
 F: (905)679-4502