

FUEL REPORT

Sample Rating Trend



DAY TANK 1

Component Diesel Fuel

Fluid No.2 DIESEL FUEL (ULTRALOW SULPHUR) (--- LTR)

DIAGNOSIS

Recommendation

Laboratory test indicate that this fuel is suitable for use and meets all test requirements. Resample at the next service interval to monitor.

Corrosion

{not applicable}

Contaminants

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The water content is negligible. There is no indication of any contamination in the diesel fuel.

Fuel Condition

All laboratory tests indicate that this sample meets specifications for No.2 ultra-low-sulfur diesel fuel (US EPA/CGSB-3.517-3 type B).

-				Sep2023		
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0841224		
Sample Date		Client Info		22 Sep 2023		
Machine Age	hrs	Client Info		0		
Sample Status				NORMAL		
PHYSICAL PROP	ERTIES	method	limit/base	current	history1	history2
Specific Gravity		ASTM D1298*	0.839	0.841		
Fuel Color	text	Visual Screen*	Yllow	Red		
Visc @ 40°C	cSt	ASTM D7279(m)	3.0	2.7		
Pensky-Martens Flash Point	°C	ASTM D7215*	52	58.8		
SULFUR CONTEN	١T	method	limit/base	current	history1	history2
Sulfur	ppm	ASTM D5185(m)	10	8		
DISTILLATION		method	limit/base	current	history1	history2
Initial Boiling Point	°C	ASTM D2887*	165	172		
5% Distillation Point	°C	ASTM D2887*		199		
10% Distill Point	°C	ASTM D2887*	201	210		
15% Distillation Point	°C	ASTM D2887*		217		
20% Distill Point	°C	ASTM D2887*	216	224		
30% Distill Point	°C	ASTM D2887*	230	238		
40% Distill Point	°C	ASTM D2887*	243	250		
50% Distill Point	°C	ASTM D2887*	255	262		
60% Distill Point	°C	ASTM D2887*	267	275		
70% Distill Point	°C	ASTM D2887*	280	288		
80% Distill Point	°C	ASTM D2887*	295	303		
85% Distillation Point	°C	ASTM D2887*		315		
90% Distill Point	°C	ASTM D2887*	310	326		
95% Distillation Point	°C	ASTM D2887*		347		
Final Boiling Point	°C	ASTM D2887*	341	366		
IGNITION QUALIT	Ϋ́	method	limit/base	current	history1	history2
API Gravity		ASTM D1298*	37.7	36		
Cetane Index		ASTM D4737*	<40.0	49		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	<1.0	0		
Sodium	ppm	ASTM D5185(m)	<0.1	<1		
Potassium	ppm	ASTM D5185(m)	<0.1	<1		
Water	%	ASTM D6304*	<0.05	0.003		
ppm Water	ppm	ASTM D6304*	<500	35.3		
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>2500	448		
Particles >6µm		ASTM D7647	>640	87		
		ASTM D7647	>80	7		
Particles >14µm						
Particles >21µm		ASTM D7647	>20	2		
Particles >21µm Particles >38µm		ASTM D7647	>20 >4	0		
Particles >21µm						

Contact/Location: Jim Cochrane - CANARN



FUEL REPORT

