

# **OIL ANALYSIS REPORT**

# Sample Rating Trend

**NORMAL** 



# NO UNIT WC0716342

Component

**Diesel Engine** 

**DIESEL ENGINE OIL SAE 30 (--- GAL)** 

### Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) DIESEL ENGINE OIL SAE 30. Please confirm. Please specify the component make and model with your next sample.

### Wear

Metal levels are typical for a components first oil change.

### Contamination

Light fuel dilution occurring. No other contaminants were detected in the oil.

### **Fluid Condition**

The condition of the oil is acceptable for the time in service.

			S	Sep 2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0716342		
Sample Date		Client Info		20 Sep 2023		
Machine Age	hrs	Client Info		500		
Oil Age	hrs	Client Info		500		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATION	٧	method	limit/base	current	history1	history2
Glycol		WC Method		NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>100	56		
Chromium	ppm	ASTM D5185(m)	>20	1		
Nickel	ppm	ASTM D5185(m)	>4	1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)	>3	<1		
Aluminum	ppm	ASTM D5185(m)	>20	8		
Lead	ppm	ASTM D5185(m)	>40	1		
Copper	ppm	ASTM D5185(m)	>330	2		
Tin	ppm	ASTM D5185(m)	>15	0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
•						
Cadmium	ppm	ASTM D5185(m)		0		
Cadmium ADDITIVES	ppm	ASTM D5185(m) method	limit/base	0 current	history1	history2
		method	limit/base			
ADDITIVES	ppm			current	history1	history2
ADDITIVES Boron	ppm ppm	method ASTM D5185(m)	250	current 63	history1	history2
ADDITIVES Boron Barium	ppm	method  ASTM D5185(m)  ASTM D5185(m)  ASTM D5185(m)	250 10	current 63 <1	history1	history2
ADDITIVES Boron Barium Molybdenum	ppm ppm ppm	method  ASTM D5185(m)  ASTM D5185(m)	250 10	current 63 <1 94	history1  	history2
ADDITIVES  Boron  Barium  Molybdenum  Manganese	ppm ppm ppm	method  ASTM D5185(m)  ASTM D5185(m)  ASTM D5185(m)  ASTM D5185(m)	250 10 100	current 63 <1 94 0	history1	history2  
ADDITIVES  Boron  Barium  Molybdenum  Manganese  Magnesium  Calcium	ppm ppm ppm ppm ppm	method ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	250 10 100 450	current 63 <1 94 0 54	history1	history2   
ADDITIVES  Boron  Barium  Molybdenum  Manganese  Magnesium	ppm ppm ppm ppm	method  ASTM D5185(m)	250 10 100 450 3000	current 63 <1 94 0 54 2213	history1	history2
ADDITIVES  Boron  Barium  Molybdenum  Manganese  Magnesium  Calcium  Phosphorus	ppm ppm ppm ppm ppm ppm ppm	method  ASTM D5185(m)	250 10 100 450 3000 1150	current 63 <1 94 0 54 2213	history1	history2
ADDITIVES  Boron  Barium  Molybdenum  Manganese  Magnesium  Calcium  Phosphorus  Zinc	ppm ppm ppm ppm ppm ppm	method  ASTM D5185(m)	250 10 100 450 3000 1150 1350	current 63 <1 94 0 54 2213 1032 1184	history1	history2
ADDITIVES  Boron  Barium  Molybdenum  Manganese  Magnesium  Calcium  Phosphorus  Zinc  Sulfur  Lithium	ppm ppm ppm ppm ppm ppm ppm ppm ppm	method  ASTM D5185(m)	250 10 100 450 3000 1150 1350 4250	current  63 <1 94 0 54 2213 1032 1184 3209	history1	history2
ADDITIVES  Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium	ppm ppm ppm ppm ppm ppm ppm ppm ppm	method  ASTM D5185(m)	250 10 100 450 3000 1150 1350 4250	current  63 <1 94 0 54 2213 1032 1184 3209 <1 current	history1	history2
ADDITIVES  Boron  Barium  Molybdenum  Manganese  Magnesium  Calcium  Phosphorus  Zinc  Sulfur  Lithium  CONTAMINANTS  Silicon	ppm ppm ppm ppm ppm ppm ppm ppm ppm	method  ASTM D5185(m)	250 10 100 450 3000 1150 1350 4250 limit/base >25	current  63 <1 94 0 54 2213 1032 1184 3209 <1 current	history1 history1	history2 history2
ADDITIVES  Boron  Barium  Molybdenum  Manganese  Magnesium  Calcium  Phosphorus  Zinc  Sulfur  Lithium  CONTAMINANTS  Silicon  Sodium	ppm ppm ppm ppm ppm ppm ppm ppm ppm	method  ASTM D5185(m)	250 10 100 450 3000 1150 1350 4250 limit/base >25 >75	current 63 <1 94 0 54 2213 1032 1184 3209 <1 current 17 6	history1 history1	history2 history2
ADDITIVES  Boron  Barium  Molybdenum  Manganese  Magnesium  Calcium  Phosphorus  Zinc  Sulfur  Lithium  CONTAMINANTS  Silicon	ppm ppm ppm ppm ppm ppm ppm ppm ppm	method  ASTM D5185(m)	250 10 100 450 3000 1150 1350 4250 limit/base >25	current  63 <1 94 0 54 2213 1032 1184 3209 <1 current	history1 history1	history2 history2 history2
ADDITIVES  Boron  Barium  Molybdenum  Manganese  Magnesium  Calcium  Phosphorus  Zinc  Sulfur  Lithium  CONTAMINANTS  Silicon  Sodium  Potassium	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	method  ASTM D5185(m)	250 10 100 450 3000 1150 1350 4250  limit/base >25 >75 >20	current  63 <1 94 0 54 2213 1032 1184 3209 <1 current  17 6 2	history1 history1	history2 history2 history2
ADDITIVES  Boron  Barium  Molybdenum  Manganese  Magnesium  Calcium  Phosphorus  Zinc  Sulfur  Lithium  CONTAMINANTS  Silicon  Sodium  Potassium  Fuel  INFRA-RED	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	method  ASTM D5185(m)	250 10 100 450 3000 1150 1350 4250  limit/base >25 >75 >20 >5  limit/base	current  63 <1 94 0 54 2213 1032 1184 3209 <1 current  17 6 2 1.9 current	history1 history1 history1 history1	history2 history2 history2 history2
ADDITIVES  Boron  Barium  Molybdenum  Manganese  Magnesium  Calcium  Phosphorus  Zinc  Sulfur  Lithium  CONTAMINANTS  Silicon  Sodium  Potassium  Fuel  INFRA-RED  Soot %	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	method  ASTM D5185(m) ASTM D7593*  method  ASTM D7844*	250 10 100 450 3000 1150 1350 4250  limit/base >25 >75 >20 >5  limit/base >3	current 63 <1 94 0 54 2213 1032 1184 3209 <1 current 17 6 2 1.9 current 0	history1 history1 history1 history1	history2 history2 history2 history2
ADDITIVES  Boron  Barium  Molybdenum  Manganese  Magnesium  Calcium  Phosphorus  Zinc  Sulfur  Lithium  CONTAMINANTS  Silicon  Sodium  Potassium  Fuel  INFRA-RED  Soot %  Nitration	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	method  ASTM D5185(m) ASTM D7593*  method  ASTM D7593*	250 10 100 450 3000 1150 1350 4250  limit/base >25 >75 >20 >5 limit/base >3 >20	current  63 <1 94 0 54 2213 1032 1184 3209 <1 current 17 6 2 1.9 current 0 8.7	history1 history1 history1 history1	history2 history2 history2 history2
ADDITIVES  Boron  Barium  Molybdenum  Manganese  Magnesium  Calcium  Phosphorus  Zinc  Sulfur  Lithium  CONTAMINANTS  Silicon  Sodium  Potassium  Fuel  INFRA-RED  Soot %  Nitration  Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	method  ASTM D5185(m) ASTM D7593*  method  ASTM D7593*  method  ASTM D7844* ASTM D7624* ASTM D7615*	250 10 100 450 3000 1150 1350 4250  limit/base >25 >75 >20 >5  limit/base >3 >20 >30	current  63 <1 94 0 54 2213 1032 1184 3209 <1 current 17 6 2 1.9 current 0 8.7 18.9	history1 history1 history1 history1	history2 history2 history2 history2
ADDITIVES  Boron  Barium  Molybdenum  Manganese  Magnesium  Calcium  Phosphorus  Zinc  Sulfur  Lithium  CONTAMINANTS  Silicon  Sodium  Potassium  Fuel  INFRA-RED  Soot %  Nitration	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	method  ASTM D5185(m) ASTM D7593*  method  ASTM D7593*	250 10 100 450 3000 1150 1350 4250  limit/base >25 >75 >20 >5 limit/base >3 >20	current  63 <1 94 0 54 2213 1032 1184 3209 <1 current 17 6 2 1.9 current 0 8.7	history1 history1 history1 history1	history2 history2 history2



## **OIL ANALYSIS REPORT**





CALA ISO 17025:2017 Accredited Laboratory

Laboratory Sample No. Lab Number Unique Number

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 : WC0716342 : 02588486

: 5657552

Received : 12 Oct 2023 Diagnosed

: 13 Oct 2023 Diagnostician : Kevin Marson **Test Package**: MOB 1 (Additional Tests: FuelDilution, PercentFuel)

To discuss this sample report, contact Customer Service at 1-800-268-2131.

Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

**COLACEM CANADA INC** 

56 RUE LONGUEUIL CP 301 L'ORIGNAL, ON CA K0B 1K0

Contact: Michel Landriault mlandriault@colacem.ca T:

F: (613)675-2747