

GREASE ANALYSIS

Sample Rating Trend





Grease

MOBIL MOBILGREASE XHP 222 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Grease Condition

The condition of the grease is acceptable for the time in service.

Contaminants

There is no indication of any contamination in the grease.


		-		Oct2023		
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0869253		
Sample Date		Client Info		17 Oct 2023		
Machine Age	hrs	Client Info		0		
Grease Age	hrs	Client Info		0		
Grease Serviced		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184*	>200	90		
Iron	ppm	ASTM D5185(m)	>250	11		
Chromium	ppm	ASTM D5185(m)	>10	0		
Nickel	ppm	ASTM D5185(m)	>5	<1		
Cadmium	ppm	ASTM D5185(m)		0		
Titanium	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Lead	ppm	ASTM D5185(m)		0		
Copper	ppm	ASTM D5185(m)	>75	<1		
Tin	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)	>5	<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		6		
Magnesium	ppm	ASTM D5185(m)		1		
Manganese	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		10		
Phosphorus	ppm	ASTM D5185(m)		111		
Zinc	ppm	ASTM D5185(m)		311		
Antimony	ppm	ASTM D5185(m)		13		
THICKENER/SOA	νP	method	limit/base	current	history1	history2
Aluminum	ppm	ASTM D5185(m)		<1		
Barium	ppm	ASTM D5185(m)		<1		
Calcium	ppm	ASTM D5185(m)		3		
Sodium	ppm	ASTM D5185(m)		2		
Lithium	ppm	ASTM D5185(m)		140		
Sulfur	ppm	ASTM D5185(m)		978		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>150	<1		
Potassium	ppm	ASTM D5185(m)		0		
GREASE CONDIT		method	limit/base	current	history1	history2
Grease Color		Visual*	Dk Blue	Black		
Texture		In-house*		Long fiber		
NLGI Consistency	NLGI Scale	SKF Method*	2	1-2		





GREASE ANALYSIS



SAMPLE IMAGES	method	limit/base	current	history1	history2
Color				no image	no image
Bottom				no image	no image
PrtFilter			•.	no image	no image
GRAPHS					
Ferrous Alloys		420 -	PQ		
iron		400 -	Severe		
nonnonnon nickel		380-	1		
8		360-			
6-		340 - 320 -			
4		300-			
2		280 -			
0					
0ct17/23		240 - 220 -			
		220- 200-	Abnormal		
Non-ferrous Metals		180-			
9 - copper		160-			
8 - mana isau		140-			
/ +					







EMS-TECH INC 699 DUNDAS STREET WEST BELLEVILLE, ON CA K8N 4Z2 Contact: Roger Dann, C.Tech roger.dann@ems-tech.net T: (613)966-6611 F: (613)966-6710



CALA ISO 17025:2017 Accredited Laboratory

Laboratory Sample No. Lab Number Unique Number : 5659233

bpm

ppm

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 : WC0869253 Received : 18 Oct 2023 : 02590167 Diagnosed : 20 Oct 2023 Diagnostician : Bill Quesnel Test Package : GRS 1 (Additional Tests: BottomAnalysis) To discuss this sample report, contact Customer Service at 1-800-268-2131.

Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

Contact/Location: Roger Dann, C.Tech - EMSBEL