

No relevant graphs to display

RECOMMENDATION	PROBLEMATIC TEST RESULTS					
We recommend an early resample to monitor this	Sample Status	SEVERE	ATTENTION			
condition.	NLGI Consistency	NLGI Scale SKF Method* 1	000-00	▲ 00-0		
	PrtFilter		•		no image	

Customer Id: VESTAS Sample No.: PP0835289 Lab Number: 02590812 Test Package: GRS 1



To manage this report scan the QR code

To discuss the diagnosis or test data: Bill Quesnel CLS,OMA II,MLA-III,LLA-I +1 (289)291-4641 x4641 Bill.Quesnel@wearcheck.com

To change component or sample information: Gloria Gonzalez +1 (289)291-4643 x4643 gloria.gonzalez@wearcheck.com

RECOMMENDED ACTIONS							
Action	Status	Date	Done By	Description			
Resample			?	We recommend an early resample to monitor this condition.			

HISTORICAL DIAGNOSIS

20 Sep 2021 Diag: Bill Quesnel

VIECOEITY



Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the grease. The NLGI grade has dropped 1-1/2 NLGI grades. The condition of the grease is acceptable for the time in service.





GREASE ANALYSIS

Sample Rating Trend

VISCOSITY

 \mathbf{X}

Area Saugeen Shores SP-17701 13K09

Component Grease Fluid SKF LGWM 1 (--- LTR)

DIAGNOSIS

Recommendation

We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Grease Condition

Grease consistency has changed by 2-1/2 NLGI grades from NLGI 1 to 000-00.

Contaminants

There is no indication of any contamination in the grease.

SAMPLE INFORM		method	limit/base	current	history1	history2
			mmubase			
Sample Number		Client Info		PP0835289	PP	
Sample Date	1/10	Client Info		21 Sep 2023 14	20 Sep 2021	
Machine Age Grease Age	yrs yrs	Client Info Client Info		14	0	
Grease Serviced	yı S	Client Info		Not Changd	N/A	
Sample Status				SEVERE	ATTENTION	
	_			-		
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184*	>200	920	780	
Iron	ppm	ASTM D5185(m)	>250	159	169	
Chromium	ppm	ASTM D5185(m)	>10	<1	<1	
Nickel	ppm	ASTM D5185(m)	>5	<1	<1	
Cadmium	ppm	ASTM D5185(m)		0	0	
Titanium	ppm	ASTM D5185(m)		0	0	
Vanadium	ppm	ASTM D5185(m)	0.5	0	0	
Lead	ppm	()	>25	0	0	
Copper	ppm	ASTM D5185(m)	>75	<1	<1	
Tin Silver	ppm	ASTM D5185(m)		0	0	
	ppm	ASTM D5185(m)	>5	<1	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	0	<1	<1	
Magnesium	ppm	ASTM D5185(m)	0	<1	<1	
Manganese	ppm	ASTM D5185(m)	0	<1	<1	
Molybdenum	ppm	ASTM D5185(m)		0	<1	
Phosphorus	ppm	ASTM D5185(m)	5	4	5	
Zinc	ppm	ASTM D5185(m)	20	10	16	
Antimony	ppm	ASTM D5185(m)	0	0	<1	
THICKENER/SOA	۱P	method	limit/base	current	history1	history2
Aluminum	ppm	ASTM D5185(m)	0	0	<1	
Barium	ppm	ASTM D5185(m)	0	0	0	
Calcium	ppm	ASTM D5185(m)	40	17	29	
Sodium	ppm	ASTM D5185(m)	2	2	2	
Lithium	ppm	ASTM D5185(m)	120	104	117	
Sulfur	ppm	ASTM D5185(m)	650	612	639	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>150	1	1	
Potassium	ppm	ASTM D5185(m)		17	<1	
GREASE CONDI	ΓΙΟΝ	method	limit/base	current	history1	history2
Grease Color		Visual*	Brown	Brown	Tan	
Texture		In-house*		Buttery	Short fiber	
NLGI Consistency	NLGI Scale	SKF Method*	1	• 000-00	▲ 00-0	



GREASE ANALYSIS

180

160

140

120

100

80

60 40

20

ppm

Sen 20/

Sep20/21









