

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Hydro Extrusions - S08200 Az310127

Component Hydraulic System Fluid NOT GIVEN (--- GAL)

DIAGNOSIS

Recommendation

This is a baseline read-out on the submitted sample.

Wear


{not applicable}


Contamination {not applicable}


				Oct2023		
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Batch #		Client Info		A2310127		
Machine ID		Client Info		Sales		
Department		Client Info		Machine		
Sample From		Client Info		Initial		
Production Stage		Client Info		10/20/2023		
Sample Number		Client Info		E30000579		
Sample Date		Client Info		04 Oct 2023		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>20	<1		
Chromium	ppm	ASTM D5185(m)		0		
Nickel		ASTM D5185(m)	>20	0		
Titanium	ppm	ASTM D5185(m)	>20	0		
Silver	ppm	ASTM D5185(m)		۰ <1		
Aluminum	ppm	ASTM D5185(m)	>20	<1		
Lead	ppm	ASTM D5185(m)	>20	<1		
Copper	ppm	ASTM D5185(m)	>20	4		
Tin	ppm	ASTM D5185(m)	>20	4		
Antimony	ppm	ASTM D5185(m)	>20	0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
	ppm	()				
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		1		
Barium	ppm	ASTM D5185(m)		<1		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		3		
Calcium	ppm	ASTM D5185(m)		61		
Phosphorus	ppm	ASTM D5185(m)		339		
Zinc	ppm	ASTM D5185(m)		416		
Sulfur	ppm	ASTM D5185(m)		696		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>15	0		
Sodium	ppm	ASTM D5185(m)		<1		
Potassium	ppm	ASTM D5185(m)	>20	0		
Water	%	ASTM D6304*	>0.05	0.003		
ppm Water	ppm	ASTM D6304*	>500	30.5		



OIL ANALYSIS REPORT







Viscosity @ 100°C



