

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

POWER STEERING ASIAN

New (Unused) Oil Fluid POWER STEERING - ASIAN (--- GAL)

DIAGNOSIS

Recommendation

This is a baseline read-out on the submitted sample.

Wear

{not applicable}

Contamination {not applicable}

Fluid Condition {not applicable}

| | | | C | lct2023 | | |
|------------------|----------------|---------------|------------|-------------|----------|----------|
| SAMPLE INFORM | /IATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | PP | | |
| Sample Date | | Client Info | | 23 Oct 2023 | | |
| Machine Age | hrs | Client Info | | 0 | | |
| Oil Age | hrs | Client Info | | 0 | | |
| Oil Changed | | Client Info | | N/A | | |
| Sample Status | | | | NORMAL | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185(m) | | 0 | | |
| Chromium | ppm | ASTM D5185(m) | | 0 | | |
| Nickel | ppm | ASTM D5185(m) | | <1 | | |
| Titanium | ppm | ASTM D5185(m) | | 0 | | |
| Silver | ppm | ASTM D5185(m) | | <1 | | |
| Aluminum | ppm | ASTM D5185(m) | | 0 | | |
| Lead | ppm | ASTM D5185(m) | | 0 | | |
| Copper | ppm | ASTM D5185(m) | | 0 | | |
| Tin | ppm | ASTM D5185(m) | | 0 | | |
| Antimony | ppm | ASTM D5185(m) | | 0 | | |
| Vanadium | ppm | ASTM D5185(m) | | 0 | | |
| Beryllium | ppm | ASTM D5185(m) | | 0 | | |
| Cadmium | ppm | ASTM D5185(m) | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185(m) | | 70 | | |
| Barium | ppm | ASTM D5185(m) | | 0 | | |
| Molybdenum | ppm | ASTM D5185(m) | | 0 | | |
| Manganese | ppm | ASTM D5185(m) | | 0 | | |
| Magnesium | ppm | ASTM D5185(m) | | <1 | | |
| Calcium | ppm | ASTM D5185(m) | | 121 | | |
| Phosphorus | ppm | ASTM D5185(m) | | 205 | | |
| Zinc | ppm | ASTM D5185(m) | | 10 | | |
| Sulfur | ppm | ASTM D5185(m) | | 1009 | | |
| Lithium | ppm | ASTM D5185(m) | | <1 | | |
| CONTAMINANTS | ; | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185(m) | | 3 | | |
| Sodium | ppm | ASTM D5185(m) | | <1 | | |
| Potassium | ppm | ASTM D5185(m) | >20 | <1 | | |
| INFRA-RED | | method | limit/base | current | history1 | history2 |
| Soot % | % | ASTM D7844* | | 0 | | |
| Nitration | Abs/cm | ASTM D7624* | | 4.2 | | |
| Sulfation | Abs/.1mm | ASTM D7415* | | 17.6 | | |
| FLUID DEGRADA | | method | limit/base | current | history1 | history2 |
| Oxidation | Abs/.1mm | ASTM D7414* | | 25.9 | | |
| Base Number (BN) | mg KOH/g | ASTM D2896* | | 2.92 | | |
| | ingitority | | | | | |



OIL ANALYSIS REPORT

| Ba | se N | umb | ber | | | | | | | | | |
|--------------------------------------------------------|------|-----|-----|------|------|------|------|------|------|------|------|---------|
| (B/HC | | | | | |
| (B),2.5 - 2.0 - 3.5 - 1.5 - 1.0 - 3.5 - | | | | | | | | | | | | |
| -0.1 Mmp | | | | | | | | | | | | |
| 0.0 | | | | | | | | | | | | |
| 0ct23/23 | | | | | | | | | | | | 0000000 |

| VISUAL | | methou | iiiiii/base | Current | TIIStOLA | THStory Z |
|---------------------|----------|---------|---------------------------------------------------------------------------|---------|-----------|-----------|
| White Metal | scalar | Visual* | NONE | NONE | | |
| Yellow Metal | scalar | Visual* | NONE | NONE | | |
| Precipitate | scalar | Visual* | NONE | NONE | | |
| Silt | scalar | Visual* | NONE | NONE | | |
| | | | | | | |
| Debris | scalar | Visual* | NONE | NONE | | |
| Sand/Dirt | scalar | Visual* | NONE | NONE | | |
| Appearance | scalar | Visual* | NORML | NORML | | |
| Odor | scalar | Visual* | NORML | NORML | | |
| SAMPLE IMAGES | ; | method | limit/base | current | history1 | history2 |
| Color | | | | | no image | no image |
| Bottom | | | | | no image | no image |
| GRAPHS | | | | | | |
| Ferrous Alloys | | | | | | |
| Non-ferrous Metals | 5 | | 0ct23/23 | | | |
| Viscosity @ 40°C | | | 0453/53 | | | |
| Abnormal Drawnal | | | 2.5. 2.5. 1.5. 1.1. 1.1. 1.1. 1.1. 1.0. 1.0. 1 | | | |
| WearCheck - C8-117 | 75 Apple | | 0ct23/23 | 7L 5H9 | WAKEFIELD | |



 Accredited Laboratory
 Unique Number
 : 5668651
 Diagnostician
 : Bill Quesnel

 Test Package
 : TEST (Additional Tests: FT-IR, ICP, TBN)

 To discuss this sample report, contact Customer Service at 1-800-268-2131.

 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.

 Validity of results and interpretation are based on the sample and information as supplied.

Diagnosed

: 26 Oct 2023

: 02591572

bpm

bpm

cSt (40°C)

Laboratory

Sample No.

Lab Number

3620 LAKESHORE BLVD WEST TORONTO, ON CA M8W 1P2 Contact: Ken Wood kwood@wakefieldcanada.ca T: (416)574-6665 F: (416)252-7315

CALA

ISO 17025:2017