

## **OIL ANALYSIS REPORT**

Sample Rating Trend

NORMAL

## POWER STEERING WAKEFIELD Component

New (Unused) Oil

POWER STEERING - WAKEFIELD (--- GAL)

DIAGNOSIS	SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Recommendation	Sample Number		Client Info		PP		
This is a baseline read-out on the submitted	Sample Date		Client Info		23 Oct 2023		
sample.	Machine Age	hrs	Client Info		0		
Wear	Oil Age	hrs	Client Info		0		
{not applicable}	Oil Changed		Client Info		N/A		
Contamination	Sample Status				NORMAL		
{not applicable}	WEAR METALS		method	limit/base	current	history1	history2
Fluid Condition	Iron	ppm	ASTM D5185(m)		0		
{not applicable}	Chromium	ppm	ASTM D5185(m)		0		
	Nickel	ppm	ASTM D5185(m)		<1		
	Titanium	ppm	ASTM D5185(m)		0		
	Silver	ppm	ASTM D5185(m)		<1		
	Aluminum	ppm	ASTM D5185(m)		0		
	Lead	ppm	ASTM D5185(m)		<1		
	Copper	ppm	ASTM D5185(m)		<1		
	Tin	ppm	ASTM D5185(m)		0		
	Antimony	ppm	ASTM D5185(m)		0		
	Vanadium	ppm	ASTM D5185(m)		0		
	Beryllium	ppm	ASTM D5185(m)		0		
	Cadmium	ppm	ASTM D5185(m)		0		
	ADDITIVES		method	limit/base	current	history1	history2
	Boron	ppm	ASTM D5185(m)		90		
	Barium	ppm	ASTM D5185(m)		0		
	Molybdenum	ppm	ASTM D5185(m)		0		
	Manganese	ppm	ASTM D5185(m)		0		
	Magnesium	ppm	ASTM D5185(m)		0		
	Calcium	ppm	ASTM D5185(m)		62		
	Phosphorus	ppm	ASTM D5185(m)		184		
	Zinc	ppm	ASTM D5185(m)		<1		
	Sulfur	ppm	ASTM D5185(m)		665		
	Lithium	ppm	ASTM D5185(m)		<1		
	CONTAMINANTS		method	limit/base	current	history1	history2
	Silicon	ppm	ASTM D5185(m)		6		
	Sodium	ppm	ASTM D5185(m)		<1		
	Potassium	ppm	ASTM D5185(m)	>20	<1		
	INFRA-RED		method	limit/base	current	history1	history2
	Soot %	%	ASTM D7844*		0		
	Nitration	Abs/cm	ASTM D7624*		2.2		
	Sulfation	Abs/.1mm	ASTM D7415*		17.0		
	FLUID DEGRADA	TION	method	limit/base	current	history1	history2
	Oxidation	Abs/.1mm	ASTM D7414*		9.1		
	Base Number (BN)	mg KOH/g	ASTM D2896*		1.51		



## **OIL ANALYSIS REPORT**

VISUAL

1.6		a	se	9	N	lu	ır	n	b	e	r																									
1.4	7											 																								Ţ.
Base Number (mg KOH/g) 9.0 0.1 0.1 0.4 0.4 0.4 0.4 0.4 0.4 0.4 0.4 0.4 0.4	÷																																			
p_1.0																																				
ja 0.8	÷																																			
J 0.6																																				
器 0.4	hi																																			
0.2																																				
0.0	4				_		_		_		_	 _	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	 	_	_	_	_	 	 	+
	0ct23/23																																			0ct23/23

	White Metal		Visual*	NONE	NONE		
	Yellow Metal		Visual*	NONE	NONE		
	Precipitate		Visual*	NONE	NONE		
	Silt		Visual*	NONE	NONE		
	Debris		Visual*	NONE	NONE		
	Sand/Dirt		Visual*	NONE	NONE		
0ct23/23	Appearance		Visual*	NORML	NORML		
00	Odor	scalar	Visual*	NORML	NORML		
	SAMPLE IMAGES	3	method	limit/base	current	history1	history2
	Color					no image	no image
	Bottom					no image	no image
	GRAPHS						
	Ferrous Alloys						
	8 - iron 6 - nickel						
	Non-ferrous Metals	S		0ct23/23			
	еба 4 2 0 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2			lct23/23			
	Viscosity @ 40°C			0	Base Number		
	Abnormal			1.6			
90	Abnormal Abnormal 80 60 40 20			(F) 1.4- Ho (F) 1.2- (F) 1.0- (F)			
	0			0.2	•		
	-20			0.0	/23		ς Γ
CALA Laboratory Sample No.		75 Appleb Received Diagnosed	: 24	lington, ON L7 Oct 2023 Oct 2023		20 LAKESHOR	CANADA INC E BLVD WES FORONTO, OF

Report Id: WAKTOR [WCAMIS] 02591574 (Generated: 10/26/2023 15:16:03) Rev: 1

Validity of results and interpretation are based on the sample and information as supplied.

Contact/Location: Natalee Davis - WAKTOR

F: (416)354-4515