




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
[41868790]

Machine Id
7403

Component
Diesel Engine

Fluid
DIESEL ENGINE OIL SAE 10W30 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			WC0853505	WC0796655	WC0737684
Sample Date	Client Info			22 Oct 2023	16 Mar 2023	23 Oct 2022
Machine Age	kms	Client Info		201107	181072	160607
Oil Age	kms	Client Info		0	0	0
Oil Changed	Client Info			Changed	Not Changd	Changed
Sample Status				NORMAL	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>2.0		<1.0	<1.0	<1.0
Glycol	WC Method			NEG	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>127	31	15	17
Chromium	ppm	ASTM D5185(m)	>3	1	<1	<1
Nickel	ppm	ASTM D5185(m)	>30	<1	0	<1
Titanium	ppm	ASTM D5185(m)	>2	0	<1	<1
Silver	ppm	ASTM D5185(m)	>2	<1	0	0
Aluminum	ppm	ASTM D5185(m)	>59	6	4	4
Lead	ppm	ASTM D5185(m)	>29	4	<1	2
Copper	ppm	ASTM D5185(m)	>135	17	8	15
Tin	ppm	ASTM D5185(m)	>2	<1	<1	<1
Antimony	ppm	ASTM D5185(m)		0	<1	0
Vanadium	ppm	ASTM D5185(m)		0	0	0
Beryllium	ppm	ASTM D5185(m)		0	0	0
Cadmium	ppm	ASTM D5185(m)		0	0	0

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	250	18	51	37
Barium	ppm	ASTM D5185(m)	10	<1	0	0
Molybdenum	ppm	ASTM D5185(m)	100	3	4	4
Manganese	ppm	ASTM D5185(m)		<1	<1	<1
Magnesium	ppm	ASTM D5185(m)	450	748	741	713
Calcium	ppm	ASTM D5185(m)	3000	1383	1418	1395
Phosphorus	ppm	ASTM D5185(m)	1150	656	767	750
Zinc	ppm	ASTM D5185(m)	1350	780	765	780
Sulfur	ppm	ASTM D5185(m)	4250	2426	2601	2564
Lithium	ppm	ASTM D5185(m)		<1	<1	<1


CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>18	8	7	7
Sodium	ppm	ASTM D5185(m)		4	3	3
Potassium	ppm	ASTM D5185(m)	>20	8	6	7

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	ASTM D7844*	>3	2.9	1.4	1.5
Nitration	Abs/cm	ASTM D7624*	>20	11.9	10.0	10.3
Sulfation	Abs/.1mm	ASTM D7415*	>30	28.1	23.9	22.8

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	ASTM D7414*	>25	17.7	13.8	14.5











OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D7279(m)	10.9	12.2	11.6

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : WC0853505
Lab Number : 02591592
Unique Number : 5668671
Test Package : MOB 1

Rush Truck Centres
 7450 Torbram Rd.
 Mississauga, ON
 CA L4T 1G9
 Contact: Serdar Okur
 sokur@rushtruckcentres.ca
 T: (905)671-7600
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.