


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



VOLVO 30T HDTR825

Component

Brake

MOBIL 56 (--- GAL)

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.

Fluid Condition

The condition of the fluid is acceptable for the time in service.

				Dec2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0883861		
Sample Date		Client Info		07 Dec 2023		
Machine Age	hrs	Client Info		21253		
Oil Age	hrs	Client Info		0		
Oil Changed	0	Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>350	11		
Chromium	ppm	ASTM D5185(m)	>5	0		
Nickel	ppm	ASTM D5185(m)	>5	<1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		1		
Aluminum	ppm	ASTM D5185(m)	>8	2		
Lead	ppm	ASTM D5185(m)	>10	4		
Copper	ppm	ASTM D5185(m)	>150	139		
Tin	ppm	ASTM D5185(m)	>5	0		
Antimony	ppm	ASTM D5185(m)	>5	0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		82		
Barium	ppm	ASTM D5185(m)		<1		
Molybdenum	ppm	ASTM D5185(m)		<1		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		10		
Calcium	ppm	ASTM D5185(m)		3001		
Phosphorus	ppm	ASTM D5185(m)		1043		
Zinc	ppm	ASTM D5185(m)		1143		
Sulfur	ppm	ASTM D5185(m)		3678		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>400	11		
Sodium	ppm	ASTM D5185(m)		2		
Datasairus		ACTM DE40E(++)	00	^		


0

Potassium

ppm ASTM D5185(m) >20



OIL ANALYSIS REPORT



VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	VLITE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*	>0.2	NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	TIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)		52.5		

SAMPLE IMAGES	method	limit/base	current	history1	history2
Color				no image	no image
Bottom				no image	no image
GRAPHS					

GRAPHS		
Iron (ppm)	Lead (ppm)	
Severe	Severe	
E 500 Abnormal	Abnomal	
Dec1/23	Dec7/23	- 1/23
1990	Dec7,	Dec7/2;
Aluminum (ppm)	Chromium (ppm)	
Severe	E 10 Severe	
E 10 - Abnormal		
O Dec7/23 T	Dec7/23	Dec7/23
Dec	Dec7,	Dec
Copper (ppm)	Silicon (ppm)	
Severe E 200 - Abnormal	E 500 - Annormal	
Dec7/23 -	733 .	Dec7/23 -
		De
Viscosity @ 40°C	Additives	
Abnormal Abnormal	3000 - calcium 2000 - calcium 2000 - calcium	
ق ا	2000	
Dec7/23	Dec7/23	Dec7/23
ã	o o	ă



CALA ISO 17025:2017 Accredited Laboratory

Laboratory Sample No. Lab Number Unique Number : 5696700

Test Package : MOB 1

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 : WC0883861 : 02603615

Validity of results and interpretation are based on the sample and information as supplied.

Recieved : 15 Dec 2023 Diagnosed : 18 Dec 2023 Diagnostician : Kevin Marson

Agnico Eagle Canada 1350 Government Rd. W, MACASSA COMPLEX

Kirkland Lake, ON CA P2N 3J1

Contact: Mitch Lamontagne

AEM_KL_macassaoilsampleresults@agnicoeagle.com

T: (705)567-5208 F: (705)567-5221

To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.