

# **OIL ANALYSIS REPORT**

# Sample Rating Trend

### **NORMAL**



# DOOSAN DX140LC DX140

**Left Final Drive** 

GEAR OIL SAE 80W90 (--- GAL)

### Recommendation

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) GEAR OIL SAE 80W90. Please confirm.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the


### **Fluid Condition**

The condition of the oil is acceptable for the time in service.

				Aug2023		
CAMPLE INFORM	AATIONI				la trade a const	h:-10
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0811303		
Sample Date		Client Info		02 Aug 2023		
Machine Age	hrs	Client Info		1052		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATIO	V	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>500	155		
Chromium	ppm	ASTM D5185(m)	>10	<1		
Nickel	ppm	ASTM D5185(m)	>10	<1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>25	7		
Lead	ppm	ASTM D5185(m)	>25	0		
Copper	ppm	ASTM D5185(m)	>50	<1		
Tin	ppm	ASTM D5185(m)	>10	0		
Antimony	ppm	ASTM D5185(m)	>5	0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	400	11		
Barium	ppm	ASTM D5185(m)	200	3		
Molybdenum	ppm	ASTM D5185(m)	12	0		
Manganese	ppm	ASTM D5185(m)		3		
Magnesium	ppm	ASTM D5185(m)	12	15		
Calcium	ppm	ASTM D5185(m)	150	60		
Phosphorus	ppm	ASTM D5185(m)	1650	1940		
Zinc	ppm	ASTM D5185(m)	125	36		
Sulfur	ppm	ASTM D5185(m)	22500	20093		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>75	27		
Sodium	ppm	ASTM D5185(m)	>170	3		
Potassium	ppm	ASTM D5185(m)	>20	10		



## **OIL ANALYSIS REPORT**



VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	VLITE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
<b>Emulsified Water</b>	scalar	Visual*	>0.2	NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	TES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	143	148		

SAMPLE IMAGES	method	limit/base	current	history1	history2
Color				no image	no image
Bottom				no image	no image

GRAPHS		
Iron (ppm)	Lead (ppm)	
Severe	E 100 - Severe	
Abnomal	50 Abnormal	
Aug2723	Aug2723 +	Aug2/23
Aluminum (ppm)	Chromium (ppm)	
Severe	E 20	
50 Abnormal	Abnormal	
Aug2/23 -	Aug2/23 +	Aug2/23
Copper (ppm)	Silicon (ppm)	
Severe	Severe Severe	
Abnormal	Abnormal	
Aug2/23	Aug2/23 -	Aug2/23
Viscosity @ 40°C	Additives	
	calcium	
S Abnormal	E 1000 - managaman phosphorus	
4ug2/23 100 100 100 100 100 100 100 100 100 10	Aug2/23 +	Aug2/23
Aug	Aug	Aug



**CALA** ISO 17025:2017 Accredited Laboratory

Laboratory Sample No. Lab Number Unique Number : 5697833 Test Package : MOB 1

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 : WC0811303 : 02604748

Recieved

: 21 Dec 2023 Diagnosed : 21 Dec 2023 Diagnostician : Wes Davis

To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

**CONESTOGA COLLEGE** 

460 Speedvale Drive Guelph, ON CA N1H 0A8 Contact: Duane Houle dhoule@conestogac.on.ca T: (519)498-7450