

OIL ANALYSIS REPORT

Sample Rating Trend





CATERPILLAR 740GL HDTR0836

Rear Left Final Drive Fluid MOBIL 56 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition


The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0879670		
Sample Date		Client Info		18 Dec 2023		
Machine Age	hrs	Client Info		725		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATION	٧	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>800	85		
Chromium	ppm	ASTM D5185(m)	>10	1		
Nickel	ppm	ASTM D5185(m)	>5	<1		
Titanium	ppm	ASTM D5185(m)	>15	0		
Silver	ppm	ASTM D5185(m)	>2	0		
Aluminum	ppm	ASTM D5185(m)	>75	2		
Lead	ppm	ASTM D5185(m)	>10	<1		
Copper	ppm	ASTM D5185(m)	>75	21		
Tin	ppm	ASTM D5185(m)	>8	<1		
Antimony	ppm	ASTM D5185(m)	>50	0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		2		
Barium	ppm	ASTM D5185(m)		<1		
Molybdenum	ppm	ASTM D5185(m)		4		
Manganese	ppm	ASTM D5185(m)		1		
Magnesium	ppm	ASTM D5185(m)		9		
Calcium	ppm	ASTM D5185(m)		3235		
Phosphorus	ppm	ASTM D5185(m)		1026		
Zinc	ppm	ASTM D5185(m)		1207		
Sulfur	ppm	ASTM D5185(m)		7304		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>400	19		
Sodium	ppm	ASTM D5185(m)		2		
Potassium	ppm	ASTM D5185(m)	>20	2		



OIL ANALYSIS REPORT

VISUAL



		VISUAL		method	limit/base	current	history1	history2
		White Metal	scalar	Visual*	NONE	NONE		
		Yellow Metal	scalar	Visual*	NONE	NONE		
		Precipitate	scalar	Visual*	NONE	NONE		
		Silt	scalar	Visual*	NONE	NONE		
		Debris	scalar	Visual*	NONE	NONE		
		Sand/Dirt	scalar	Visual*	NONE	NONE		
	Dec18/23	Appearance	scalar	Visual*	NORML	NORML		
	Deci	Odor	scalar	Visual*	NORML	NORML		
		Emulsified Water	scalar	Visual*	>0.2	NEG		
		Free Water	scalar	Visual*		NEG		
		FLUID PROPERT	TIES	method	limit/base	current	history1	history2
					innibuse		Thotory I	motoryz
		Visc @ 40°C	cSt	ASTM D7279(m)		95.8		
		SAMPLE IMAGES	S	method	limit/base	current	history1	history2
		Color					no image	no image
		Bottom					no image	no image
		GRAPHS						
	20	Iron (ppm)			30	Lead (ppm)		
	톱 10	Severe			ع 20 10			
		0						
		Dec18/23			Dec18/23	Dec18/23		Dec18/23
		Aluminum (ppm)				Chromium (pp	om)	
	2	Severe			30	0		
	<u>ط</u> 1	00 - Abnormal			ور 10 10	Abnormal		1
		0				1		
		Jec18/23			Dec18/23	Dec18/23		Dec18/23
		Deci			Dec1	Decl		Decl
		Copper (ppm)				Silicon (ppm)		
	2	Severe			1000	Severe		
	L 1	00 - Abnormal			Ē 500	Abnormal		
		0			— (
		Dec18/23			Dec18/23	Dec18/23		Dec18/23
		Dec			Dec	Dec		Dec
	2	Viscosity @ 40°C			4000	Additives		
		Abnormal			4000 = 3000	calcium		
	(C) (10°C) SS	00 - Abnormal			E 3000	- management phosphorus	1	
	5	04			1000		~	-
		Dec18/23			Dec18/23	Dec18/23		Dec18/23
		D.			Dei	ei D		Dec
	Sample No. Lab Number Unique Number Test Package sample report, co	: 02605368 : 5698453 : MOB 1 ontact Customer Serve	Recieved Diagnose Diagnost	l : 27 ed : 27 ician : Kev	Dec 2023 Dec 2023 rin Marson	1350 Gov AEM_KL_n	ernment Rd. W, MA Kirł Contact: Mito nacassaoilsampleresul	kland Lake, ON CA P2N 3J1 ch Lamontagne ts@agnicoeagle.com
		of accreditation, (m) m ion are based on the s						(705)567-5208 (705)567-5221