

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL





Abbott Point of Care Ch#6 [4500054809] TRANE N09M02355

Component Chiller

REFRIG COMP OIL ISO 46 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

The water content is negligible. There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

) 46 (GAL)						
, ,				Jun2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GTT0001366		
Sample Date		Client Info		21 Jun 2023		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
ron	ppm	ASTM D5185(m)	>8	4		
Chromium	ppm	ASTM D5185(m)	>2	0		
lickel	ppm	ASTM D5185(m)		<1		
- itanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)	>2	0		
lluminum	ppm	ASTM D5185(m)	>3	<1		
ead	ppm	ASTM D5185(m)	>2	0		
Copper	ppm	ASTM D5185(m)	>8	2		
in	ppm	ASTM D5185(m)	>4	<1		
ntimony	ppm	ASTM D5185(m)		0		
anadium/	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	5	<1		
arium	ppm	ASTM D5185(m)	5	0		
lolybdenum	ppm	ASTM D5185(m)	5	0		
Manganese	ppm	ASTM D5185(m)		0		
/lagnesium	ppm	ASTM D5185(m)	5	0		
Calcium	ppm	ASTM D5185(m)	12	<1		
hosphorus	ppm	ASTM D5185(m)	12	2		
linc	ppm	ASTM D5185(m)	12	35		
Sulfur	ppm	ASTM D5185(m)	1000	0		
ithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>15	13		
Sodium	ppm	ASTM D5185(m)		<1		
Potassium	ppm	ASTM D5185(m)	>20	0		
pm Water	ppm	ASTM D6304*	>100	15		

FLUID DEGRADATION method

mg KOH/g ASTM D974* 0.10

Acid Number (AN)

0.07



OIL ANALYSIS REPORT

VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	46	36.2		
SAMPLE IMAGES		method	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image
GRAPHS						



 Sample No.
 : GTT0001366
 Recieved
 : 28 Dec 2023

 Lab Number
 : 02605644
 Diagnosed
 : 05 Jan 2024

 Unique Number
 : 5698729
 Diagnostician
 : Bill Quesnel

 Test Package
 : IND 2 (Additional Tests: KV40)

To discuss this sample report, contact Customer Service at 1-905-847-9300 Ext 26.

Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.

Damages: Seller shall in no event be liable for special, incidental, or consequential damages, of a commercial nature, resulting from any cause.

Carrier Commerical Service

C/O Conduent Div of Carrier Canada, 1-2740 Matheson Blvd

Mississauga, ON CA L4W 4X3

Contact: Brian Raymundo

Brian.Raymundo@carrier.com T:

nature, resulting from any cause.

Report Id: GTT0000224 [WCAMIS] 02605644 (Generated: 01/08/2024 08:20:07) Rev: 1

Contact/Location: Brian Raymundo - GTT0000224