


OIL ANALYSIS REPORT

Sample Rating Trend



Praxair #2 **CARRIER 3708Q18028** Component



COMP OIL (ESTER) ISO 68 (--- GAL)

DIAGNOSIS	SAMPLE INFORI	MATION	method	limit/base	current	history1	history2
A Recommendation	Sample Number		Client Info		GTT0001371	GTT12003	GTT12004
If not recently done change any filter driers to reduce moisture level. We recommend an early resample to monitor this condition. Please specify the brand, type, and viscosity of the oil on your next sample.	Sample Date		Client Info		14 Jun 2023	05 Apr 2023	07 Dec 2021
	Machine Age	hrs	Client Info		0		
	Oil Age	hrs	Client Info		0		
	Oil Changed		Client Info		N/A	N/A	N/A
Wear	Sample Status				ABNORMAL	NORMAL	NORMAL
All component wear rates are normal.	WEAR METALS		method	limit/base	current	history1	history2
Contamination There is a moderate concentration of water present in the oil.	Iron	ppm	ASTM D5185(m)	>8	0	<1	<1
	Chromium	ppm	ASTM D5185(m)	>2	0	<1	<1
	Nickel	ppm	ASTM D5185(m)		<1		
Fluid Condition	Titanium	ppm	ASTM D5185(m)		0		
The AN level is acceptable for this fluid. The oil is still serviceable provided that the contaminant(s) can be reduced to acceptable levels.	Silver	ppm	ASTM D5185(m)	>2	0		
	Aluminum	ppm	ASTM D5185(m)		<1	<1	<1
	Lead	ppm	ASTM D5185(m)		<1	<1	<1
	Copper	ppm	ASTM D5185(m)		2	7	1
	Tin	ppm	ASTM D5185(m)		0	<1	<1
	Antimony	ppm	ASTM D5185(m)		0		
	Vanadium	ppm	ASTM D5185(m)		0		
	Beryllium	ppm	ASTM D5185(m)		0		
	Cadmium	ppm	ASTM D5185(m)		0		
	ADDITIVES		method	limit/base	current	history1	history2
	Boron	ppm	ASTM D5185(m)	5	0		
	Barium	ppm	ASTM D5185(m)		0		
	Molybdenum	ppm	ASTM D5185(m)		0		
	Manganese	ppm	ASTM D5185(m)		0		
	Magnesium	ppm	ASTM D5185(m)	5	0		
	Calcium	ppm	ASTM D5185(m)		0		
	Phosphorus	ppm	ASTM D5185(m)		1191		
	Zinc	ppm	ASTM D5185(m)		5	7	2
	Sulfur	ppm	ASTM D5185(m)	100	0		
	Lithium	ppm	ASTM D5185(m)		<1		
	CONTAMINANTS	6	method	limit/base	current	history1	history2
	Silicon	ppm	ASTM D5185(m)	>15	8		
	Sodium	ppm	ASTM D5185(m)	210	ہ <1		
	Potassium	ppm	ASTM D5185(m) ASTM D5185(m)	>20	< 1 0		
	ppm Water	ppm	ASTM D5185(III) ASTM D6304*		▲ 339	1.1	134
							-
	FLUID DEGRAD	ATION	method	limit/base	current	history1	history2
	Acid Number (AN)	mg KOH/g	ASTM D974*	0.40	0.08	0.054	0.047

Report Id: GTT0000224 [WCAMIS] 02605669 (Generated: 01/08/2024 08:23:22) Rev: 1



OIL ANALYSIS REPORT

VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	68	95.1		
SAMPLE IMAGES	6	method	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image
GRAPHS			_			



Sample No. : GTT0001371 Recieved : 28 Dec 2023 C/O Conduent Div of Carrier Canada, 1-2740 Matheson Blvd : 06 Jan 2024 Lab Number : 02605669 Diagnosed Unique Number : 5698754 Diagnostician : Bill Quesnel Test Package : IND 2 (Additional Tests: KV40) Contact: Brian Raymundo To discuss this sample report, contact Customer Service at 1-905-847-9300 Ext 26. Brian.Raymundo@carrier.com Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Damages: Seller shall in no event be liable for special, incidental, or consequential damages, of a commercial nature, resulting from any cause.

Report Id: GTT0000224 [WCAMIS] 02605669 (Generated: 01/08/2024 08:23:22) Rev: 1

Contact/Location: Brian Raymundo - GTT0000224

Carrier Commerical Service

Mississauga, ON

CA L4W 4X3

T:

F:

Page 2 of 2