




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Area  
**[1495110]**  
 Machine Id  
**NOVA 1715**  
 Component  
**Natural Gas Engine**  
 Fluid  
**VALVOLINE PREMIUM BLUE 9200 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The condition of the oil is acceptable for the time in service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>WC0878046</b>	WC0849835	WC0811465
Sample Date	Client Info		<b>01 Jan 2024</b>	26 Sep 2023	26 Jun 2023
Machine Age	kms	Client Info	<b>392059</b>	0	0
Oil Age	kms	Client Info	<b>0</b>	0	0
Oil Changed	Client Info		<b>N/A</b>	N/A	N/A
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.1	<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185(m)	>50	<b>10</b>	13	10
Chromium	ppm	ASTM D5185(m)	>4	<b>1</b>	1	1
Nickel	ppm	ASTM D5185(m)	>2	<b>&lt;1</b>	0	<1
Titanium	ppm	ASTM D5185(m)		<b>0</b>	0	1
Silver	ppm	ASTM D5185(m)	>3	<b>&lt;1</b>	1	1
Aluminum	ppm	ASTM D5185(m)	>9	<b>2</b>	3	2
Lead	ppm	ASTM D5185(m)	>30	<b>&lt;1</b>	4	1
Copper	ppm	ASTM D5185(m)	>35	<b>9</b>	13	11
Tin	ppm	ASTM D5185(m)	>4	<b>0</b>	<1	<1
Antimony	ppm	ASTM D5185(m)		<b>0</b>	0	0
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0	0
Beryllium	ppm	ASTM D5185(m)		<b>0</b>	0	0
Cadmium	ppm	ASTM D5185(m)		<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185(m)		<b>5</b>	4	6
Barium	ppm	ASTM D5185(m)		<b>0</b>	<1	0
Molybdenum	ppm	ASTM D5185(m)		<b>54</b>	57	50
Manganese	ppm	ASTM D5185(m)		<b>0</b>	0	<1
Magnesium	ppm	ASTM D5185(m)		<b>819</b>	896	802
Calcium	ppm	ASTM D5185(m)		<b>1276</b>	1339	1216
Phosphorus	ppm	ASTM D5185(m)		<b>684</b>	751	675
Zinc	ppm	ASTM D5185(m)		<b>880</b>	951	839
Sulfur	ppm	ASTM D5185(m)		<b>2011</b>	1947	1762
Lithium	ppm	ASTM D5185(m)		<b>&lt;1</b>	<1	<1

## CONTAMINANTS

	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185(m)	>+100	<b>5</b>	6	5
Sodium	ppm	ASTM D5185(m)		<b>6</b>	5	4
Potassium	ppm	ASTM D5185(m)	>20	<b>2</b>	2	3

## INFRA-RED


	method	limit/base	current	history1	history2	
Soot %	%	ASTM D7844*		<b>0</b>	0	0
Nitration	Abs/cm	ASTM D7624*	>20	<b>13.2</b>	13.9	13.1
Sulfation	Abs/.1mm	ASTM D7415*	>30	<b>24.7</b>	26.0	24.6

## FLUID DEGRADATION

	method	limit/base	current	history1	history2	
Oxidation	Abs/.1mm	ASTM D7414*	>25	<b>22.8</b>	24.9	23.3











# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.1	NEG	NEG
Free Water	scalar	Visual*		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D7279(m)	14.8	<b>14.2</b>	14.1	14.1

## GRAPHS



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : WC0878046  
**Lab Number** : 02605816  
**Unique Number** : 5698901  
**Test Package** : MOB 1

**CITY OF HAMILTON**  
 2200 UPPER JAMES., MOUNTAIN TRANSIT STOREROOM  
 MOUNT HOPE, ON  
 CA L0R 1W0  
 Contact: Jeff Parr  
 jeff.parr@hamilton.ca  
 T: (905)546-2424  
 F: (905)679-4502

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.