


OIL ANALYSIS REPORT

Machine Id **7530** Component **Diesel Engine** CHEVRON DELO 400 SAE 10W30 (--- GAL)



Recommendation

Resample at the next service interval to monitor.

Metal levels are typical for a new component breaking in.

Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

				Dec2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0796587		
Sample Date		Client Info		13 Dec 2023		
Machine Age	kms	Client Info		93961		
Oil Age	kms	Client Info		0		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATION	1	method	limit/base	current	history1	history2
Fuel		WC Method	>3.0	<1.0		
Water		WC Method	>0.2	NEG		
Glycol		WC Method		NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>90	29		
Chromium	ppm	ASTM D5185(m)	>20	2		
Nickel	ppm	ASTM D5185(m)	>2	<1		
Titanium	ppm	ASTM D5185(m)	>2	0		
Silver	ppm	ASTM D5185(m)	>2	0		
Aluminum	ppm	ASTM D5185(m)	>20	57		
Lead	ppm	ASTM D5185(m)	>40	<1		
Copper	ppm	ASTM D5185(m)	>330	10		
Tin	ppm	ASTM D5185(m)	>15	0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		66		
Barium	ppm	ASTM D5185(m)		<1		
Molybdenum	ppm	ASTM D5185(m)		4		
Manganese	ppm	ASTM D5185(m)		<1		
Magnesium	ppm	ASTM D5185(m)		550		
Calcium	ppm	ASTM D5185(m)	1000	1549		
Phosphorus	ppm	ASTM D5185(m)	1260	767		
Zinc	ppm	ASTM D5185(m)	1400	877		
Sulfur	ppm	ASTM D5185(m)		2724		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>25	8		
Sodium	ppm	ASTM D5185(m)	00	3		
Potassium	ppm	ASTM D5185(m)	>20	106		
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	ASTM D7844*	>6	0.1		
Nitration	Abs/cm	ASTM D7624*	>20	9.5		
Sulfation	Abs/.1mm	ASTM D7415*	>30	21.3		



OIL ANALYSIS REPORT





CALA ISO 17025:2017 Accredited Laboratory

Laboratory Sample No. Lab Number Unique Number : 5707315

: 02606229

: WC0796587 Test Package : MOB 1

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 Recieved : 03 Jan 2024 : 03 Jan 2024

Diagnosed Diagnostician : Wes Davis

To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

Rush Truck Centres 7450 Torbram Rd. Mississauga, ON **CA L4T 1G9** Contact: Serdar Okur sokur@rushtruckcentres.ca

T: (905)671-7600