

## **OIL ANALYSIS REPORT**

Sample Rating Trend



Fluid

## Area Analyse D`huile Ch#2A [0068796-H00653] CARRIER 3919Q26053(2A) Component



WATER

**REFRIGERATION OIL (POE) (--- GAL)** 

DIAGNOSIS	SAMPLE INFORM	NATION	method				history2
A Recommendation	Sample Number		Client Info		GTT0001315		
If not recently done change any filter driers to	Sample Date		Client Info		03 Nov 2023		
reduce moisture level. Resample at the next service	Machine Age	hrs	Client Info		0		
interval to monitor. Please specify the brand, type,	Oil Age	hrs	Client Info		0		
and viscosity of the oil on your next sample.	Oil Changed		Client Info		N/A		
Wear	Sample Status				ATTENTION		
All component wear rates are normal.	WEAR METALS		method	limit/base	current	history1	history2
Contamination The elevated moisture content is associated with POE oils which are hygroscopic, and can absorb moisture from sampling and processing.	Iron	ppm	ASTM D5185(m)		2		
	Chromium	ppm	ASTM D5185(m)		0		
	Nickel	ppm	ASTM D5185(m)	~~	<1		
Fluid Condition	Titanium	ppm	ASTM D5185(m)		0		
The AN level is acceptable for this fluid. The	Silver	ppm	ASTM D5185(m)	>2	0		
condition of the oil is suitable for further service.	Aluminum	ppm	ASTM D5185(m)		<1		
	Lead	ppm	ASTM D5185(m)		1		
	Copper	ppm	ASTM D5185(m)		<1		
	Tin	ppm	ASTM D5185(m)		0		
	Antimony	ppm	ASTM D5185(m)	~7	0		
	Vanadium	ppm	ASTM D5185(m)		0		
	Beryllium	ppm	ASTM D5185(m)		0		
	Cadmium	ppm	ASTM D5185(m)		0		
	ADDITIVES		method	limit/base	current	history1	history2
	Boron	ppm	ASTM D5185(m)		1		
	Barium	ppm	ASTM D5185(m)		0		
	Molybdenum	ppm	ASTM D5185(m)		0		
	Manganese	ppm	ASTM D5185(m)		0		
	Magnesium	ppm	ASTM D5185(m)		<1		
	Calcium	ppm	ASTM D5185(m)		0		
	Phosphorus	ppm	ASTM D5185(m)		49		
	Zinc	ppm	ASTM D5185(m)		1		
	Sulfur	ppm	ASTM D5185(m)	400	20		
	Lithium	ppm	ASTM D5185(m)	400	<1		
	CONTAMINANTS		method	limit/base	current	history1	historv2
							,
	Silicon	ppm	ASTM D5185(m)	>15	25		
	Sodium	ppm	ASTM D5185(m)	00	<1		
	Potassium	ppm	ASTM D5185(m)	>20	5		
	ppm Water	ppm	ASTM D6304*	>200	<b>4</b> 99		
	FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
	Acid Number (AN)	mg KOH/g	ASTM D974*	0.07	0.06		



## **OIL ANALYSIS REPORT**

VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)		141		
SAMPLE IMAGES	\$	method	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image
GRAPHS			_			



 Lab Number
 : 02606383
 Diagnosed
 : 12 Jan 2024

 Unique Number
 : 5707469
 Diagnostician
 : Bill Quesnel

 Test Package
 : IND 2 (Additional Tests: KV40)
 : Bill Quesnel

 To discuss this sample report, contact Customer Service at 1-905-847-9300 Ext 26.
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.

 Damages: Seller shall in no event be liable for special, incidental, or consequential damages, of a commercial nature, resulting from any cause.

: 03 Jan 2024

Recieved

Baulne Inc 1850 32nd Avenue Montreal, QC CA H8T 3J7 Contact: Paula Carvalho pcarvalho@baulne.ca T: (514)422-0444 F:

Sample No.

: GTT0001315

Contact/Location: Paula Carvalho - GTT0000213