

OIL ANALYSIS REPORT

Area 220 Simcoe Ch#3 [792224]

Sample Rating Trend WATER

YORK SCFM390280

GAL	-)		Aay2005 Ma	r2010 Dec2011 Dec20	3 Dec2015 Jan2019 Dec20	21 Dec2023	
	SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
ce	Sample Number		Client Info		GTT0001503	GTT62667	GTT62668
	Sample Date		Client Info		20 Dec 2023	07 Mar 2023	22 Dec 2021
	Machine Age	hrs	Client Info		0		
	Oil Age	hrs	Client Info		0		
	Oil Changed		Client Info		N/A	N/A	N/A
	Sample Status				MARGINAL	NORMAL	NORMAL
	WEAR METALS		method	limit/base	current	history1	history2
	Iron	ppm	ASTM D5185(m)	>8	3	<1	<1
	Chromium	ppm	ASTM D5185(m)	>2	0	<1	<1
	Nickel	ppm	ASTM D5185(m)		<1		
	Titanium	ppm	ASTM D5185(m)		0		
	Silver	ppm	ASTM D5185(m)	>2	0		
	Aluminum	ppm	ASTM D5185(m)	>3	<1	<1	<1
	Lead	ppm	ASTM D5185(m)	>2	<1	<1	<1
	Copper	ppm	ASTM D5185(m)	>8	<1	<1	<1
	Tin	ppm	ASTM D5185(m)	>4	0	<1	<1
	Antimony	ppm	ASTM D5185(m)		0		
	Vanadium	ppm	ASTM D5185(m)		0		
	Beryllium	ppm	ASTM D5185(m)		0		
	Cadmium	ppm	ASTM D5185(m)		0		
	ADDITIVES		method	limit/base	current	history1	history2
	Boron	ppm	ASTM D5185(m)	0	0		
	Barium	ppm	ASTM D5185(m)	0	0		
	Molybdenum	ppm	ASTM D5185(m)	0	0		
	Manganese	ppm	ASTM D5185(m)	0	0		
	Magnesium	ppm	ASTM D5185(m)	0	0		
	Calcium	ppm	ASTM D5185(m)	0	0		
	Phosphorus	ppm	ASTM D5185(m)	5	0		
	Zinc	ppm	ASTM D5185(m)	0	7	2	1
	Sulfur	ppm	ASTM D5185(m)	10	0		
	Lithium	ppm	ASTM D5185(m)		<1		
	CONTAMINANTS		method	limit/base	current	history1	history2
	Silicon	ppm	ASTM D5185(m)	>15	11		
	Sodium	ppm	ASTM D5185(m)		<1		
	Potassium	ppm	ASTM D5185(m)	>20	5		
	ppm Water	ppm	ASTM D6304*	>300	<u> </u>	50	296
	FLUID DEGRADA	TION	method	limit/base	current	history1	history2
	Acid Number (AN)	mg KOH/g	ASTM D974*	0.03	0.05	0.031	0.031

YORK TYPE K (--- GAL)

DIAGNOSIS

Recommendation

If not recently done change any filter driers to reduce moisture level. Resample at the next service interval to monitor.

Component Chiller Iuid

Wear

All component wear rates are normal.

Contamination

There is a trace of moisture present in the oil. The elevated moisture content is associated with POE oils which are hygroscopic, and can absorb moisture from sampling and processing.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



OIL ANALYSIS REPORT

VISUAL		method	limit/base	current	history1	history2			
White Metal	scalar	Visual*	NONE	NONE					
Yellow Metal	scalar	Visual*	NONE	NONE					
Precipitate	scalar	Visual*	NONE	NONE					
Silt	scalar	Visual*	NONE	NONE					
Debris	scalar	Visual*	NONE	NONE					
Sand/Dirt	scalar	Visual*	NONE	NONE					
Appearance	scalar	Visual*	NORML	NORML					
Odor	scalar	Visual*	NORML	NORML					
FLUID PROPERT	IES	method	limit/base	current	history1	history2			
Visc @ 40°C	cSt	ASTM D7279(m)	32.0	27.5					
SAMPLE IMAGES	method	limit/base	current	history1	history2				
Color					no image	no image			
Bottom					no image	no image			
GRAPHS									



 Lab Number
 : 02606409
 Diagnosed
 : 12 Jan 2024

 Unique Number
 : 5707495
 Diagnostician
 : Bill Quesnel

 Test Package
 : IND 2 (Additional Tests: KV40)
 : Bill Quesnel

 To discuss this sample report, contact Customer Service at 1-905-847-9300 Ext 26.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.

 Damages: Seller shall in no event be liable for special, incidental, or consequential damages, of a commercial nature, resulting from any cause.

: 03 Jan 2024

Recieved

Ainsworth Electric 131 Bermondsey Road Toronto, ON CA M4A 1X4 Contact: Service Manager invoices@ainsworth.com T: (905)694-6302 F:

Sample No.

: GTT0001503

Contact/Location: Service Manager - GTT0000006