

IPEX - 888063

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL





Component Hydraulic System Fluid AW HYDRAULIC OIL ISO 46 (--- GAL)

DIAGNOSIS

AM975

Recommendation

This is a baseline read-out on the submitted sample.

Wear


{not applicable}

Contamination {not applicable}


| SAMPLE INFORM | IATION | method | limit/base | current | history1 | history2 |
|------------------|--------|---------------|------------|-------------|----------|----------|
| Machine ID | | Client Info | | IMM54 | | |
| Department | | Client Info | | Sales | | |
| Sample From | | Client Info | | Machine | | |
| Production Stage | | Client Info | | Initial | | |
| Sent to WC | | Client Info | | 01/03/2024 | | |
| Sample Number | | Client Info | | E30001073 | | |
| Sample Date | | Client Info | | 20 Dec 2023 | | |
| Machine Age | hrs | Client Info | | 0 | | |
| Oil Age | hrs | Client Info | | 0 | | |
| Oil Changed | | Client Info | | N/A | | |
| Sample Status | | | | NORMAL | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185(m) | >20 | <1 | | |
| Chromium | ppm | ASTM D5185(m) | >20 | 0 | | |
| Nickel | ppm | ASTM D5185(m) | >20 | 0 | | |
| Titanium | ppm | ASTM D5185(m) | | 0 | | |
| Silver | ppm | ASTM D5185(m) | | 0 | | |
| Aluminum | ppm | ASTM D5185(m) | >20 | <1 | | |
| Lead | ppm | ASTM D5185(m) | >20 | 0 | | |
| Copper | ppm | ASTM D5185(m) | >20 | <1 | | |
| Tin | ppm | ASTM D5185(m) | >20 | 0 | | |
| Antimony | ppm | ASTM D5185(m) | | 0 | | |
| Vanadium | ppm | ASTM D5185(m) | | 0 | | |
| Beryllium | ppm | ASTM D5185(m) | | 0 | | |
| Cadmium | ppm | ASTM D5185(m) | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185(m) | 5 | 1 | | |
| Barium | ppm | ASTM D5185(m) | 5 | 0 | | |
| Molybdenum | ppm | ASTM D5185(m) | 5 | 0 | | |
| Manganese | ppm | ASTM D5185(m) | | 0 | | |
| Magnesium | ppm | ASTM D5185(m) | 25 | 5 | | |
| Calcium | ppm | ASTM D5185(m) | 200 | 144 | | |
| Phosphorus | ppm | ASTM D5185(m) | 300 | 344 | | |
| Zinc | ppm | ASTM D5185(m) | 370 | 424 | | |
| Sulfur | ppm | ASTM D5185(m) | 2500 | 887 | | |
| Lithium | ppm | ASTM D5185(m) | | <1 | | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185(m) | >15 | 0 | | |
| Sodium | ppm | ASTM D5185(m) | | 0 | | |
| Potassium | ppm | ASTM D5185(m) | >20 | 0 | | |
| Water | % | ASTM D6304* | >0.05 | 0.005 | | |
| ppm Water | ppm | ASTM D6304* | >500 | 53 | | |




OIL ANALYSIS REPORT









| Deutieles Aure | IESS | method | limit/base | current | history1 | history2 |
|----------------------|----------|---------------|------------|----------|----------------------|-----------------------|
| Particles >4µm | | ASTM D7647 | >10000 | 1220 | | |
| Particles >6µm | | ASTM D7647 | >2500 | 221 | | |
| Particles >14µm | | ASTM D7647 | >320 | 11 | | |
| Particles >21µm | | ASTM D7647 | >80 | 2 | | |
| Particles >38µm | | ASTM D7647 | >20 | 0 | | |
| Particles >71µm | | ASTM D7647 | >4 | 0 | | |
| Oil Cleanliness | | ISO 4406 (c) | >20/18/15 | 17/15/11 | | |
| FLUID DEGRADA | TION | method | limit/base | current | history1 | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D974* | 0.57 | 0.37 | | |
| VISUAL | | method | limit/base | current | history1 | history2 |
| White Metal | scalar | Visual* | NONE | NONE | | |
| Yellow Metal | scalar | Visual* | NONE | NONE | | |
| Precipitate | scalar | Visual* | NONE | NONE | | |
| Silt | scalar | Visual* | NONE | NONE | | |
| Debris | scalar | Visual* | NONE | NONE | | |
| Sand/Dirt | scalar | Visual* | NONE | NONE | | |
| Appearance | scalar | Visual* | NORML | NORML | | |
| Odor | scalar | Visual* | NORML | NORML | | |
| Emulsified Water | scalar | Visual* | >0.05 | NEG | | |
| Free Water | scalar | Visual* | | NEG | | |
| FLUID PROPERT | IES | method | limit/base | current | history1 | history2 |
| Visc @ 40°C | cSt | ASTM D7279(m) | 46 | 43.3 | | |
| Visc @ 100°C | cSt | ASTM D7279(m) | 6.7 | 7 | | |
| Viscosity Index (VI) | Scale | ASTM D2270* | 97 | 120 | | |
| | | | | | | |
| SAMPLE IMAGES | 5 | method | limit/base | current | history1 | history2 |
| SAMPLE IMAGES | 6 | method | limit/base | current | history1 no image | history'2 no image |

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 Environmental 360 Solutions Ltd. : E30001073 Recieved : 04 Jan 2024 640 Victoria Street Lab Number : 02606558 Diagnosed : 08 Jan 2024 Cobourg, ON ISO 17025:2017 Accredited Laboratory Unique Number : 5707644 Diagnostician : Tatiana Sorkina CA K9A 5H5 Test Package : IND 2 (Additional Tests: KF, KV100, VI) Contact: Tatiana Sorkina To discuss this sample report, contact Customer Service at 1-905-372-2251. tsorkina@e360s.ca T: (800)263-3939 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied. F: (905)373-4950