

OIL ANALYSIS REPORT

Sample Rating Trend



Area RONI Machine Id 174 Component Left Final Drive Fluid DETEC CAMADA

PETRO CANADA TRAXON 80W90 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0872986	LH0270773	
Sample Date		Client Info		06 Dec 2023	14 Jul 2023	
Machine Age	hrs	Client Info		0	5594	
Oil Age	hrs	Client Info		0	0	
Oil Changed		Client Info		Changed	Changed	
Sample Status				NORMAL	ABNORMAL	
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>500	80	371	
Chromium	ppm	ASTM D5185(m)	>10	<1	4	
Nickel	ppm	ASTM D5185(m)	>10	<1	3	
Titanium	ppm	ASTM D5185(m)		0	4	
Silver	ppm	ASTM D5185(m)		0	0	
Aluminum	ppm	ASTM D5185(m)	>25	11	6 4	
Lead	ppm	ASTM D5185(m)	>25	0	0	
Copper	ppm	ASTM D5185(m)	>50	<1	1	
Tin	ppm	ASTM D5185(m)	>10	0	0	
Antimony	ppm	ASTM D5185(m)	>5	0	0	
Vanadium	ppm	ASTM D5185(m)		0	<1	
Beryllium	ppm	ASTM D5185(m)		0	0	
Cadmium	ppm	ASTM D5185(m)		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	243	235	182	
Barium	ppm	ASTM D5185(m)	1	<1	<1	
Molybdenum	ppm	ASTM D5185(m)		0	<1	
Manganese	ppm	ASTM D5185(m)		<1	5	
Magnesium	ppm	ASTM D5185(m)	2	5	28	
Calcium	ppm	ASTM D5185(m)	6	64	367	
Phosphorus	ppm	ASTM D5185(m)	987	990	1047	
Zinc	ppm	ASTM D5185(m)	1	15	78	
Sulfur	ppm	ASTM D5185(m)	21530	17914	17509	
Lithium	ppm	ASTM D5185(m)		<1	<1	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>75	51	<u> </u>	
Sodium	ppm	ASTM D5185(m)		3	17	
Potassium	ppm	ASTM D5185(m)	>20	5	30	



OIL ANALYSIS REPORT



C	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	Visual*	NONE	NONE	VLITE	
	Yellow Metal	scalar	Visual*	NONE	NONE	NONE	
	Precipitate	scalar	Visual*	NONE	NONE	NONE	
	Silt	scalar	Visual*	NONE	NONE	MODER	
	Debris	scalar	Visual*	NONE	NONE	NONE	
	Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	
Dec6/23	Appearance	scalar	Visual*	NORML	NORML	NORML	
De	Odor	scalar	Visual*	NORML	NORML	NORML	
	Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	
	Free Water	scalar	Visual*		NEG	NEG	
	FLUID PROPERT	IES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D7279(m)	141.0	134	129	
	SAMPLE IMAGES	5	method	limit/base	current	history1	history2
	Color						no image
	Bottom						no image
	GRAPHS						
20	Iron (ppm)			100	Lead (ppm)		
	Severe			150	Severe		
<u>톱</u> 10	Abnormal			E 100	Abnormal		
					L.;		-
	Jul14/23			Dec6/23	Jul14/23		Dec6/23
	Aluminum (ppm)			20	Chromium (pp	om)	
	Sminn			30-			
Ed a	50 Abnormal			²⁰ 10	Abnormal		
	04						
	Jul14/23			Dec6/23	Jul14/23		Dec6/23
				Ō			ā
2	Copper (ppm)			300-	Silicon (ppm)		
	Severe				Severe		
톱1	Abnormal			200 ع 100	Abnormal		
							3
	Jul14/23			Dec6/23	Jul14/23		Dec6/23
	Viscosity @ 40°C			1500	Additives		
	Abnormal			- 1000	calcium	1	
(1000) t 400	50 - Base			트 ¹⁰⁰⁰ 500	annanan phosphorus zinc		
				0			
	114/23			ec6/23	114/23		ac6/23
		75 Apple Recieved Diagnose Diagnost	d : 08 .	ington, ON L Jan 2024 Jan 2024 rin Marson	7L 5H9 RONI/IR	100 MAC	AVATING LTD. INTOSH BLVD AUGHAN, ON CA L4K 4P3

Report Id: RONVAU [WCAMIS] 02607258 (Generated: 01/09/2024 10:33:39) Rev: 1

Contact/Location: Service Team - RONVAU Page 2 of 2