

OIL ANALYSIS REPORT

Area [4401] 01-014-CE

Component **New (Unused) Oil** Fluid

PETRO CANADA LUMINOL TRI (--- GAL)

Sample Rating Trend NORMAL

Recommendation

This is a baseline read-out on the submitted sample.

Wear

{not applicable}

Contamination

{not applicable}

Fluid Condition

Pour Point = -60°C.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PP0000883		
Sample Date		Client Info		12 Jan 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATION	1	method	limit/base	current	history1	history2
Water		WC Method		NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>5	0		
Chromium	ppm	ASTM D5185(m)	>5	0		
Nickel	ppm	ASTM D5185(m)	>5	0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)	>5	0		
Aluminum	ppm	ASTM D5185(m)	>5	<1		
Lead	ppm	ASTM D5185(m)	>5	0		
Copper	ppm	ASTM D5185(m)	>5	0		
Tin	ppm	ASTM D5185(m)	>5	0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	0	0		
Barium	ppm	ASTM D5185(m)	0	0		
Molybdenum	ppm	ASTM D5185(m)	0	0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)	0	<1		
Calcium	ppm	ASTM D5185(m)		0		
Phosphorus	ppm	ASTM D5185(m)	0	0		
Zinc	ppm	ASTM D5185(m)	0	-		
Sulfur	PP	7101111 20100(111)		<i>-</i> 1		
	nnm	ASTM D5185(m)		<1 0		
Lithium	ppm	ASTM D5185(m) ASTM D5185(m)	10	<1 0 <1		
Lithium CONTAMINANTS		. ,		0		 history2
CONTAMINANTS		ASTM D5185(m)	10	0 <1		
	ppm	ASTM D5185(m) method	10 limit/base >15	0 <1 current	 history1	
CONTAMINANTS Silicon	ppm	ASTM D5185(m) method ASTM D5185(m)	10 limit/base >15	0 <1 current	history1	history2
CONTAMINANTS Silicon Sodium	ppm ppm ppm	ASTM D5185(m) method ASTM D5185(m) ASTM D5185(m)	10 limit/base >15 >5	0 <1 current 0 0	history1	history2
CONTAMINANTS Silicon Sodium Potassium VISUAL	ppm ppm ppm	ASTM D5185(m) method ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	10 limit/base >15 >5 >20	0 <1 current 0 0 <1	history1	history2
CONTAMINANTS Silicon Sodium Potassium VISUAL White Metal	ppm ppm ppm ppm	ASTM D5185(m) method ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) method	limit/base >15 >5 >20 limit/base	0 <1 current 0 0 <1 current	history1 history1 history1	history2
CONTAMINANTS Silicon Sodium Potassium VISUAL White Metal Yellow Metal	ppm ppm ppm ppm	ASTM D5185(m) method ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) method Visual*	limit/base >15 >5 >20 limit/base NONE	0 <1 current 0 0 <1 current NONE	history1 history1 history1	history2
CONTAMINANTS Silicon Sodium Potassium VISUAL White Metal	ppm ppm ppm ppm scalar	ASTM D5185(m) method ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) method Visual*	limit/base >15 >5 >20 limit/base NONE	0 <1 current 0 0 <1 current NONE	history1 history1 history1	history2
CONTAMINANTS Silicon Sodium Potassium VISUAL White Metal Yellow Metal Precipitate Silt	ppm ppm ppm ppm scalar scalar	ASTM D5185(m) method ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) method Visual* Visual*	limit/base >15 >5 >20 limit/base NONE NONE NONE	0 current 0 0 c1 current NONE NONE	history1 history1 history1	history2
CONTAMINANTS Silicon Sodium Potassium VISUAL White Metal Yellow Metal Precipitate	ppm ppm ppm scalar scalar scalar scalar scalar	ASTM D5185(m) method ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) Wethod Visual* Visual* Visual* Visual*	limit/base >15 >5 >20 limit/base NONE NONE NONE NONE NONE NONE NONE	0 <1 current 0 0 <1 current NONE NONE NONE NONE NONE	history1 history1 history1	history2
CONTAMINANTS Silicon Sodium Potassium VISUAL White Metal Yellow Metal Precipitate Silt Debris	ppm ppm ppm scalar scalar scalar scalar	ASTM D5185(m) method ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) Method Visual* Visual* Visual* Visual* Visual*	limit/base >15 >5 >20 limit/base NONE NONE NONE	current 0 0 <1 current NONE NONE NONE	history1 history1	history2



OIL ANALYSIS REPORT

FLUID PROPER	TIES	method	limit/base	current	history1	history2
Pour Point	°C	ASTM D97*	-60	-60		
SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image
GRAPHS						



CALA ISO 17025:2017 Accredited Laboratory

Laboratory Sample No. Lab Number Unique Number : 5709912

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 : PP0000883 Recieved : 15 Jan 2024 : 15 Jan 2024 : 02608826 Diagnosed Diagnostician : Kevin Marson Test Package : TEST (Additional Tests: ICP, PourPt, Visual)

To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied.

Oleo Energies 5800 Thorold Stone Road Niagara Falls, ON CA L2J 1A2 Contact: Mark Michalkoff

mmichalkoff@oleoenergies.com T: (905)358-5133