


OIL ANALYSIS REPORT





Machine Id **093106** Component

Hydraulic System

AW HYDRAULIC OIL ISO 46 (170 LTR)

Ν		

Recommendation

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is (GENERIC) AW HYDRAULIC OIL ISO 46. Please confirm. Please contact your representative for information

regarding the proper sampling kits for your service. NOTE: We recommend using MOB 2 test kits, this testkit includes Particle Count to determine the ISO cleanliness of the fluid.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the component(unconfirmed).

Fluid Condition

The condition of the oil is acceptable for the time in service.

		<u>, </u>		Jan 2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC105095		
Sample Date		Client Info		12 Jan 2024		
Machine Age	hrs	Client Info		3093		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATION	V	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>20	12		
Chromium	ppm	ASTM D5185(m)	>10	<1		
Nickel	ppm	ASTM D5185(m)	>10	0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>10	1		
Lead	ppm	ASTM D5185(m)	>10	<1		
Copper	ppm	ASTM D5185(m)	>75	11		
Tin	ppm	ASTM D5185(m)	>10	0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	5	8		
Barium	ppm	ASTM D5185(m)	5	0		
Molybdenum	ppm	ASTM D5185(m)	5	0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)	25	5		
Calcium	ppm	ASTM D5185(m)	200	132		
Phosphorus	ppm	ASTM D5185(m)	300	412		
Zinc	ppm	ASTM D5185(m)	370	561		
Sulfur	ppm	ASTM D5185(m)	2500	1001		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>20	3		
Sodium	ppm	ASTM D5185(m)		1		
Potassium	ppm	ASTM D5185(m)	>20	1		




OIL ANALYSIS REPORT

cSt

ASTM D7279(m) 46

Visc @ 40°C



VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*	>0.1	NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	TES	method	limit/base	current	history1	history2

SAMPLE IMAGES	method	limit/base	current	history1	history2
Color			The state of the s	no image	no image
Bottom				no image	no image
CDADUC					

41.1

Bottom		no maye	no image
GRAPHS			
Iron (ppm) Severe Abnormal		Lead (ppm) Severe Abnormal	
Jan 12/24	Jan 12/24	Jan 12/24	Jan 12/24
Aluminum (ppm) 30 T Severe 20 T Abnormal		Chromium (ppm) Severe Abnormal	
0	+2/	0	- 124
Copper (ppm)	Jan12/24	Silicon (ppm)	Jan12/24
200 Severe 200 Abnormal		Severe Adnormal	
Jan12/24	Jan 12/24	Jan 12/24	Jan12/24 -
Viscosity @ 40°C		Additives	
S 40 Abnormal		calcium phosphorus	
30 Jan 12/24	Jan 12/24 +	Jan 12/24	Jan 12/24 +



CALA ISO 17025:2017 Accredited Laboratory

Laboratory Sample No.

: WC105095 Lab Number : 02609022

Unique Number : 5710108 Test Package : MOB 1

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 Received : 16 Jan 2024 **Tested** : 16 Jan 2024

Diagnosed : 16 Jan 2024 - Wes Davis

7367 Wellington Rd. 30, Unit A

Contact: CG Equipment CG Guelph cory@cgequipment.com T: (519)826-0550

F: (519)837-2055

To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.

Validity of results and interpretation are based on the sample and information as supplied.

C.G. EQUIPMENT

Guelph, ON

CA N0M 2T0