




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**1427M**

Component  
**Diesel Engine**

Fluid  
**CHEVRON DELO 400 SAE 10W30 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

Metal levels are typical for a new component breaking in.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The condition of the oil is acceptable for the time in service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>WC0853071</b>	WC0796578	WC0581115
Sample Date	Client Info		<b>15 Jan 2024</b>	26 Oct 2023	10 Aug 2023
Machine Age	kms	Client Info	<b>20105</b>	20918	17680
Oil Age	kms	Client Info	<b>0</b>	0	0
Oil Changed	Client Info		<b>Changed</b>	N/A	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185(m)	>90	<b>33</b>	50	17
Chromium	ppm	ASTM D5185(m)	>20	<b>&lt;1</b>	<1	0
Nickel	ppm	ASTM D5185(m)	>2	<b>&lt;1</b>	<1	<1
Titanium	ppm	ASTM D5185(m)	>2	<b>0</b>	0	0
Silver	ppm	ASTM D5185(m)	>2	<b>0</b>	<1	0
Aluminum	ppm	ASTM D5185(m)	>20	<b>3</b>	3	2
Lead	ppm	ASTM D5185(m)	>40	<b>0</b>	0	0
Copper	ppm	ASTM D5185(m)	>330	<b>&lt;1</b>	<1	<1
Tin	ppm	ASTM D5185(m)	>15	<b>0</b>	0	0
Antimony	ppm	ASTM D5185(m)		<b>0</b>	0	0
Vanadium	ppm	ASTM D5185(m)		<b>0</b>	0	0
Beryllium	ppm	ASTM D5185(m)		<b>0</b>	0	0
Cadmium	ppm	ASTM D5185(m)		<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185(m)		<b>50</b>	41	79
Barium	ppm	ASTM D5185(m)		<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185(m)		<b>2</b>	<1	2
Manganese	ppm	ASTM D5185(m)		<b>0</b>	0	<1
Magnesium	ppm	ASTM D5185(m)		<b>725</b>	711	664
Calcium	ppm	ASTM D5185(m)		<b>1305</b>	1293	1356
Phosphorus	ppm	ASTM D5185(m)	1260	<b>692</b>	670	735
Zinc	ppm	ASTM D5185(m)	1400	<b>757</b>	754	792
Sulfur	ppm	ASTM D5185(m)		<b>2626</b>	2379	2495
Lithium	ppm	ASTM D5185(m)		<b>&lt;1</b>	<1	<1

## CONTAMINANTS


	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185(m)	>25	<b>5</b>	6	4
Sodium	ppm	ASTM D5185(m)		<b>3</b>	2	2
Potassium	ppm	ASTM D5185(m)	>20	<b>4</b>	1	3

## INFRA-RED

	method	limit/base	current	history1	history2	
Soot %	%	ASTM D7844*	>6	<b>0.1</b>	0.8	0.2
Nitration	Abs/cm	ASTM D7624*	>20	<b>2.7</b>	11.0	9.1
Sulfation	Abs/.1mm	ASTM D7415*	>30	<b>6.2</b>	24.5	20.5



# OIL ANALYSIS REPORT



## FLUID DEGRADATION

method	limit/base	current	history1	history2	
Abs./1mm	ASTM D7414*	>25	4.3	21.2	14.7









## VISUAL

method	limit/base	current	history1	history2	
scalar	Visual*	>0.2	NEG	NEG	NEG
scalar	Visual*	NEG	NEG	NEG	

## FLUID PROPERTIES

method	limit/base	current	history1	history2	
cSt	ASTM D7279(m)	11.1	11.3	11.6	11.5

## GRAPHS



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : WC0853071 **Received** : 17 Jan 2024  
**Lab Number** : 02609181 **Diagnosed** : 17 Jan 2024  
**Unique Number** : 5710267 **Diagnostician** : Wes Davis  
**Test Package** : MOB 1

**Rush Truck Centres**  
 7450 Torbram Rd.  
 Mississauga, ON  
 CA L4T 1G9  
 Contact: Serdar Okur  
 sokur@rushtruckcentres.ca  
 T: (905)671-7600  
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.