



# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**UT99 EMC012**

Component  
**Diesel Engine**

Fluid  
**DIESEL ENGINE OIL SAE 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The condition of the oil is acceptable for the time in service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>WC0886146</b>	---	---
Sample Date	Client Info		<b>06 Jan 2024</b>	---	---
Machine Age	hrs	Client Info	<b>3284</b>	---	---
Oil Age	hrs	Client Info	<b>0</b>	---	---
Oil Changed	Client Info		<b>Changed</b>	---	---
Sample Status			<b>NORMAL</b>	---	---

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	---	---
Water	WC Method	>0.2	<b>NEG</b>	---	---
Glycol	WC Method		<b>NEG</b>	---	---

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m) >100	<b>14</b>	---	---
Chromium	ppm	ASTM D5185(m) >20	<b>&lt;1</b>	---	---
Nickel	ppm	ASTM D5185(m) >4	<b>&lt;1</b>	---	---
Titanium	ppm	ASTM D5185(m)	<b>0</b>	---	---
Silver	ppm	ASTM D5185(m) >3	<b>0</b>	---	---
Aluminum	ppm	ASTM D5185(m) >20	<b>4</b>	---	---
Lead	ppm	ASTM D5185(m) >40	<b>2</b>	---	---
Copper	ppm	ASTM D5185(m) >330	<b>&lt;1</b>	---	---
Tin	ppm	ASTM D5185(m) >15	<b>&lt;1</b>	---	---
Antimony	ppm	ASTM D5185(m)	<b>0</b>	---	---
Vanadium	ppm	ASTM D5185(m)	<b>0</b>	---	---
Beryllium	ppm	ASTM D5185(m)	<b>0</b>	---	---
Cadmium	ppm	ASTM D5185(m)	<b>0</b>	---	---

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m) 250	<b>58</b>	---	---
Barium	ppm	ASTM D5185(m) 10	<b>0</b>	---	---
Molybdenum	ppm	ASTM D5185(m) 100	<b>34</b>	---	---
Manganese	ppm	ASTM D5185(m)	<b>0</b>	---	---
Magnesium	ppm	ASTM D5185(m) 450	<b>435</b>	---	---
Calcium	ppm	ASTM D5185(m) 3000	<b>1694</b>	---	---
Phosphorus	ppm	ASTM D5185(m) 1150	<b>762</b>	---	---
Zinc	ppm	ASTM D5185(m) 1350	<b>875</b>	---	---
Sulfur	ppm	ASTM D5185(m) 4250	<b>2256</b>	---	---
Lithium	ppm	ASTM D5185(m)	<b>&lt;1</b>	---	---

## CONTAMINANTS


	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m) >25	<b>5</b>	---	---
Sodium	ppm	ASTM D5185(m) >158	<b>2</b>	---	---
Potassium	ppm	ASTM D5185(m) >20	<b>2</b>	---	---

## INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	ASTM D7844* >3	<b>0.3</b>	---	---
Nitration	Abs/cm	ASTM D7624* >20	<b>6.9</b>	---	---
Sulfation	Abs./1mm	ASTM D7415* >30	<b>23.1</b>	---	---



# OIL ANALYSIS REPORT



### FLUID DEGRADATION

Method	Limit/Base	Current	History1	History2
Abs./1mm	ASTM D7414*	>25	---	---

### VISUAL

Method	Limit/Base	Current	History1	History2
scalar	Visual*	>0.2	---	---
scalar	Visual*	NEG	---	---

### FLUID PROPERTIES


Method	Limit/Base	Current	History1	History2
cSt	ASTM D7279(m)	14.4	---	---

### GRAPHS


Iron (ppm)




Lead (ppm)




Aluminum (ppm)



Chromium (ppm)




Copper (ppm)




Silicon (ppm)



Viscosity @ 100°C



Soot %



**Laboratory** : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9  
**Sample No.** : WC0886146 **Received** : 17 Jan 2024  
**Lab Number** : 02609232 **Diagnosed** : 17 Jan 2024  
**Unique Number** : 5710318 **Diagnostician** : Wes Davis  
**Test Package** : MOB 1

**Agnico Eagle Canada**  
 1350 Government Rd. W, MACASSA COMPLEX  
 Kirkland Lake, ON  
 CA P2N 3J1  
 Contact: Mitch Lamontagne  
 AEM\_KL\_macassaoilsampleresults@agnicoeagle.com  
 T: (705)567-5208  
 F: (705)567-5221

To discuss this sample report, contact Customer Service at 1-800-268-2131.  
 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab.  
 Validity of results and interpretation are based on the sample and information as supplied.