

# **OIL ANALYSIS REPORT**

Sample Rating Trend

NORMAL



#### Area NIRO BROTHERS Machine Id 365

Component Hydraulic System

### JOHN DEERE HYDRAU (--- GAL)

### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.


#### Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	IATION	method				history2
Sample Number		Client Info		WC0888511	LH0275269	
Sample Date		Client Info		04 Jan 2024	02 Sep 2023	
Machine Age	hrs	Client Info		0	14989	
Oil Age	hrs	Client Info		0	0	
Oil Changed		Client Info		Not Changd	Changed	
Sample Status				NORMAL	NORMAL	
CONTAMINATION	٧	method	limit/base	current	history1	history2
Water		WC Method	>0.075	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>23	13	25	
Chromium	ppm	ASTM D5185(m)	>9	2	4	
Nickel	ppm	ASTM D5185(m)	>5	0	<1	
Titanium	ppm	ASTM D5185(m)		0	<1	
Silver	ppm	ASTM D5185(m)		0	0	
Aluminum	ppm	ASTM D5185(m)	>9	3	5	
Lead	ppm	ASTM D5185(m)	>28	0	<1	
Copper	ppm	ASTM D5185(m)	>51	2	3	
Tin	ppm	ASTM D5185(m)	>5	0	0	
Antimony	ppm	ASTM D5185(m)		0	0	
Vanadium	ppm	ASTM D5185(m)		0	0	
Beryllium	ppm	ASTM D5185(m)		0	0	
Cadmium	ppm	ASTM D5185(m)		0	0	
ADDITIVES		method	limit/base	current	history1	history2
ADDITIVES Boron	ppm	method ASTM D5185(m)	limit/base	current	history1 2	history2
	ppm ppm		limit/base		· · · · · · · · · · · · · · · · · · ·	
Boron		ASTM D5185(m)	limit/base	<1	2	
Boron Barium	ppm	ASTM D5185(m) ASTM D5185(m)	limit/base	<1 0	2 0	
Boron Barium Molybdenum	ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	limit/base	<1 0 0	2 0 <1	
Boron Barium Molybdenum Manganese	ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)		<1 0 0 0	2 0 <1 <1	
Boron Barium Molybdenum Manganese Magnesium	ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)		<1 0 0 0 2	2 0 <1 <1 4	
Boron Barium Molybdenum Manganese Magnesium Calcium	ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	87	<1 0 0 2 112	2 0 <1 <1 4 138	  
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	87 727	<1 0 0 2 112 645	2 0 <1 <1 4 138 678	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc	ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	87 727 900	<1 0 0 2 112 645 788	2 0 <1 <1 4 138 678 764	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	87 727 900	<1 0 0 2 112 645 788 1503	2 0 <1 <1 4 138 678 764 1390	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	87 727 900 1500	<1 0 0 2 112 645 788 1503 <1	2 0 <1 4 138 678 764 1390 <1	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m)	87 727 900 1500 limit/base	<1 0 0 2 112 645 788 1503 <1 current	2 0 <1 <1 4 138 678 764 1390 <1 history1	      history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon	ppm	ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) ASTM D5185(m) <b>method</b> ASTM D5185(m)	87 727 900 1500 limit/base >31	<1 0 0 2 112 645 788 1503 <1 <i>current</i> 7	2 0 <1 <1 4 138 678 764 1390 <1 history1 13	      history2 
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon Sodium	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m)	87 727 900 1500 limit/base >31 >21	<1 0 0 2 112 645 788 1503 <1 <b>Current</b> 7 <	2 0 <1 4 138 678 764 1390 <1 <b>history1</b> 13 1	      history2 
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m)	87 727 900 1500 limit/base >31 >21 >20	<1 0 0 2 112 645 788 1503 <1 <i>current</i> 7 <1 <1	2 0 <1 <1 4 138 678 764 1390 <1 <b>history1</b> 13 1 3	      history2  
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m)	87 727 900 1500 limit/base >31 >21 >20 limit/base	<1 0 0 2 112 645 788 1503 <1 <i>current</i> 7 <1 <1 <1	2 0 <1 4 138 678 764 1390 <1 <b>history1</b> 13 1 3 <i>history1</i>	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m)	87 727 900 1500 Iimit/base >31 >21 >20 Iimit/base >80000	<1 0 0 2 112 645 788 1503 <1 <i>current</i> 7 <1 <1 <1 <1 <1 <i>current</i>	2 0 <1 (1 4 138 678 764 1390 <1 <b>history1</b> 13 1 3 <b>history1</b> 39896	      history2  history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >6µm	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D5185(m)	87 727 900 1500 imit/base >31 >21 >20 imit/base >80000 >20000 >640	<1 0 0 2 112 645 788 1503 <1 <i>current</i> 7 <1 <1 <1 <1 <i>current</i> 35549 2237	2 0 <1 (1 4 138 678 764 1390 <1 <b>history1</b> 13 1 3 <b>history1</b> 39896 615	history2 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon Sodium Potassium FLUID CLEANLIN Particles >4µm Particles >14µm	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D7647 ASTM D7647	87 727 900 1500 imit/base >31 >21 >20 imit/base >80000 >20000 >640	<1 0 0 2 112 645 788 1503 <1 <i>current</i> 7 <1 <1 <1 <1 <1 <1 <1 235549 2237 62	2 0 <1 (1 4 138 678 764 1390 <1 <b>history1</b> 13 1 3 1 3 <b>history1</b> 39896 615 16	      history2  history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon Sodium Potassium Potassium Particles >4µm Particles >14µm Particles >21µm	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	87 727 900 1500 ilimit/base >31 >21 >20 ilimit/base >80000 >20000 >640 >160	<1 0 0 2 112 645 788 1503 <1 Current 7 <1 <1 <1 <1 <1 35549 2237 62 12	2 0 <1 (1 4 138 678 764 1390 <1 13 13 1 3 1 3 3 <u>history1</u> 39896 615 16 5	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur Lithium CONTAMINANTS Silicon Sodium Potassium Potassium Particles >4µm Particles >14µm Particles >21µm Particles >38µm	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185(m) ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	87 727 900 1500 <b>iimit/base</b> >31 >21 >20 <b>iimit/base</b> >80000 >20000 >640 >160 >160	<1 0 0 0 2 112 645 788 1503 <1  Current 7 <1 <1 <1   2237 62 12 1	2 0 <1 (1 4 138 678 764 1390 <1 <b>history1</b> 13 1 3 3 <b>history1</b> 39896 615 16 5 1 1	history2 history2




# **OIL ANALYSIS REPORT**







FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*	1.0	0.87		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE	NONE	
Yellow Metal	scalar	Visual*	NONE	NONE	NONE	
Precipitate	scalar	Visual*	NONE	NONE	NONE	
Silt		Visual*	NONE	NONE	NONE	
Debris	scalar	Visual*	NONE	NONE	NONE	
Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	
Appearance	scalar	Visual*	NORML	NORML	NORML	
Odor Emulsified Water	scalar scalar	Visual* Visual*	NORML >0.075	NORML NEG	NORML	
Free Water	scalar	Visual*	>0.075	NEG	NEG	
FLUID PROPERT		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	65	57.6	50.9	TIIStoryz
SAMPLE IMAGES	)	method	limit/base	current	history1	history2
Color						no image
Bottom						no image
GRAPHS						
Ferrous Alloys			401 52	Searticle Coun	t	20
30 iron			491,52			T <sup>26</sup>
20 - nickel			122,88	0 Abnormal		-24
10			30,72			-22
0	****		호 ( 7,68		N	20 8
Sep2/23			Jan4/24. [per 1 m]]			-18
Non-ferrous Metal	-		Jan4/24 Jan4/24 1.92 1.92 1.92		N	-20 130 4406; 1999 -18 5: 1999 -16 Ceamines Co -14 ress Co
<sup>10</sup> T			ofpai		\	leanlin
copper			un 12			14 iess C
5- tin			= 3	0 -		-12 🛱
0				8-		-10
Sep 2/23			Jan 4/24	2-		8
Set			Jan	0	14	28
Viscosity @ 40°C			_	<sup>4μ</sup> 6μ Acid Number	14µ 21µ	36µ 71µ́
Abnormal			5/HOX	0T		
				Base		
			E1.0	ч Т <mark>-</mark>		
70 Base 60			<u>د</u> ا.0 تو 0.5	0		
			24 30.0 0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0	0		Jan4,24



Report Id: RONVAU [WCAMIS] 02609431 (Generated: 01/19/2024 13:59:04) Rev: 1

> Contact/Location: Service Team - RONVAU Page 2 of 2