

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

EPIROC ST7 SCP212 Component

Front Right Planetary Fluid {not provided} (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. The fluid was not specified, however, a fluid match indicates that this fluid is SAE 90W140 Gear Oil. Please confirm the oil type and grade, and specify the brand of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

Viscosity of sample indicates oil is within SAE 90W140 range, advise investigate. The condition of the oil is acceptable for the time in service.

				Jan2024			
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2	
Sample Number		Client Info		WC0894615			
Sample Date		Client Info		13 Jan 2024			
Machine Age	hrs	Client Info		0			
Oil Age	hrs	Client Info		0			
Oil Changed		Client Info		N/A			
Sample Status				NORMAL			
CONTAMINATION	٧	method	limit/base	current	history1	history2	
Water		WC Method	>0.2	NEG			
WEAR METALS		method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185(m)	>500	27			
Chromium	ppm	ASTM D5185(m)	>10	0			
Nickel	ppm	ASTM D5185(m)	>10	0			
Titanium	ppm	ASTM D5185(m)		0			
Silver	ppm	ASTM D5185(m)		0			
Aluminum	ppm	ASTM D5185(m)	>25	<1			
Lead	ppm	ASTM D5185(m)	>25	0			
Copper	ppm	ASTM D5185(m)	>75	1			
Tin	ppm	ASTM D5185(m)	>10	0			
Antimony	ppm	ASTM D5185(m)	>5	0			
Vanadium	ppm	ASTM D5185(m)		0			
Beryllium	ppm	ASTM D5185(m)		0			
Cadmium	ppm	ASTM D5185(m)		0			
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185(m)		175			
Barium	ppm	ASTM D5185(m)		0			
Molybdenum	ppm	ASTM D5185(m)		0			
Manganese	ppm	ASTM D5185(m)		0			
Magnesium	ppm	ASTM D5185(m)		<1			
Calcium	ppm	ASTM D5185(m)		<1			
Phosphorus	ppm	ASTM D5185(m)		1017			
Zinc	ppm	ASTM D5185(m)		2			
Sulfur	ppm	ASTM D5185(m)		21280			
Lithium	ppm	ASTM D5185(m)		<1			
CONTAMINANTS		method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185(m)	>75	3			
Sodium	ppm	ASTM D5185(m)		0			
Potassium	ppm	ASTM D5185(m)	>20	0			



OIL ANALYSIS REPORT



С	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	Visual*	NONE	NONE		
	Yellow Metal	scalar	Visual*	NONE	NONE		
	Precipitate	scalar	Visual*	NONE	NONE		
	Silt	scalar	Visual*	NONE	NONE		
	Debris	scalar	Visual*	NONE	NONE		
	Sand/Dirt	scalar	Visual*	NONE	NONE		
Jan 13/24	Appearance	scalar	Visual*	NORML	NORML		
را عا	Odor	scalar	Visual*	NORML	NORML		
	Emulsified Water	scalar	Visual*	>0.2	NEG		
	Free Water	scalar	Visual*		NEG		
	FLUID PROPER	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D7279(m)		341		
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
	Color					no image	no image
	Bottom					no image	no image
	GRAPHS						
-	Iron (ppm)			150-	Lead (ppm)		
	Severe				Severe		
ā1	000 - Abnormal			E 100-	Abnormal		

	lan 13/24			Jan 13/24	Jan 13/24		Jan 13/24
	-,			Ja	-		la.
	Aluminum (ppm)			30-	Chromium (pp	m)	
	Severe				Severe		
	50 - Abnormal			²⁰ الم	Abnormal		
					5		5
	Jan 13/24			Jan 13/24	Jan 13/24		Jan 13/24
				Ja			р Г
	Copper (ppm)			300-	Silicon (ppm)		
	Severe				Severe		
8	100 - Abnormal			²⁰⁰ -	Abnormal		
	0 54 0			-0	24		24
	Jan 13/24			Jan 13/24	Jan 13/24		Jan 13/24
	Viscosity @ 40°C			ت ت	Additives		Ť.
	400			1500	caloium		
t (40°	200 - Abnormal			트 1000· 토 500·	nanananan phosphorus		
8	Abnormal 0 + +				200	J	
	Jan 13/24			Jan 13/24	Jan 13/24		Jan 13/24
	Jan			Jan	Jan		Jan
Laboratory Sample No. Lab Number Unique Number Test Package To discuss this sample report, c	: 02609464 : 5710550 : MOB 1	Recieved Diagnose Diagnost	ician : Kev	Jan 2024 Jan 2024 rin Marson	1350 Gove	ernment Rd. W, MA Kirł Contact: Mito acassaoilsampleresu	kland Lake, ON CA P2N 3J1 ch Lamontagne Its@agnicoeagle.com
Test denoted (*) outside scope Validity of results and interpreta	of accreditation, (m) m	nethod mo	odified, (e) te	sted at extern	al lab.	T:	(705)567-5208 (705)567-5221