

OIL ANALYSIS REPORT

Sample Rating Trend





Area **RONI** Machine Id **148** Component **Right Final Drive** Fluid

PETRO CANADA 30W (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0888456	LH0218905	
Sample Date		Client Info		10 Jan 2024	22 Mar 2023	
Machine Age	hrs	Client Info		0	1000	
Oil Age	hrs	Client Info		0	0	
Oil Changed		Client Info		Not Changd	Not Changd	
Sample Status				NORMAL	NORMAL	
CONTAMINATION	٧	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>800	88	75	
Chromium	ppm	ASTM D5185(m)	>10	1	1	
Nickel	ppm	ASTM D5185(m)	>5	0	0	
Titanium	ppm	ASTM D5185(m)	>15	0	<1	
Silver	ppm	ASTM D5185(m)	>2	0	0	
Aluminum	ppm	ASTM D5185(m)	>75	5	6	
Lead	ppm	ASTM D5185(m)	>10	0	0	
Copper	ppm	ASTM D5185(m)	>75	2	2	
Tin	ppm	ASTM D5185(m)	>8	0	0	
Antimony	ppm	ASTM D5185(m)	>50	0	<1	
Vanadium	ppm	ASTM D5185(m)		0	0	
Beryllium	ppm	ASTM D5185(m)		0	0	
Cadmium	ppm	ASTM D5185(m)		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		<1	1	
Barium	ppm	ASTM D5185(m)		2	2	
Molybdenum	ppm	ASTM D5185(m)		<1	<1	
Manganese	ppm	ASTM D5185(m)		<1	1	
Magnesium	ppm	ASTM D5185(m)		15	15	
Calcium	ppm	ASTM D5185(m)		3174	3410	
Phosphorus	ppm	ASTM D5185(m)		1085	1187	
Zinc	ppm	ASTM D5185(m)		1250	1296	
Sulfur	ppm	ASTM D5185(m)		8732	8707	
Lithium	ppm	ASTM D5185(m)		<1	<1	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>400	20	23	
Sodium	ppm	ASTM D5185(m)		3	2	
Potassium	ppm	ASTM D5185(m)	>20	4	3	



OIL ANALYSIS REPORT



C	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	Visual*	NONE	NONE	NONE	
	Yellow Metal	scalar	Visual*	NONE	NONE	NONE	
	Precipitate	scalar	Visual*	NONE	VLITE	NONE	
	Silt	scalar	Visual*	NONE	NONE	NONE	
	Debris	scalar	Visual*	NONE	VLITE	NONE	
	Sand/Dirt	scalar	Visual*	NONE	NONE	NONE	
Jan 10/24	Appearance	scalar	Visual*	NORML	NORML	NORML	
ے ا	Odor	scalar	Visual*	NORML	NORML	NORML	
	Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	
	Free Water	scalar	Visual*		NEG	NEG	
	FLUID PROPERT	IES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D7279(m)		97.0	96.8	
	SAMPLE IMAGES	6	method	limit/base	current	history1	history2
	Color						no image
	Bottom						no image
	GRAPHS						
	Iron (ppm)				Lead (ppm)		
20	Severe			30			
톱 10	00 - Abnormal			²⁰ ال	Abnormal		
	0			0			
	Mar22/23			Jan 10/24	Mar22/23		Jan10/24
	Mar			Jan	Mar		Jan
	Aluminum (ppm)				Chromium (pp	om)	
2	00 Severe			30			
<u></u> 11	00 - Abnormal			²⁰ 10	Abnormal		· · · · · · · · · · · · · · · · · · ·
	0			0			
	Mar22/23			Jan 10/24	Mar22/23		Jan 10/24
	Mar			Jan	Mar		Jan
	Copper (ppm)			1000	Silicon (ppm)		
	00 Severe			1000	Severe		
톱1	00 - Abnormal			<u>a</u> 500	Abnormal		
	0			0	L;		
	Mar22/23			Jan 10/24	Mar22/23		Jan10/24
				Jan			Jan
4	Viscosity @ 40°C			4000	Additives		
					<u></u>		
(C) 11 153	80 - Abnormal			E 3000	zinc		
5	60 L						
	Mar2/23			Jan 10/24	Mar22/23		Jan 10/24
	M			Ja	M		Jar
Sample No. Iso 17025:2017 Accredited Unique Number	: 02609500 I : 5710586 I : MOBCE (Additional ontact Customer Servi f accreditation, (m) mo	Recieved Diagnos Diagnos Tests: V ice at 1-8 ethod mo	d : 17 . ed : 18 . tician : Kev /isual) 800-268-213 bodified, (e) te	Jan 2024 Jan 2024 rin Marson 1. sted at exterr	nal lab.	100 MAC \ Contact	AVATING LTD. INTOSH BLVD /AUGHAN, ON CA L4K 4P3 Service Team .team@roni.ca T: F:

Contact/Location: Service Team - RONVAU Page 2 of 2