

FUEL REPORT

Sample Rating Trend





ANDEROL Royco 950 MIL-PRF-7024 Type II (--- GAL)

DIAGNOSIS

Recommendation

Laboratory test indicate that this fuel is suitable for use and meets all test requirements. Resample at the next service interval to monitor.

Corrosion

{not applicable}

Contaminants

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The water content is negligible. There is no indication of any contamination in the diesel fuel.

Fuel Condition

The condition of the fuel is acceptable for the time in service.

I (GAL)				Jan 2024		
SAMPLE INFORM	1ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0887308		
Sample Date		Client Info		15 Jan 2024		
Machine Age	hrs	Client Info		0		
Sample Status				NORMAL		
PHYSICAL PROP	ERTIES	method	limit/base	current	history1	history2
Specific Gravity		ASTM D1298*		0.766		
Fuel Color	text	Visual Screen*		Yllow		
visc @ 40°C	cSt	ASTM D7279(m)	1.5	1		
Pensky-Martens Flash Point	°C	ASTM D7215*		44		
SULFUR CONTEN	NT	method	limit/base	current	history1	history2
Sulfur	ppm	ASTM D5185(m)		33		
DISTILLATION		method	limit/base	current	history1	history2
nitial Boiling Point	°C	ASTM D2887*	158	162		
5% Distillation Point	°C	ASTM D2887*		169		
10% Distill Point	°C	ASTM D2887*		168		
5% Distillation Point	°C	ASTM D2887*		170		
20% Distill Point	°C	ASTM D2887*		171		
30% Distill Point	°C	ASTM D2887*		171		
10% Distill Point	°C	ASTM D2887*		173		
50% Distill Point	°C	ASTM D2887*		175		
60% Distill Point	°C	ASTM D2887*		177		
70% Distill Point	°C	ASTM D2887*		179		
30% Distill Point	°C	ASTM D2887*		185		
35% Distillation Point	°C	ASTM D2887*		192		
90% Distill Point	°C	ASTM D2887*		198		
95% Distillation Point	°C	ASTM D2887*		209		
Final Boiling Point	°C	ASTM D2887*	200	253		
IGNITION QUALIT	ΓY	method	limit/base	current	history1	history2
API Gravity		ASTM D1298*		53		
Cetane Index		ASTM D4737*	<40.0	52		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	<1.0	2		
Sodium	ppm	ASTM D5185(m)	<0.1	<1		
Potassium	ppm	ASTM D5185(m)	<0.1	0		
Nater	%	ASTM D6304*	<0.05	0.002		
opm Water	ppm	ASTM D6304*	<500	17		
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>2500	1364		
Particles >6µm		ASTM D7647	>640	462		
Particles >14µm		ASTM D7647	>80	42		
Particles >21µm		ASTM D7647	>20	8		
Particles >38µm		ASTM D7647	>4	2		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>18/16/13	18/16/13		
49:22) Rev: 1				Contact/Locati	on: Chris Newso	on - ACT91CH



FUEL REPORT

