




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id

7376

Component

Diesel Engine

Fluid

DIESEL ENGINE OIL SAE 10W30 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			WC0853151	WC0702853	WC0654383
Sample Date	Client Info			08 Jan 2024	10 Jan 2023	22 Feb 2022
Machine Age	kms	Client Info		126769	104859	79874
Oil Age	kms	Client Info		0	0	0
Oil Changed	Client Info			Not Chngd	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>3.0		<1.0	<1.0	<1.0
Water	WC Method	>0.2		NEG	NEG	NEG
Glycol	WC Method			NEG	NEG	0.0

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>130	8	19	34
Chromium	ppm	ASTM D5185(m)	>10	0	<1	<1
Nickel	ppm	ASTM D5185(m)	>4	<1	0	<1
Titanium	ppm	ASTM D5185(m)	>2	0	<1	0
Silver	ppm	ASTM D5185(m)	>2	0	0	0
Aluminum	ppm	ASTM D5185(m)	>20	6	11	14
Lead	ppm	ASTM D5185(m)	>20	0	<1	2
Copper	ppm	ASTM D5185(m)	>125	<1	10	58
Tin	ppm	ASTM D5185(m)	>4	0	0	<1
Antimony	ppm	ASTM D5185(m)		0	<1	<1
Vanadium	ppm	ASTM D5185(m)		0	0	0
Beryllium	ppm	ASTM D5185(m)		0	0	0
Cadmium	ppm	ASTM D5185(m)		0	0	0


ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	250	74	49	34
Barium	ppm	ASTM D5185(m)	10	0	0	0
Molybdenum	ppm	ASTM D5185(m)	100	2	8	4
Manganese	ppm	ASTM D5185(m)		0	<1	1
Magnesium	ppm	ASTM D5185(m)	450	713	712	760
Calcium	ppm	ASTM D5185(m)	3000	1293	1423	1437
Phosphorus	ppm	ASTM D5185(m)	1150	688	723	722
Zinc	ppm	ASTM D5185(m)	1350	744	773	850
Sulfur	ppm	ASTM D5185(m)	4250	2616	2549	2536
Lithium	ppm	ASTM D5185(m)		<1	<1	<1

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>25	4	6	10
Sodium	ppm	ASTM D5185(m)		2	3	4
Potassium	ppm	ASTM D5185(m)	>20	8	16	18

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	ASTM D7844*	>6	0	0	0.1
Nitration	Abs/cm	ASTM D7624*	>20	8.5	10.3	11.2
Sulfation	Abs/.1mm	ASTM D7415*	>30	18.9	22.5	24.2



OIL ANALYSIS REPORT











FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs./1mm	ASTM D7414*	>25	13.7	17.3	18.6

VISUAL		method	limit/base	current	history1	history2
Emulsified Water	scalar	Visual*	>0.2	NEG	NEG	.5%
Free Water	scalar	Visual*		NEG	NEG	NEG

FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D7279(m)	10.9	10.8	11.0	10.7

GRAPHS



Laboratory : WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9
Sample No. : WC0853151 **Received** : 19 Jan 2024
Lab Number : **02609845** **Diagnosed** : 19 Jan 2024
Unique Number : 5710931 **Diagnostician** : Wes Davis
Test Package : MOB 1

Rush Truck Centres
 7450 Torbram Rd.
 Mississauga, ON
 CA L4T 1G9
 Contact: Serdar Okur
 sokur@rushtruckcentres.ca
 T: (905)671-7600
 F:

To discuss this sample report, contact Customer Service at 1-800-268-2131.
 Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.
 Validity of results and interpretation are based on the sample and information as supplied.