


## **OIL ANALYSIS REPORT**

## Sample Rating Trend







Area Chem-Ecol Machine Id A2401090

Component Chain Case Fluid CHEM-ECOL CHAIN OIL ALL SEASON (--- GAL)

## DIAGNOSIS

Recommendation

This is a baseline read-out on the submitted sample.

Wear

Copper and iron ppm levels are noted.


Contamination {not applicable}


Fluid Condition {not applicable}


SAMPLE INFORM	<b>IATION</b>	method	limit/base	current	history1	history2
Batch #		Client Info		2978-A		
Department		Client Info		Production		
Sample From		Client Info		Machine		
Production Stage		Client Info		Final		
Sent to WC		Client Info		01/18/2024		
Sample Number		Client Info		E30001204		
Sample Date		Client Info		17 Jan 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>150	12		
Chromium	ppm	ASTM D5185(m)	>10	0		
Nickel	ppm	ASTM D5185(m)	>10	<1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>25	<1		
Lead	ppm	ASTM D5185(m)	>100	2		
Copper	ppm	ASTM D5185(m)	>50	13		
Tin	ppm	ASTM D5185(m)	>10	0		
Antimony	ppm	ASTM D5185(m)	>5	0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		0		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		5		
Calcium	ppm	ASTM D5185(m)		45		
Phosphorus	ppm	ASTM D5185(m)		104		
Zinc	ppm	ASTM D5185(m)		87		
Sulfur	ppm	ASTM D5185(m)		719		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>50	2		
Sodium	ppm	ASTM D5185(m)		4		
Potassium	ppm	ASTM D5185(m)	>20	<1		
Water	%	ASTM D6304*	>0.1	0.001		
ppm Water	ppm	ASTM D6304*	>1000	3		



## **OIL ANALYSIS REPORT**







FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	240		
Particles >6µm		ASTM D7647	>2500	60		
Particles >14µm		ASTM D7647	>320	4		
Particles >21µm		ASTM D7647	>80	3		
Particles >38µm		ASTM D7647	>20	2		
Particles >71µm		ASTM D7647	>4	2		
Oil Cleanliness		ISO 4406 (c)	>20/18/15	15/13/9		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*		0.52		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*	>0.1	NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	46	45.8		
Visc @ 100°C	cSt	ASTM D7279(m)		7.5		
				100		
Viscosity Index (VI)	Scale	ASTM D2270*		128		
Viscosity Index (VI) SAMPLE IMAGES		method	limit/base	current	history1	history2
			limit/base	current		

🔘 CALA	Laboratory Sample No.	: WearCheck - C8- : E30001204	1175 Appleby Line <b>Recieved</b>	e, Burlington, ON L7L 5H9 : 22 Jan 2024	Environmental 360 Solutions Ltd. 640 Victoria Street
Accreditation No. 1005019	Lab Number	: 02610292	Diagnosed	: 23 Jan 2024	
ISO 17025:2017					Cobourg, ON
Accredited Laboratory	Unique Number	: 5711378			CA K9A 5H5
Laboratory	Test Package	: IND 2 ( Additional	Tests: KF, KV100	), PrtCount, TAN Man, VI)	Contact: Tatiana Sorkina
To discuss this	tsorkina@e360s.ca				
Test denoted (	T: (800)263-3939				
Validity of resu	F: (905)373-4950				