

# **OIL ANALYSIS REPORT**

Sample Rating Trend



CATERPILLAR R1300 SCP228

Front Left Planetary

{not provided} (--- GAL)

#### DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The condition of the oil is acceptable for the time in service.


-)				Jan2024		
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0883846		
Sample Date		Client Info		18 Jan 2024		
Machine Age	hrs	Client Info		980		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>500	49		
Chromium	ppm	ASTM D5185(m)	>10	<1		
Nickel	ppm	ASTM D5185(m)	>10	<1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		<1		
Aluminum	ppm	ASTM D5185(m)	>25	3		
Lead	ppm	ASTM D5185(m)	>25	<1		
Copper	ppm	ASTM D5185(m)	>75	18		
Tin	ppm	ASTM D5185(m)	>10	2		
Antimony	ppm	ASTM D5185(m)	>5	0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		2		
Barium	ppm	ASTM D5185(m)		10		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		1		
Magnesium	ppm	ASTM D5185(m)		11		
Calcium	ppm	ASTM D5185(m)		3084		
Phosphorus	ppm	ASTM D5185(m)		1049		
Zinc	ppm	ASTM D5185(m)		1227		
Sulfur	ppm	ASTM D5185(m)		8873		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS	S	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>75	4		
Sodium	ppm	ASTM D5185(m)		4		
Potassium	ppm	ASTM D5185(m)	>20	<1		



NORMAL



# **OIL ANALYSIS REPORT**



	White Metal Yellow Metal		Visual*				
	Yellow Metal			NONE	NONE		
		scalar	Visual*	NONE	NONE		
	Precipitate	scalar	Visual*	NONE	NONE		
	Silt	scalar	Visual*	NONE	NONE		
	Debris		Visual*	NONE	NONE		
	Sand/Dirt		Visual*	NONE	NONE		
Jan 18/24	Appearance	scalar	Visual*	NORML	NORML		
ب	Odor		Visual*	NORML	NORML		
	Emulsified Water Free Water	scalar	Visual* Visual*	>0.2	NEG NEG		
		scalar	VISUAI		NEG		
	FLUID PROPERT		method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D7279(m)		195		
	SAMPLE IMAGES	6	method	limit/base	current	history1	history2
	Color					no image	no image
	Bottom					no image	no image
	GRAPHS						
200	Iron (ppm)			150	Lead (ppm)		
	Severe			1	Severe		
톱 100	Abnormal			E 100 -	Abnormal		
				54			24
	Jan 18/24			Jan 18/24	Jan 18/24		4.01 fuel
	¬ Aluminum (ppm)			7	Chromium (pp	m)	
10				<sup>30</sup> T	Severe		
Ē. 5	50			e <sup>20</sup>	Abnormal		
B.	Abnormal			<sup>10</sup> ·			
	8/24				8/24		1
	Jan 18/24			Jan 18/24	Jan 18/24		1 C S 1
	Copper (ppm)				Silicon (ppm)		
20	Severe			300	Severe		
<u>۾</u> 10	00 - Abnormal			200 · ط 100 ·	Abnormal		
	0			0.	T		
	Jan 18/24			Jan 18/24	Jan 18/24		101
	ے Viscosity @ 40°C			Jar	Additives		1
20 27				4000	calcium	 1	
01 80 10 80				트 <sup>3000</sup> -	calcium management phosphorus zinc		
	00 Abnormal						
	Jan 18/24			Jan 18/24	Jan 18/24		b (/ 81 mc)
	Jan			Jan	Jan		
Accredited Unique Number	: 02610698 E : 5711784 E : MOB 1 ntact Customer Servic	Recieved Diagnose Diagnosti	: 23 c ed : 23 c cian : Kev	Jan 2024 Jan 2024 in Marson	1350 Gove AEM_KL_m	rnment Rd. W, MA Kirk Contact: Mitc acassaoilsampleresul	land Lake, Of CA P2N 3J h Lamontagn

Contact/Location: Mitch Lamontagne - KIR370KIR