

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Area Bibby Ste-Croix - 888077 Machine Id XB119-R

Component Unknown Component Fluid CONDAT D 46 (--- GAL)

DIAGNOSIS

Recommendation

We certify this oil to be clean, that the additives are at acceptable levels and the oil is suitable for use.


SAMPLE INFORM	NATION	method	limit/base	current	history1	history2
Machine ID		Client Info		560006		
Department		Client Info		Sales		
Sample From		Client Info		Machine		
Production Stage		Client Info		Lab Reclaim		
Sent to WC		Client Info		03/08/2024		
Sample Number		Client Info		E30001564		
Sample Date		Client Info		08 Mar 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)		<1		
Chromium	ppm	ASTM D5185(m)		0		
Nickel	ppm	ASTM D5185(m)		0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)		<1		
Lead	ppm	ASTM D5185(m)		<1		
Copper	ppm	ASTM D5185(m)		1		
Tin	ppm	ASTM D5185(m)		0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)	0	<1		
Barium	ppm	ASTM D5185(m)	40	0		
Molybdenum	ppm	ASTM D5185(m)	0	0		
Manganese	ppm	ASTM D5185(m)	0	0		
Magnesium	ppm	ASTM D5185(m)	0	0		
Calcium	ppm	ASTM D5185(m)	0	1		
Phosphorus	ppm	ASTM D5185(m)	1500	1465		
Zinc	ppm	ASTM D5185(m)	0	6		
Sulfur	ppm	ASTM D5185(m)	2100	2225		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)		0		
Sodium	ppm	ASTM D5185(m)		<1		
Potassium	ppm	ASTM D5185(m)	>20	<1		
Water	%	ASTM D6304*		0.013		
ppm Water	ppm	ASTM D6304*		140		





OIL ANALYSIS REPORT

FLUID CLEANLINESS

Particles >4µm








10 2k

0

Particles >6µm		ASTM D7647	>640	212		
Particles >14µm		ASTM D7647	>160	17		
Particles >21µm		ASTM D7647	>40	4		
Particles >38µm		ASTM D7647	>10	1		
Particles >71µm		ASTM D7647	>3	1		
Oil Cleanliness		ISO 4406 (c)	>19/16/14	16/15/11		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*	2.0	0.50		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*		NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	IES	method	limit/base	current	history1	history2
FLUID PROPERT Visc @ 40°C	IES cSt	method ASTM D7279(m)	limit/base 45.1	current 45.5	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	45.1	45.5		
Visc @ 40°C Visc @ 100°C	cSt cSt Scale	ASTM D7279(m) ASTM D7279(m)	45.1 9.5	45.5 9.2		
Visc @ 40°C Visc @ 100°C Viscosity Index (VI)	cSt cSt Scale	ASTM D7279(m) ASTM D7279(m) ASTM D2270*	45.1 9.5 201	45.5 9.2 189		
Visc @ 40°C Visc @ 100°C Viscosity Index (VI) SAMPLE IMAGES	cSt cSt Scale	ASTM D7279(m) ASTM D7279(m) ASTM D2270*	45.1 9.5 201	45.5 9.2 189	 history1	 history2

510

ASTM D7647 >5000



Mar8/74