

## **OIL ANALYSIS REPORT**

Sample Rating Trend







Machine Id Component Main Hydraulic System {not provided} (--- LTR)

### DIAGNOSIS

#### Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

#### Wear

All component wear rates are normal.

#### Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0914624		
Sample Date		Client Info		11 Mar 2024		
Machine Age	hrs	Client Info		0		
-	hrs	Client Info		0		
Oil Age Oil Changed	1115	Client Info		N/A		
•		Client Inio		NORMAL		
Sample Status				NORMAL		
CONTAMINATIC	DN	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>20	<1		
Chromium	ppm	ASTM D5185(m)	>20	0		
Nickel	ppm	ASTM D5185(m)	>20	1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>20	<1		
Lead	ppm	ASTM D5185(m)	>20	<1		
Copper	ppm	ASTM D5185(m)	>20	2		
Tin	ppm	ASTM D5185(m)	>20	0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		0		
Barium	ppm	ASTM D5185(m)		13		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		<1		
Calcium	ppm	ASTM D5185(m)		7		
Phosphorus	ppm	ASTM D5185(m)		502		
Zinc	ppm	ASTM D5185(m)		554		
Sulfur	ppm	ASTM D5185(m)		1141		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANT	S	method	limit/base	current	history1	history2
0.11						
Silicon	ppm	ASTM D5185(m)	>15	0		
Silicon Sodium	ppm ppm	ASTM D5185(m) ASTM D5185(m)	>15	0		
		( )	>15 >20			
Sodium	ppm ppm	ASTM D5185(m)		0		
Sodium Potassium	ppm ppm	ASTM D5185(m) ASTM D5185(m)	>20	0 2		
Sodium Potassium FLUID CLEANLI Particles >4µm	ppm ppm	ASTM D5185(m) ASTM D5185(m) method	>20 limit/base	0 2 current	  history1	
Sodium Potassium FLUID CLEANLI Particles >4µm Particles >6µm	ppm ppm	ASTM D5185(m) ASTM D5185(m) method ASTM D7647	>20 limit/base >5000	0 2 current 4601	  history1 	 history2 
Sodium Potassium FLUID CLEANLI Particles >4µm Particles >6µm Particles >14µm	ppm ppm	ASTM D5185(m) ASTM D5185(m) method ASTM D7647 ASTM D7647 ASTM D7647	>20 limit/base >5000 >1300 >160	0 2 current 4601 666 38	 history1 	 history2 
Sodium Potassium FLUID CLEANLI Particles >4µm Particles >6µm Particles >14µm Particles >21µm	ppm ppm	ASTM D5185(m) ASTM D5185(m) <b>method</b> ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>20 limit/base >5000 >1300 >160 >40	0 2 current 4601 666 38 12	 history1  	 history2  
Sodium Potassium FLUID CLEANLI Particles >4µm Particles >6µm Particles >21µm Particles >38µm	ppm ppm	ASTM D5185(m) ASTM D5185(m) <b>method</b> ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>20 limit/base >5000 >1300 >160 >40 >10	0 2 current 4601 666 38 12 1	 history1  	 history2   
Sodium Potassium FLUID CLEANLI Particles >4µm Particles >6µm Particles >14µm Particles >21µm Particles >38µm Particles >71µm	ppm ppm	ASTM D5185(m) ASTM D5185(m) <b>method</b> ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>20 limit/base >5000 >1300 >160 >40 >10	0 2 current 4601 666 38 12 1 1 0	 history1   	 history2   
Sodium Potassium FLUID CLEANLI Particles >4µm Particles >6µm Particles >21µm Particles >38µm	ppm ppm	ASTM D5185(m) ASTM D5185(m) <b>method</b> ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>20 limit/base >5000 >1300 >160 >40 >10	0 2 current 4601 666 38 12 1 1 0 19/17/12	 history1       	 history2   

Page 1 of 2



# **OIL ANALYSIS REPORT**

k т			FLUID DEGRAD	ATION	method	limit/base	current	history1	history2
α - Abnorma 4μm 6μm			Acid Number (AN)	mg KOH/g	ASTM D974*		0.54		
			VISUAL		method	limit/base	current	history1	history2
			White Metal	scalar	Visual*	NONE	NONE		
			Yellow Metal	scalar	Visual*	NONE	NONE		
			Precipitate	scalar	Visual*	NONE	NONE		
1/24		1/24 -	Silt	scalar	Visual*	NONE	NONE		
Mar11/24		Mar11/24	Debris	scalar	Visual*	NONE	NONE		
Acid Number			Sand/Dirt	scalar	Visual*	NONE	NONE		
			Appearance	scalar	Visual*	NORML	NORML		
1			Odor Emulsified Water	scalar scalar	Visual* Visual*	NORML >0.05	NORML NEG		
			Free Water	scalar	Visual*	>0.05	NEG		
			FLUID PROPERT		method	limit/base	current	history1	history2
						iiiiii/base		TIIStOLA	nistory
1 1 #*		5	Visc @ 40°C	cSt	ASTM D7279(m)		45.5		
Mar11/24		Mar11/24	SAMPLE IMAGE	5	method	limit/base	current	history1	history2
Viscosity @ 40°C Abnormal	2		Color					no image	no image
Abnormal			Bottom					no image	no image
Abnormal			GRAPHS					· · · · ·	
Mar11/24 -		1 nd	Ferrous Alloys				Particle Count		
Mari		h 1	10 iron			491,520			ľ
Particle Trend			E. 5 -			122,880	Severe		
Automatic 4µm						30,720			
6μm 						황 (글 7,680	Abnormal		-
			lar11/2			Mar11/24 Mar11/24 1950 1890 1900 1900	Y	s	
			≥ Non-ferrous Meta	s		≥ <u>sa</u> 12 480	1.		
			<sup>10</sup> T			5		<b>N</b>	
			copper lead			qui			
Mar11/24		10.10	ق 5- •••••• tin			≡ 30			
Ma		- P. 4	0			8			
			11/24			0 Mar11/24	•		
			Market Market			₩ 0 <sub>4</sub>	μ 6μ	14µ 21µ	38µ 71
			Viscosity @ 40°C				Acid Number		
			Abnormal			(月0.60 円 の 型 0.40			
			50 + <b>A</b> binomal			0.40	•		
			<sup>40</sup> 40 - Abnormal			4 Vinnper 4			
			35			Acid Acid			
			Mar11/3			Mar11/24	Mar11/24		
	CALA ISO 17025:2017 Accredited Laboratory	Sample No. Lab Number Unique Number Test Package	: WearCheck - C8-117 : WC0914624 : 02621465 : 5746584	Recei Teste Diagr	ved : 12 d : 13 losed : 13	ngton, ON L7L 2 Mar 2024 3 Mar 2024 5 Mar 2024 - Wi	5H9 Amcor	Mi	nnia Road E ssissauga, CA L4Z t: Sandip P