

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id MG SET Component Gearbox

{not provided} (--- GAL)

DIAGNOSIS

Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

				Mar2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0813592		
Sample Date		Client Info		11 Mar 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATION	V	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184*		0		
Iron	ppm	ASTM D5185(m)	>200	<1		
Chromium	ppm	ASTM D5185(m)	>15	0		
Nickel	ppm	ASTM D5185(m)		<1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>25	<1		
Lead	ppm	ASTM D5185(m)	>100	1		
Copper		ASTM D5185(m)	>200	<1		
Tin	ppm	ASTM D5185(m)	>25	2		
Antimony	ppm	ASTM D5185(III) ASTM D5185(m)	>5	0		
Vanadium	ppm	ASTM D5185(m)	>5	0		
	ppm	, ,				
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		0		
Barium	ppm	ASTM D5185(m)		0		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		0		
Calcium	ppm	ASTM D5185(m)		<1		
Phosphorus	ppm	ASTM D5185(m)		9		
Zinc	ppm	ASTM D5185(m)		5		
Sulfur	ppm	ASTM D5185(m)		157		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>50	0		
Sodium	ppm	ASTM D5185(m)	7 00	0		
Potassium	ppm	ASTM D5185(m)	>20	1		
FLUID DEGRADA		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*		0.06		



OIL ANALYSIS REPORT







Laboratory

Laboratory Sample No.

Lab Number : 02621502 Unique Number : 5746621

100

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 ALGOMA STEEL INC. - STORES DEPT. : WC0813592 Received **Tested**

: 12 Mar 2024 Diagnosed Test Package : IND 2 (Additional Tests: TAN Man)

: 12 Mar 2024 : 13 Mar 2024 - Kevin Marson 301 WALLACE TERRACE SAULT STE MARIE, ON CA P6C 1K8

Contact: Algoma Reliability algomareliability@algoma.com T: (705)206-1059

To discuss this sample report, contact Customer Service at 1-800-268-2131. Test denoted (*) outside scope of accreditation, (m) method modified, (e) tested at external lab.

Validity of results and interpretation are based on the sample and information as supplied.

F: (705)945-3585