

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Machine Id DWGCWLECAM1010072 Component

Rear Gearbox

{not provided} (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The condition of the oil is acceptable for the time in service.

				Mar2024		
SAMPLE INFORM	1ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0890797		
Sample Date		Client Info		01 Mar 2024		
Machine Age	hrs	Client Info		4500		
Oil Age	hrs	Client Info		1500		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATION	١	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>200	79		
Chromium	ppm	ASTM D5185(m)	>10	<1		
Nickel	ppm	ASTM D5185(m)	>10	<1		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>25	1		
Lead	ppm	ASTM D5185(m)	>50	<1		
Copper	ppm	ASTM D5185(m)	>200	16		
Tin	ppm	ASTM D5185(m)	>10	<1		
Antimony	ppm	ASTM D5185(m)	>5	0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		100		
Barium	ppm	ASTM D5185(m)		<1		
Molybdenum	ppm	ASTM D5185(m)		<1		
Manganese	ppm	ASTM D5185(m)		1		
Magnesium	ppm	ASTM D5185(m)		23		
Calcium	ppm	ASTM D5185(m)		3408		
Phosphorus	ppm	ASTM D5185(m)		1186		
Zinc	ppm	ASTM D5185(m)		1428		
Sulfur	ppm	ASTM D5185(m)		7282		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>50	13		
Sodium	ppm	ASTM D5185(m)		4		
Potassium	ppm	ASTM D5185(m)	>20	2		
	C. F. 11	()	-			



OIL ANALYSIS REPORT



	VISUAL		method	limit/base	current	history1	history2		
	White Metal	scalar	Visual*	NONE	NONE				
	Yellow Metal	scalar	Visual*	NONE	NONE				
	Precipitate	scalar	Visual*	NONE	NONE				
	Silt	scalar	Visual*	NONE	NONE				
	Debris	scalar	Visual*	NONE	NONE				
	Sand/Dirt	scalar	Visual*	NONE	NONE				
Marl/24	Appearance	scalar	Visual*	NORML	NORML				
Mar	Odor	scalar	Visual*	NORML	NORML				
	Emulsified Water	scalar	Visual*	>0.2	NEG				
	Free Water	scalar	Visual*		NEG				
	FLUID PROPERT			limit/booo			biotory ()		
			method	limit/base	current	history1	history2		
	Visc @ 40°C	cSt	ASTM D7279(m)		50.1				
	SAMPLE IMAGES	S	method	limit/base	current	history1	history2		
	Color					no image	no image		
	Bottom					no image	no image		
	GRAPHS								
	Iron (ppm)				Lead (ppm)				
	600 Severe			20	Severe				
	400 - Abnormal			튭 10	0 - Abnormal				
	0								
	Mar1/24			Mar1/24	Mar1/24		Mar1/24		
	Z Aluminum (ppm)		Chromium (ppm)						
	100		3	Severe					
	Severe	evere bnormal							
	E 50 Abnormal			⁸ 1	0 - Abnormal				
				5			4		
	Mar1/24			Mar1/24	Mar1/24		Mar1/24		
				2			2		
	Copper (ppm)			15	Silicon (ppm)				
	Courses				detere				
	400 - Abnormal			¹⁰ ق	0 - Abnormal				
	Mar1/24			Mar1/24	Mar1/24		Mar1/24		
	≥ Viscosity @ 40°C			2	≥ Additives		2		
	300 Abnormal								
	(200 Abnormal 장 100 -			E 300	0 - calcium				
	평 100			200	0 - zinc				
	24+10						24		
	Mar1/24			Mar1/24	Mar1/24		Mar1/24		
Accredited Unique Number Laboratory Test Package to discuss this sample report,	: 5746943 : MOB 1	Rece Teste Diagr	ived : 13 ed : 13 nosed : 13 800-268-213	3 Mar 2024 3 Mar 2024 Mar 2024 - Ke 1.	rin Marson Conta	7367 Wellingtor act: CG Equipm cory@cg	Guelph, ON CA N0M 2T0		

Report Id: CGEGUE [WCAMIS] 02621824 (Generated: 03/14/2024 15:40:36) Rev: 1

Contact/Location: CG Equipment CG Guelph - CGEGUE