

OIL ANALYSIS REPORT

Area **315 Nantucket** Machine Id **F2** Component Hydraulic System Fluid {not provided} (--- LTR)

DIAGNOSIS

Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. We recommend you service the filters on this component. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is a light amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sample Rating Trend

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0925482		
Sample Date		Client Info		19 Mar 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ATTENTION		
CONTAMINATION	١	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>20	<1		
Chromium	ppm	ASTM D5185(m)	>20	0		
Nickel	ppm	ASTM D5185(m)	>20	0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)	>20	0		
Lead	ppm	ASTM D5185(m)	>20	0		
Copper	ppm	ASTM D5185(m)	>20	17		
Tin	ppm	ASTM D5185(m)	>20	0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		0		
Barium	ppm	ASTM D5185(m)		<1		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		<1		
Calcium	ppm	ASTM D5185(m)		32		
Phosphorus	ppm	ASTM D5185(m)		225		
Zinc	ppm	ASTM D5185(m)		270		
Sulfur	ppm	ASTM D5185(m)		5341		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)	>15	0		
Sodium	ppm	ASTM D5185(m)		0		
Potassium	ppm	ASTM D5185(m)	>20	0		
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	8340		
Particles >6µm		ASTM D7647	>1300	0 1709		
Particles >14µm		ASTM D7647	>160	117		
Particles >21µm		ASTM D7647		31		
Particles >38µm		ASTM D7647	>10	3		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>19/17/14	20/18/14		
8:33:00) Rev: 1		. /		Contact/Loca		



OIL ANALYSIS REPORT

10k .			FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
8k - 4μm			Acid Number (AN)	mg KOH/g	ASTM D974*		0.29		
8k Abnomal 4k 2k			VISUAL		method	limit/base	current	history1	history2
Abnormal 4k			White Metal	scalar	Visual*	NONE	NONE		
2k			Yellow Metal		Visual*	NONE	NONE		
			Precipitate	scalar	Visual*	NONE	NONE		
0k 47	*********	/24	Silt	scalar	Visual*	NONE	NONE		
Mar1 9/24		Mar19/24	Debris	scalar	Visual*	NONE	NONE		
Darticla Trand			Sand/Dirt	scalar	Visual*	NONE	NONE		
Particle Trend			Appearance	scalar	Visual*	NORML	NORML		
8k - 4μm			Odor	scalar	Visual*	NORML	NORML		
6k			Emulsified Water	scalar	Visual*	>0.05	NEG		
Abnormal 4k			Free Water	scalar	Visual*		NEG		
2k			FLUID PROPERT	TIES	method	limit/base	current	history1	history2
0k			Visc @ 40°C	cSt	ASTM D7279(m)		45.0		
Mar1 9/24		Mar19/24	SAMPLE IMAGES	S	method	limit/base	current	history1	history2
Acid Number		~	Color					no image	no image
.24			Bottom					no image	no image
.00			GRAPHS						
Mar1 9/24		tion of the second s	Ferrous Alloys				Particle Count		20
Ma		- PA	10 iron			491,520			T ²⁶
Viscosity @ 40	°C		E 5-			122,880	Severe		-24
52 50						30,720	· · · · ·		-22
48 -			54 0 54 0	*******		5 E 7,680	Renormal		-20 8
46			far 19,24			Mar19/24 19/24 19/20 19/24 19/20		\$	-18
44			∠ Non-ferrous Metal	s		~ saj :만 480-			-16 g
42 40 - Abnormal			20			120- 120-			-20 5 -18 - 16 - -14 -
38			15 E 10			aguar - 30			-12
Mar19/24		AC D	B 10			30			
Ma		- 11 - 1	0						-10
			ır19/24			7 Mar19/24			
						≊ _{0.} 4	μ 6μ	14µ 21µ	38µ 71µ
			Viscosity @ 40°C			<u></u> © 30-	Acid Number		
			S 50 - Abnormal			() () () () () () () () () () () () () (
			50 - Abnormal			E 0.20			
						4 Vin Dec			
			354			-00.0 PCI	1/24		24 -
			Mar1 9/24			Mar19/24	Mar1 9/24		Mar19/24
	ISO 17025:2017 Accredited Laboratory		: 5748515	Recei Teste Diagr	ved : 20 d : 21 losed : 21) Mar 2024 1 Mar 2024 Mar 2024 - We		T Contact:	RODUCTS LTD CHMOUNT RD ORONTO, ON CA M1P 2C6 Joseph Kovacs Markdom.com

Contact/Location: Joseph Kovacs - MARSCA