

## **COOLANT REPORT**

Sample Rating Trend

### TJ034209] Machine Id B+M BUILD 201

#### Component Coolant Fluid

CONVENTIONAL COOLANT (--- GAL)

#### DIAGNOSIS

#### Recommendation

We recommend drain system, and refill with 50/50 antifreeze water mixture. We advise that you replenish the supplemental coolant additives (SCAs) and add per manufacturer`s specifications. We recommend an early resample to monitor this condition.

#### Corrosion

Copper ppm levels are abnormal. The high metal levels indicate corrosion in the system.

#### Contaminants

There is no indication of any contamination in the coolant.

#### **Coolant Condition**

The nitrite level is acceptable. The pH level of this fluid is within the acceptable limits.

SAMPLE INFORM	TATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0788016		
Sample Date		Client Info		29 Feb 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ABNORMAL		
PHYSICAL TEST R	ESULTS	method	limit/base	current	history1	history2
Glycol Type		FT-IR		UNK		
Specific Gravity		ASTM D1298*		1.076		
рН	Scale 0-14	ASTM D1287*	9.5	8.96		
Nitrites	ppm	Alcan Test Kit*	1500	1000		
Reserve Alkalinity	Scale 0-20	ASTM D1121*	8.5	5.3		
Percentage Glycol	%	ASTM D3321*	50	56.8		
Freezing Point	°C	ASTM D3321*	-40	-46		
Carboxylate						
CORROSION INHI	BITORS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)		29		
Phosphorus	ppm	ASTM D5185(m)		512		
Boron	ppm	ASTM D5185(m)		227		
Molybdenum	ppm	ASTM D5185(m)		132		
CORROSION		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)	>15	0		
Aluminum	ppm	ASTM D5185(m)	>10	1		
Copper	ppm	ASTM D5185(m)	>10	<u> </u>		
Lead	ppm	ASTM D5185(m)	>10	6		
Tin	ppm	ASTM D5185(m)	>10	0		
Silver	ppm	ASTM D5185(m)	>10	<1		
Zinc	ppm	ASTM D5185(m)		0		
CARRIER SALTS		method	limit/base	current	history1	history2
Sodium	ppm	ASTM D5185(m)		2495		
Potassium	ppm	ASTM D5185(m)		2592		
SCALE POTENTI	AL	method	limit/base	current	history1	history2
Calcium	ppm	ASTM D5185(m)	>100	3		
Magnesium	ppm	ASTM D5185(m)	>40	<1		
Hardness	mg/L CaCO3	In-house*	<75	8		
				•		



20

15

E 10

300

250

<sup>≝</sup>1500

1000

500 Feb29/2

-eb29/

# **COOLANT REPORT**

