

**Chem-Ecol** 

# **OIL ANALYSIS REPORT**

## Sample Rating Trend

SAMPLE INFORMATION method limit/base







A2403134 Component Unknown Component Fluid CHEM-ECOL TOOL OIL 1002 (--- GAL)

#### DIAGNOSIS


## Recommendation


We certify that this oil is clean, that the additives are at acceptable levels, and that it is suitable for use.


SAMPLE INFORM		method	limit/base	current	nistory i	nistory2
Batch #		Client Info		3039-A		
Department		Client Info		Production		
Production Stage		Client Info		Final		
Sent to WC		Client Info		03/19/2024		
Sample Number		Client Info		E30001710		
Sample Date		Client Info		19 Mar 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185(m)		7		
Chromium	ppm	ASTM D5185(m)		0		
Nickel	ppm	ASTM D5185(m)		0		
Titanium	ppm	ASTM D5185(m)		0		
Silver	ppm	ASTM D5185(m)		0		
Aluminum	ppm	ASTM D5185(m)		0		
Lead	ppm	ASTM D5185(m)		0		
Copper	ppm	ASTM D5185(m)		8		
Tin	ppm	ASTM D5185(m)		0		
Antimony	ppm	ASTM D5185(m)		0		
Vanadium	ppm	ASTM D5185(m)		0		
Beryllium	ppm	ASTM D5185(m)		0		
Cadmium	ppm	ASTM D5185(m)		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185(m)		0		
Barium	ppm	ASTM D5185(m)		1		
Molybdenum	ppm	ASTM D5185(m)		0		
Manganese	ppm	ASTM D5185(m)		0		
Magnesium	ppm	ASTM D5185(m)		3		
Calcium	ppm	ASTM D5185(m)		44		
Phosphorus	ppm	ASTM D5185(m)		245		
Zinc	ppm	ASTM D5185(m)		246		
Sulfur	ppm	ASTM D5185(m)		23345		
Lithium	ppm	ASTM D5185(m)		<1		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185(m)		5		
Sodium	ppm	ASTM D5185(m)		2		
Potassium	ppm	ASTM D5185(m)	>20	0		
Water	%	ASTM D6304*		0.003		
ppm Water	ppm	ASTM D6304*		30		



# **OIL ANALYSIS REPORT**







FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	869		
Particles >6µm		ASTM D7647	>640	222		
Particles >14µm		ASTM D7647	>160	13		
Particles >21µm		ASTM D7647	>40	4		
Particles >38µm		ASTM D7647	>10	1		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>19/16/14	17/15/11		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D974*		0.83		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	Visual*	NONE	NONE		
Yellow Metal	scalar	Visual*	NONE	NONE		
Precipitate	scalar	Visual*	NONE	NONE		
Silt	scalar	Visual*	NONE	NONE		
Debris	scalar	Visual*	NONE	NONE		
Sand/Dirt	scalar	Visual*	NONE	NONE		
Appearance	scalar	Visual*	NORML	NORML		
Odor	scalar	Visual*	NORML	NORML		
Emulsified Water	scalar	Visual*		NEG		
Free Water	scalar	Visual*		NEG		
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D7279(m)	46	49.8		
Visc @ 100°C	cSt	ASTM D7279(m)		8.0		
Viscosity Index (VI)	Scale	ASTM D2270*		130		
SAMPLE IMAGES		method	limit/base	current	history1	history2
Color					no image	no image
Bottom				(use, 10 P)	no image	no image

: WearCheck - C8-1175 Appleby Line, Burlington, ON L7L 5H9 Environmental 360 Solutions Ltd. Sample No. : E30001710 Received : 21 Mar 2024 640 Victoria Street Lab Number : 02623849 Tested : 22 Mar 2024 Cobourg, ON ISO 17025:2017 Accredited Laboratory Unique Number : 5748968 Diagnosed : 25 Mar 2024 - Tatiana Sorkina CA K9A 5H5 Test Package : IND 2 (Additional Tests: KF, KV100, PrtCount, TAN Man, VI) Contact: Tatiana Sorkina To discuss this sample report, contact Customer Service at 1-905-372-2251. tsorkina@e360s.ca T: (800)263-3939 Test denoted (\*) outside scope of accreditation, (m) method modified, (e) tested at external lab. Validity of results and interpretation are based on the sample and information as supplied. F: (905)373-4950